



Smart concept; Smart design

Bright & Compact



Light Output **2500 lm**

Front Exhaust

USB Display

AV Mute
Slide Lens Shutter

W9/X9/S9 offers not just a stylish new design, but great performance as well. Its 2500 lumens allows for use in bright light conditions. Simple functions such as USB Display and Auto Source Search allow you to use the projector very easily.

- 5000 hour *E-TORL long-life lamp
- Quick Start-up 5 sec / Instant Off function
- Low standby power consumption (0,4W in Standby)
- 60 inch projection at 1.8m

*E-TORL Epson-Twin Optimize Reflection Lamp



Multimedia Projector EB-S9/EB-X9/EB-W9



AV Mute Slide Lens Shutter

Mute is achieved easily by closing the slide cover. This is convenient for situations like writing memos on the white board when using it as a screen, or even when you want to take a short break.



Front Exhaust

Positioning the projector exhaust in the front of the projector means no irritating hot air flow affecting the audience during desktop usage.

USB Display for Windows & Mac PC


Projection begins immediately by simply connecting the projector to a PC using the included USB cable. It's also possible to operate the mouse and page up/down between presentation pages with the remote controller.



| SUPPLIED ACCESSORIES | |
|---|----------------|
| Power Cable 1.8m | |
| Remote Control | |
| With AA type alkaline batteries x 2pcs | |
| Computer Cable | |
| 1.8m <6 ft>, AHD-15 pin type slim-cable | |
| Storage Case | |
| Password Protect Sticker | |
| Owner's Manual | |
| OPTIONAL ACCESSORIES | |
| ELPLP58 | Spare Lamp |
| ELPAF25 | Air Filter Set |

| SPECIFICATIONS | | | EB-S9 | EB-X9 | EB-W9 |
|-------------------------------------|-----------------------------------|--|--|----------------------------------|---------------------------------|
| Specification of Main Parts | LCD | Size | 0.55 inch (x 3) | 0.55 inch (x 3) | 0.59 inch (x 3) |
| | | Pixel Number | 480,000 dots (800 x 600) x 3 | 786,432 dots (1024 x 768) x 3 | 1,024,000 dots (1280 x 800) x 3 |
| | | Native Resolution | SVGA | XGA | WXGA |
| | Projection Lens | | Manual focus & 1.35x digital zoom | Manual focus & 1.2x optical zoom | |
| | | F=1.44 / F=16.6mm | F=1.58 - 1.72 / F=16.9 - 20.28mm | | |
| Lamp | Type | 200W UHE | | | |
| | Life | 4000 hours (Power consumption: Normal) / 5000 hours (Power consumption: Eco) | | | |
| Screen Size | | 30 to 350 inch [0.87 to 10.5m] | 30 to 300 inch [0.9 to 9.0m] | 33 to 318 inch [0.9 to 9.0m] | |
| Offset | | 8:1 | | 6:1 | |
| Light Output* | Brightness Control Normal / Eco | | 2500 lm / 1960 lm | | |
| Color Light Output* | | | 2500 lm / 1960 lm | | |
| Contrast* | | 2000:1 | | | |
| Sound Output | | 1W monaural | | | |
| Analog RGB | Input Terminal | Video | D-sub 15-pin x 1 | | |
| | | Audio | Stereo Mini x 1 | | |
| | Output Terminal | Video | D-sub 15-pin x 1 | | |
| | | Audio | Stereo Mini x 1 | | |
| Video | Input Terminal | Video | Composite Video: RCA (Yellow) x 1 | | |
| | | | S-Video: Mini DIN x 1 | | |
| | | | Component Video: D-sub 15-pin x1 (in common with Analog RGB connector) | | |
| | | RGB Video: D-sub 15-pin x1 (in common with Analog RGB connector) | | | |
| | Audio | Stereo Mini x 1 (in common with Analog RGB Audio terminal) | | | |
| Control | | Terminal | USB Type B x 1 | | |
| Operating Temperature | | 5°C to 35°C <41°F to 95°F> | | | |
| Operating Altitude | | Up to 7,500 feet <2,286m> (over 4,921 feet <1,500m> area: with High Altitude mode) | | | |
| Start-Up Period | | About 5 sec. | | | |
| Direct Power On | | Yes | | | |
| Cool-Down Period | | Instant off | | | |
| Power Supply Voltage | | 100 - 240V AC +/- 10%, 50/60Hz | | | |
| Power Consumption | 100-120V | Lamp on | 280W | | |
| | | Stand by | 0.3W (Communication Off) | | |
| | 220-240V | Lamp on | 265W | | |
| | | Stand by | 0.4W (Communication Off) | | |
| Dimensions Exclude Feet (D x W x H) | | 228 x 295 x 77 | | | |
| Weight | | Approx. 5.1 lbs. / 2.3 kg | | | |
| Fan Noise | Brightness Control : Normal / Eco | | 37dB / 29dB | | |

CONNECTOR PANEL



| CONNECTOR PANEL | |
|-----------------|----------------|
| 1 | Audio Out |
| 2 | Audio Input |
| 3 | S-Video Input |
| 4 | Video Input |
| 5 | USB (Type B) |
| 6 | Computer Input |
| 7 | Monitor Out |

*Light Output / Color Light Output / Contrast — Color mode: Dynamic, Zoom: Wide

PROJECTION DISTANCE (EB-S9)

| 4:3 Screen size | Shortest (Wide) | Longest (Tele) | Offset (Wide) | Offset (Tele) |
|---|-----------------|----------------|---------------|---------------|
| X (screen size / dimension) | Y (cm / inch) | | Z (cm / inch) | Z (cm / inch) |
| 60" / 120 cm x 91 cm 47.2" x 35.4" | 177 / 70 | 240 / 95 | 10 / 3,9 | 3 / 1 |
| 80" / 160 cm x 120 cm 63.0" x 47.2" | 237 / 93 | 321 / 126 | 13 / 5,2 | 3 / 1,3 |
| 100" / 200 cm x 150 cm 78.7" x 59.1" | 297 / 117 | 402 / 158 | 17 / 6,5 | 4 / 1,7 |
| 200" / 410 cm x 300 cm 161.4" x 118.1" | 597 / 235 | 807 / 318 | 33 / 13,1 | 9 / 3,4 |

PROJECTION DISTANCE (EB-X9)

| 4:3 Screen size | Shortest (Wide) | Longest (Tele) | Offset |
|---|-----------------|----------------|---------------|
| X (screen size / dimension) | Y (cm / inch) | | Z (cm / inch) |
| 60" / 120cm x 91cm 47.2" x 35.4" | 180 / 71 | 217 / 85 | 10 / 4 |
| 80" / 160 cm x 120 cm 63.0" x 47.2" | 241 / 95 | 290 / 114 | 14 / 5,3 |
| 100" / 200 cm x 150 cm 78.8" x 59.1" | 302 / 119 | 363 / 143 | 17 / 6,7 |
| 200" / 410 cm x 300 cm 161.4" x 118.1" | 607 / 239 | 729 / 287 | 34 / 13,3 |

PROJECTION DISTANCE (EB-W9)

| 16:10 Screen size | Shortest (Wide) | Longest (Tele) | Offset |
|---|-----------------|----------------|---------------|
| X (screen size / dimension) | Y (cm / inch) | | Z (cm / inch) |
| 60" / 130 cm x 81 cm 51.0" x 32.0" | 168 / 66 | 202 / 79 | 12 / 4,5 |
| 80" / 170 cm x 110 cm 67.0" x 43.0" | 225 / 88 | 270 / 106 | 15 / 6,1 |
| 100" / 220 cm x 130 cm 87.0" x 51.0" | 281 / 111 | 338 / 133 | 19 / 7,6 |
| 200" / 430 cm x 270 cm 169.0" x 106.0" | 566 / 223 | 680 / 268 | 38 / 15,1 |