

Maximum Flexibility for Customized Installations



Optoma's TX7000 provides performance and flexibility to meet the most demanding large-venue installation challenges. Powered with 4800 ANSI lumens and the latest in image and color enhancement technologies, the TX7000 ensures excellence in projection performance. Standard, long and short throw lens options, optimized with PureOptics ED-glass lens elements, create consistently high picture quality at a wide range of projection distances. Vertical and horizontal lens shift further increases the extensive range of installation options. With its wide array of inputs and management options, the TX7000 is your ideal solution for large-venue projection needs.

3D content can be viewed with active LCD shutter glasses when the projector is connected to a computer with a compatible 3D graphics card. Please visit www.optoma.com for more information.

TX7000 FEATURES

- ❑ 4200 ANSI lumens of brightness project crystal clear images that are easily viewable by audiences seated in large venues such as auditoriums and lecture halls
- ❑ Native WXGA resolution is an ideal match for widescreen PCs and laptops
- ❑ Flexible projector placement with extensive vertical and horizontal lens shift
- ❑ Three lens choices with easy-to-change bayonet mounts create a wide range of projection distances and image sizes
- ❑ Remote monitoring and control capabilities over a LAN network via integrated RJ45 connection – compatible with Crestron RoomView™
- ❑ Complete security features protect projector settings and lock out unauthorized users

TX7000 Installation Projector

Specifications

Display Technology:	Single 0.7" DarkChip3™ DLP® Technology by Texas Instruments
Resolution:	Native XGA (1024 x 768)
Maximum Resolution:	UXGA (1600 x 1200)
Brightness (Typical):	4800 ANSI Lumens
Contrast Ratio:	2000:1 (Full On/Full Off)
Lamp Type:	330W P-VIP
Lamp Life (STD/Bright)*:	Estimated at 3000/2000 Hours
Noise Level:	31dB
Remote Control:	Fully Featured IR Remote Control with Mouse and Laser Pointer
Computer Compatibility:	UXGA, SXGA+, WXGA, SXGA, XGA, SVGA, VGA Resized, VESA, PC and Macintosh Compatible
Video Compatibility:	NTSC, PAL, SECAM, SDTV (480i/576i), EDTV (480p/576p), HDTV (720p, 1080i/p)
3D Compatibility:	120Hz Frame Sequential 3D for Resolutions Up to 720p, 60Hz Field Sequential 3D for Resolutions Up to 480i
Monitor Loop Through:	D-sub 15-pin VGA Output (Functional in Both Normal and 5W Standby Modes)
Aspect Ratio:	Native 4:3 and 16:9 Compatible
User Controls:	Complete On-Screen Menu Adjustments in 23 Languages
Keystone Correction:	± 30° Vertical
Lens Shift:	Vertical -15% to +50% Image Height, Horizontal ±10% Image Width
Power Supply:	AC Input 100 - 240V, 50-60 Hz, Auto-Switching
Power Consumption:	430 Watts (Bright), 390 Watts (STD), <1 Watt (Standby)
Weight:	18.1 lbs (8.2 kg) w/o Lens
Dimensions (W x H x D):	16.9" x 7.1" x 13.4" (430 x 181 x 340 mm)
Operating Temperature:	41 - 104°F (5 - 40°C), 85% Max Humidity, Adjustable Fan Speed for High Altitude Application
Displayable Colors:	1.07 Billion
Projection Method:	Front, Rear, Ceiling Mount, Table Top
Uniformity:	85%
Security:	One Kensington® Lock Port, Keypad Lock, Security Bar
I/O Connectors:	HDMI, DVI-D w/ HDCP, Two VGA-In, VGA-Out, Component Video, S-Video, Composite Video, Five BNC (RGBHV/YPbPr), Three Stereo Mini Jack Audio-In, Two RCA Stereo Audio-In, Audio-Out, USB, RS-232, RJ45, and Two +12V Triggers
Standard Accessories:	AC Power Cord, VGA to VGA Cable, USB Cable, Remote Control, Batteries for Remote, CD-ROM User's Manual, Quick Start Card and Warranty Card
Optional Accessories:	Lens Throw Options, Wireless Dongle, Ceiling Mount, S-Video Cable, Audio-Out Adapter, HDMI Cable, DVI Cable, HDMI Cable, DVI Cable, and Panoview™ Series Screens
Warranty:	3 Years Optoma Express Replacement Service, 1 Year on Lamp
UPC:	796435 41 174 9

www.optoma.com

* Lamp life is dependent upon many factors, including lamp mode, display mode, usage, environmental conditions and more. Lamp brightness can decrease over time.

Lens Throw Options (PureOptics)

	Standard Throw Lens	Long Throw Lens	Short Throw Lens
Throw Ratio (Distance/Width)	1.60 to 2.00:1	2.03 to 3.05:1	0.80:1
Projection Distance	4.9' to 23.0' (1.5 to 7m)	6.6' to 65.6' (2 to 20m)	1.6' to 9.8' (0.5 to 3m)
Image Size (Diagonal)	36.8" to 216" (0.93 to 5.49m)	30.6" to 457" (0.78 to 11.6m)	30.0" to 184" (0.76 to 4.67m)
Projection Lens	F-2.46-2.56, f-22.8-28.5 mm, 1.25x Manual Zoom and Focus	F-2.5-3.1, f-28.5-42.75 mm, 1.5x Manual Zoom and Focus	F-2.5, f-11.5 mm, Manual Focus
Weight w/Projector	18.9 lbs (8.6 kg)	18.9 lbs (8.6 kg)	19.1 lbs (8.7 kg)
Part Number	BX-DL200	BX-DL300	BX-DL080

