XD200/SD200 COLORVIEW PROJECTORS

FULLY FEATURED, YET PORTABLE

A BRILLIANT COMBINATION











2000 ANSI LUMENS

6.6 Pounds

DIGITAL KEYSTONE Adjustment

DCDI TECHNOLOGY FOR Cutting-Edge Video The XD200/SD200 ColorView projectors from Mitsubishi are powerhouse projectors that you can carry with confidence. Truly in a class by themselves, the XD200/SD200 are the first DLP[™] projectors in the industry to incorporate both the ColorView Natural Color Matrix and sRGB color compliance for vivid and uniform color reproduction.

- Exclusive, award-winning ColorView Natural Color Matrix for rich, vivid colors
- sRGB color profile technology ensures standard, uniform color reproduction regardless of the type of display used
- Integrated Faroudja technology features Emmy® award-winning Direction Correlational Deinterlacing (DCDi) for smooth and natural-looking images
- Picture-In-Picture with smooth video playback on computer background
- Three-year parts and labor warranty and 90-day warranty on the lamp (both warranties available in U.S. and Canada), toll-free technical support, plus an Express Replacement Assistance (ERA) program (three-years XD200; two-years SD200) that guarantees free replacement product shipped overnight for next business day delivery when and where available



XD200/SD200

ColorView

COLORVIEW™ PROJECTORS

COLORVIEW™ NATURAL COLOR MATRIX

Mitsubishi's award-winning ColorView enables the

ColorView enables the XD200/SD200 to produce vivid colors that precisely match their real-life counterparts, as well as giving you the ability to precisely adjust color saturation and control color tones.





With ColorView


Without ColorView

WITH sRGB

Developed to ensure standard, uniform color reproduction regardless of the type of display used, sRGB color profile uses color coordinates common to all display technologies. As a result, it eliminates the hue variations that occur between different display systems and accurately matches the way colors look in real life.



INPUT AND DUTPUT TERMINALS



1. Video/audio input

- 2.PC audio input
- 3.PC analog RGB input (mini D-Sub 15P)
- 4.PC analog RGB output (mini D-Sub 15P)
- 5.PC audio output
- 6.RS-232C input (Din-9P)

SPECIFICATIONS



Display Technology 0.7" single chip digital micro device with R,G,B,W color wheel (W-52 ty Resolution XGA 1024 x 768, 500 video lines SVGA 800 x 600, 500 vide Brightness 2000 ANSI Lumens Colors 16,770,000 colors Contrast Ratio 450:1 typical Projection Lens F = 2.5 - 3.0 100": 3.3m (vide) Zoom/Focus Manual zoom and manual focus lens Picture Size 40"~ 300" Lamp 210 W high-performance compact lamp Computer Compatibility VGA ~ SXGA 640 x 480 ~ 1024 x 768, VGA ~ XGA 640 x 480 ~ 80 Compressed 1280 x 1024, zoom researd 1280 x 1024 x zoom researd 1280 x 1024, zoom researd 128	
Brightness 2000 ANSI Lumens Colors 16,770,000 colors Contrast Ratio 450:1 typical Projection Lens F = 2.5 - 3.0 100": 3.3m (wide) Zoom/Focus Manual zoom and manual focus lens Picture Size 40"~ 300" Lamp 210 W high-performance compact lamp Computer Compatibility VGA ~ SXGA 640 x 480 ~ 1024 x 768, Sync on green available VGA ~ XGA 640 x 480 ~ 80 Video Compatibility VISC/NTSC 4.43/PAL (including PAL-M, NJ/SECAM/PAL-60/DVD (comp 480P (525i, 525P) HD (1080i, 720P) Input Terminals RGB: mini D-sub 15 pin x 2, Audio: stereo mini jack x 2 (3.5 mm), Video: RCA x 2 = s video x 2, Audio: stereo mini jack x 2 (3.5 mm), Video: RCA x 2 = s video x 2, Audio: stereo mini jack x 2 (3.5 mm) Output Terminals RGB: mini D-sub 15, Audio: stereo mini jack x 3 (3.5 mm), Video: RCA x 2 = s video x 2, Audio: stereo mini jack x 2 (3.5 mm) Output Terminals RGB: mini D-sub 15, Audio: stereo mini jack x 3 (3.5 mm), Video: RCA x 2 = s video x 2, Audio: stereo mini jack x 3 (3.5 mm) Communication Terminals Mouse output x 1 : Min Din9-pin (PS2 mouse, USB mouse) Audio Speaker 2 W Mono Scanning Rates Horizontal: 15 - 91 kHz, Vertical: 50 - 85 Hz, Dot clock: max. 140 MI laser pointer; wireless remote Power Consumption 280 W Dimension	pe)
Colors 16,770,000 colors Contrast Ratio 450:1 typical Projection Lens F = 2.5 - 3.0 100": 3.3m (wide) Zoom/Focus Manual zoom and manual focus lens Picture Size 40"~ 300" Lamp 210 W high-performance compact lamp Computer Compatibility VGA ~ SXGA 640 x 480 ~ 1024 x 768, VGA ~ XGA 640 x 480 ~ 80 compressed 1280 x 1024, compressed 1024 x 76 Sync on green available Sync on green available Sync on green available Video Compatibility NTSC/NTSC 4.43/PAL (including PAL-M, N)/SECAM/PAL-60/DVD (comp 480P (525i, 525P) HD (1080i, 720P) Input Terminals RGB: mini D-sub 15 pin x 2, Audio: stereo mini jack x 1 (3.5 mm), Video: RCA x 2 = S video x 2, Audio: stereo mini jack x2 (3.5 mm) Output Terminals RGB: mini D-sub 15, Audio: stereo mini jack (3.5 mm) Variable Communication Terminals Mouse output x 1 : Min Din9-pin (PS2 mouse, USB mouse) Audio Speaker 2 W Mono Scanning Rates Horizontal: 15 - 91 kHz, Vertical: 50 - 85 Hz, Dot clock: max. 140 Mi Fan Noise 34 duB Projector full control; PS2/Mac cursor control; USB mouse compatibil Laser Pointer Iaser Pointer 280 W Dimensions (W x H x D) 11.8" x 3.5" x 9.7" (300 x 90 x 245mm) Weight 6	eo lines
Contrast Ratio 450:1 typical Projection Lens F = 2.5 - 3.0 100": 3.3m (wide) Zoom/Focus Manual zoom and manual focus lens Picture Size 40"~ 300" Lamp 210 W high-performance compact lamp Computer Compatibility VGA ~ SXGA 640 x 480 ~ 1024 x 768, compressed 1280 x 1024, compressed 1024 x 77 Sync on green available Sync on green available Video Compatibility NTSC/NTSC 4.43/PAL (including PAL-M, NJ/SECAM/PAL-60/DVD (comp 480P (525i, 525P) HD (1080i, 720P) Input Terminals RGB: mini D-sub 15 pin x 2, Audio: stereo mini jack x 1 (3.5 mm), Video: RCA x 2 = S video x 2, Audio: stereo mini jack x 2 (3.5 mm) Output Terminals RGB: mini D-sub 15, Audio: stereo mini jack x 3 (3.5 mm) Variable Communication Terminals Mouse output x 1 : Min Din9-pin (PS2 mouse, USB mouse) Audio Speaker 2 W Mono Scanning Rates Horizontal: 15 - 91 kHz, Vertical: 50 - 85 Hz, Dot clock: max. 140 Mi Laser Pointer Projector full control; PS2/Mac cursor control; USB mouse compatibil Laser Pointer 280 W Dimensions (W x H x D) 11.8" x 3.5" x 9.7" (300 x 90 x 245mm) Weight 6.6 lbs (3.0 kg) Power Supply AC 100 ~ 220V / ±10%, 50/60 Hz Safety Approvals CSA, CSA NRT L/C, FCC Class-B (good for hor	
Projection Lens F = 2.5 - 3.0 100": 3.3m (wide) Zoom/Focus Manual zoom and manual focus lens Picture Size 40" - 300" Lamp 210 W high-performance compact lamp Computer Compatibility VGA ~ SXGA 640 x 480 ~ 1024 x 768, VGA ~ XGA 640 x 480 ~ 80 compressed 1280 x 1024, compressed 1024 x 76 Sync on green available Video Compatibility NTSC/NTSC 4.43/PAL (including PAL-M, N)/SECAM/PAL-60/DVD (comp 480P (525i, 525P) HD (1080i, 720P) Input Terminals RGB: mini D-sub 15 pin x 2, Audio: stereo mini jack x 1 (3.5 mm), Video: RCA x 2 = S video x 2, Audio: stereo mini jack x 2 (3.5 mm) Output Terminals RGB: mini D-sub 15, Audio: stereo mini jack x 2 (3.5 mm) Audio Speaker 2 W Mono Scanning Rates Horizontal: 15 - 91 kHz, Vertical: 50 - 85 Hz, Dot clock: max. 140 Mi Fan Noise 34 dB Remote Control/ Projector full control; PS2/Mac cursor control; USB mouse compatibil laser pointer; wireless remote Power Consumption 280 W Dimensions (W x H x D) 11.8" x 3.5" x 9.7" (300 x 90 x 245mm) Weight 6.6 lbs (3.0 kg) Power Supply AC 100 ~ 220V / ±10%, 50/60 Hz Safety Approvals CSA, CSA NRT L/C, FCC Class-B (good for home use) Warranty <	
Zoom/Focus Manual zoom and manual focus lens Picture Size 40"- 300" Lamp 210 W high-performance compact lamp Computer Compatibility VGA ~ SXGA 640 x 480 ~ 1024 x 768, VGA ~ XGA 640 x 480 ~ 80 compressed 1280 x 1024, compressed 1024 x 76 sync on green available Video Compatibility VGA ~ SXGA 640 x 480 ~ 1024 x 768, VGA ~ XGA 640 x 480 ~ 80 compressed 1280 x 1024, compressed 1024 x 76 sync on green available Video Compatibility NTSC/NTSC 4.43/PAL (including PAL-M, NJ/SECAM/PAL-60/DVD (comp 480P (525i, 525P) HD (1080i, 720P) Input Terminals RGB: mini D-sub 15 pin x 2, Audio: stereo mini jack x 1 (3.5 mm), Video: RCA x 2 = S video x 2, Audio: stereo mini jack x 2 (3.5 mm) Output Terminals RGB: mini D-sub 15, Audio: stereo mini jack (3.5 mm) Variable Communication Terminals Mouse output x 1 : Min Din9-pin (PS2 mouse, USB mouse) Audio Speaker 2 W Mono Scanning Rates Horizontal: 15 - 91 kHz, Vertical: 50 - 85 Hz, Dot clock: max. 140 Mi Fan Noise 34 dB Remote Control/ Projector full control; PS2/Mac cursor control; USB mouse compatibil laser pointer; wireless remote Power Consumption 280 W Dimensions (W x H x D) 11.8" x 3.5" x 9.7" (300 x 90 x 245mm) Weight 6.6 lbs (3.0 kg) Power Supply AC 100 ~ 220V / ±1	
Picture Size 40"~ 300" Lamp 210 W high-performance compact lamp Computer Compatibility VGA ~ SXGA 640 x 480 ~ 1024 x 768, vGA ~ XGA 640 x 480 ~ 80 compressed 1280 x 1024, compressed 1024 x 76 Sync on green available Video Compatibility VTSC/NTSC 4.43/PAL (including PAL-M, NJ/SECAM/PAL-60/DVD (comp 480P (525i, 525P) HD (1080i, 720P) Input Terminals RGB: mini D-sub 15 pin x 2, Audio: stereo mini jack x 1 (3.5 mm), Video: RCA x 2 = S video x 2, Audio: stereo mini jack x2 (3.5 mm) Output Terminals RGB: mini D-sub 15, Audio: stereo mini jack (3.5 mm) Variable Communication Terminals Mouse output x 1 : Min Din9-pin (PS2 mouse, USB mouse) Audio Speaker 2 W Mono Scanning Rates Horizontal: 15 - 91 kHz, Vertical: 50 - 85 Hz, Dot clock: max. 140 Mi Fan Noise 34 dB Remote Control/ Projector full control; PS2/Mac cursor control; USB mouse compatibl laser pointer; wireless remote Power Consumption 280 W Dimensions (W x H x D) 11.8" x 3.5" x 9.7" (300 x 90 x 245mm) Weight 6.6 lbs (3.0 kg) Power Supply AC 100 ~ 220V / ±10%, 50/60 Hz Safety Approvals CSA, CSA NRT L/C, FCC Class-B (good for home use) Warranty Three-year parts and labor warranty and 90 day warranty on lamp (both warranty con lamp (both warranty con	
Lamp 210 W high-performance compact lamp Computer Compatibility VGA ~ SXGA 640 x 480 ~ 1024 x 768, compressed 1024 x 76 Sync on green available Sync on green available Video Compatibility NTSC/NTSC 4.43/PAL (including PAL-M, NJ/SECAM/PAL-60/DVD (comp 480P (5251, 525P) HD (1080i, 720P) Input Terminals RGB: mini D-sub 15 pin x 2, Audio: stereo mini jack x 1 (3.5 mm), Video: RCA x 2 = S video x 2, Audio: stereo mini jack x2 (3.5 mm) Output Terminals RGB: mini D-sub 15, Audio: stereo mini jack (3.5 mm) Variable Communication Terminals Mouse output x 1 : Min Din9-pin (PS2 mouse, USB mouse) Audio Speaker 2 W Mono Scanning Rates Horizontal: 15 - 91 kHz, Vertical: 50 - 85 Hz, Dot clock: max. 140 Mi Fan Noise 34 dB Projector full control; PS2/Mac cursor control; USB mouse compatibl Laser Pointer Projector full control; PS2/Mac cursor control; USB mouse compatibl Power Consumption 280 W Dimensions (W x H x D) 11.8" x 3.5" x 9.7" (300 x 90 x 245mm) Weight 6.6 lbs (3.0 kg) Power Supply AC 100 ~ 220V / ±10%, 50/60 Hz Safety Approvals CSA, CSA NRT L/C, FCC Class-B (good for home use) Warranty Three-year parts and labor warranty and 90 day warranty on lamp (both warranty	
Computer Compatibility VGA ~ SXGA 640 x 480 ~ 1024 x 768, compressed 1280 x 1024, Sync on green available VGA ~ XGA 640 x 480 ~ 80 compressed 1280 x 1024, Sync on green available Video Compatibility NTSC/NTSC 4.43/PAL (including PAL-M, N)/SECAM/PAL-60/DVD (comp 480P (525i, 525P) HD (1080i, 720P) Input Terminals RGB: mini D-sub 15 pin x 2, Audio: stereo mini jack x 1 (3.5 mm), Video: RCA x 2 = S video x 2, Audio: stereo mini jack x 2 (3.5 mm) Output Terminals RGB: mini D-sub 15, Audio: stereo mini jack x 2 (3.5 mm) Output Terminals Mouse output x 1 : Min Din9-pin (PS2 mouse, USB mouse) Audio Speaker 2 W Mono Scanning Rates Horizontal: 15 - 91 kHz, Vertical: 50 - 85 Hz, Dot clock: max. 140 MI Fan Noise 34 dB Remote Control/ Projector full control; PS2/Mac cursor control; USB mouse compatibil laser pointer; wireless remote Power Consumption 280 W Dimensions (W x H x D) 11.8" x 3.5" x 9.7" (300 x 90 x 245mm) Weight 6.6 lbs (3.0 kg) Power Supply AC 100 ~ 220V / ±10%, 50/60 Hz Safety Approvals CSA, CSA NRT L/C, FCC Class-B (good for home use) Warranty Three-year parts and labor warranty and 90 day warranty on lamp (both warranty marked mark	
compressed 1280 x 1024, Sync on green available compressed 1024 x 76 Sync on green available Video Compatibility NTSC/NTSC 4.43/PAL (including PAL-M, N)/SECAM/PAL-60/DVD (comp 480P (525i, 525P) HD (1080i, 720P) Input Terminals RGB: mini D-sub 15 pin x 2, Audio: stereo mini jack x 1 (3.5 mm), Video: RCA x 2 = S video x 2, Audio: stereo mini jack x 2 (3.5 mm) Output Terminals RGB: mini D-sub 15, Audio: stereo mini jack x 2 (3.5 mm) Output Terminals Mouse output x 1 : Min Din9-pin (PS2 mouse, USB mouse) Audio Speaker 2 W Mono Scanning Rates Horizontal: 15 - 91 kHz, Vertical: 50 - 85 Hz, Dot clock: max. 140 MI Fan Noise 34 dB Remote Control/ Projector full control; PS2/Mac cursor control; USB mouse compatibl laser pointer Power Consumption 280 W Dimensions (W x H x D) 11.8" x 3.5" x 9.7" (300 x 90 x 245mm) Weight 6.6 lbs (3.0 kg) Power Supply AC 100 ~ 220V / ±10%, 50/60 Hz Safety Approvals CSA, CSA NRT L/C, FCC Class-B (good for home use) Warranty Three-year parts and labor warranty and 90 day warranty on lamp (both warranty	
480P (525ĭ, 525P) HD (1080i, 720P) Input Terminals RGB: mini D-sub 15 pin x 2, Audio: stereo mini jack x 1 (3.5 mm), Video: RCA x 2 = S video x 2, Audio: stereo mini jack x2 (3.5 mm) Output Terminals RGB: mini D-sub 15, Audio: stereo mini jack (3.5 mm) Variable Communication Terminals Mouse output x 1 : Min Din9-pin (PS2 mouse, USB mouse) Audio Speaker 2 W Mono Scanning Rates Horizontal: 15 - 91 kHz, Vertical: 50 - 85 Hz, Dot clock: max. 140 MI Fan Noise 34 dB Remote Control/ Projector full control; PS2/Mac cursor control; USB mouse compatibl Laser Pointer 280 W Dimensions (W x H x D) 11.8" x 3.5" x 9.7" (300 x 90 x 245mm) Weight 6.6 lbs (3.0 kg) Power Supply AC 100 ~ 220V / ±10%, 50/60 Hz Safety Approvals CSA, CSA NRT L/C, FCC Class-B (good for home use) Warranty Three-year parts and labor warranty and 90 day warranty on lamp (both warranty	68,
Video: RCA x 2 = S video x 2, Audio: stereo mini jack x2 (3.5 mm) Output Terminals RGB: mini D-sub 15, Audio: stereo mini jack (3.5 mm) Variable Communication Terminals Mouse output x 1 : Min Din9-pin (PS2 mouse, USB mouse) Audio Speaker 2 W Mono Scanning Rates Horizontal: 15 - 91 kHz, Vertical: 50 - 85 Hz, Dot clock: max. 140 MI Fan Noise 34 dB Remote Control/ Projector full control; PS2/Mac cursor control; USB mouse compatibl Laser Pointer 280 W Dimensions (W x H x D) 11.8" x 3.5" x 9.7" (300 x 90 x 245mm) Weight 6.6 lbs (3.0 kg) Power Supply AC 100 ~ 220V / ±10%, 50/60 Hz Safety Approvals CSA, CSA NRT L/C, FCC Class-B (good for home use) Warranty Three-year parts and labor warranty and 90 day warranty on lamp (both warranty	onent)
Communication Terminals Mouse output x 1 : Min Din9-pin (PS2 mouse, USB mouse) Audio Speaker 2 W Mono Scanning Rates Horizontal: 15 - 91 kHz, Vertical: 50 - 85 Hz, Dot clock: max. 140 MI Fan Noise 34 dB Remote Control/ Projector full control; PS2/Mac cursor control; USB mouse compatible Laser Pointer 280 W Dimensions (W x H x D) 11.8" x 3.5" x 9.7" (300 x 90 x 245mm) Weight 6.6 lbs (3.0 kg) Power Supply AC 100 ~ 220V / ±10%, 50/60 Hz Safety Approvals CSA, CSA NRT L/C, FCC Class-B (good for home use) Warranty Three-year parts and labor warranty and 90 day warranty on lamp (both warranty	
Audio Speaker 2 W Mono Scanning Rates Horizontal: 15 - 91 kHz, Vertical: 50 - 85 Hz, Dot clock: max. 140 Mł Fan Noise 34 dB Remote Control/ Projector full control; PS2/Mac cursor control; USB mouse compatibl Laser Pointer 280 W Dimensions (W x H x D) 11.8" x 3.5" x 9.7" (300 x 90 x 245mm) Weight 6.6 lbs (3.0 kg) Power Supply AC 100 ~ 220V / ±10%, 50/60 Hz Safety Approvals CSA, CSA NRT L/C, FCC Class-B (good for home use) Warranty Three-year parts and labor warranty and 90 day warranty on lamp (both warranty	
Scanning Rates Horizontal: 15 - 91 kHz, Vertical: 50 - 85 Hz, Dot clock: max. 140 Ml Fan Noise 34 dB Remote Control/ Projector full control; PS2/Mac cursor control; USB mouse compatibl Laser Pointer 280 W Dimensions (W x H x D) 11.8" x 3.5" x 9.7" (300 x 90 x 245mm) Weight 6.6 lbs (3.0 kg) Power Supply AC 100 ~ 220V / ±10%, 50/60 Hz Safety Approvals CSA, CSA NRT L/C, FCC Class-B (good for home use) Warranty Three-year parts and labor warranty and 90 day warranty on lamp (both warranty	
Fan Noise 34 dB Remote Control/ Laser Pointer Projector full control; PS2/Mac cursor control; USB mouse compatible laser pointer; wireless remote Power Consumption 280 W Dimensions (W x H x D) 11.8" x 3.5" x 9.7" (300 x 90 x 245mm) Weight 6.6 lbs (3.0 kg) Power Supply AC 100 ~ 220V / ±10%, 50/60 Hz Safety Approvals CSA, CSA NRT L/C, FCC Class-B (good for home use) Warranty Three-year parts and labor warranty and 90 day warranty on lamp (both warranty	
Remote Control/ Laser Pointer Projector full control; PS2/Mac cursor control; USB mouse compatible laser pointer; wireless remote Power Consumption 280 W Dimensions (W x H x D) 11.8" x 3.5" x 9.7" (300 x 90 x 245mm) Weight 6.6 lbs (3.0 kg) Power Supply AC 100 ~ 220V / ±10%, 50/60 Hz Safety Approvals CSA, CSA NRT L/C, FCC Class-B (good for home use) Warranty Three-year parts and labor warranty and 90 day warranty on lamp (both warranty	Ηz
Laser Pointer laser pointer; wireless remote Power Consumption 280 W Dimensions (W x H x D) 11.8" x 3.5" x 9.7" (300 x 90 x 245mm) Weight 6.6 lbs (3.0 kg) Power Supply AC 100 ~ 220V / ±10%, 50/60 Hz Safety Approvals CSA, CSA NRT L/C, FCC Class-B (good for home use) Warranty Three-year parts and labor warranty and 90 day warranty on lamp (both warranty	
Dimensions (W x H x D) 11.8" x 3.5" x 9.7" (300 x 90 x 245mm) Weight 6.6 lbs (3.0 kg) Power Supply AC 100 ~ 220V / ±10%, 50/60 Hz Safety Approvals CSA, CSA NRT L/C, FCC Class-B (good for home use) Warranty Three-year parts and labor warranty and 90 day warranty on lamp (both warranty	9;
Weight 6.6 lbs (3.0 kg) Power Supply AC 100 ~ 220V / ±10%, 50/60 Hz Safety Approvals CSA, CSA NRT L/C, FCC Class-B (good for home use) Warranty Three-year parts and labor warranty and 90 day warranty on lamp (both warranty	
AC 100 ~ 220V / ±10%, 50/60 Hz Safety Approvals CSA, CSA NRT L/C, FCC Class-B (good for home use) Warranty Three-year parts and labor warranty and 90 day warranty on lamp (both warranty	
Safety Approvals CSA, CSA NRT L/C, FCC Class-B (good for home use) Warranty Three-year parts and labor warranty and 90 day warranty on lamp (both warranty and 90 day warranty 90 day warranty and 90 day warranty 90 day warranty 90 day wara	
Warranty Three-year parts and labor warranty and 90 day warranty on lamp (both warranty	
[three-years XD2OD; two-years SD2OD] that guarantees free replacement pro shipped overnight for next business day delivery when and where available	program
Accessories Standard: AC power cable, video cable, S video cable, audio cable, RGB cable USB cable, remote unit (with battery), soft carrying case, quick sta and user manual Optional: Spare lamp (VTL-XD2DOLP), ceiling mount bracket (XD2OOCM), hard case (X7O-ATA)	, PS2 cable rt guide,
Special features ColorView Natural Color Matrix; sRGB color compliance; DCDi technology; digi adjustment; zoom and focus lens; Picture-In-Picture	al keystone

For more information on the XD200/SD200 or any of Mitsubishi's other projectors or presentation products, contact Mitsubishi Digital Electronics today. Detailed technical specifications available upon request. Projector Part Number: XD200U/SD200U



The above numbers are approximate, and may be slightly different from the actual measurements.

©2002 Mitsubishi Digital Electronics America, Inc. Standard features, options and specifications subject to change without notice. Microsoft, Windows, and the Windows logo are registered trademarks of Microsoft Corporation. Mac and the Mac logo are trademarks of Apple Computer, Inc, registered in the U.S. and other countries. DDD is a trademark of Faroudja, a division of Sage Inc. Digital Light Processing and DLP are trademarks of Texas Instruments, Inc. All other trademarks or registered trademarks are the property of their respective holders.

Printed on 50% recycled paper including 20% post-consumer fibers.

Mitsubishi Digital Electronics America, Inc. Presentation Products Division 9351 Jeronimo Road Irvine, CA 92618 Toll Free: 888-880-6351 email: ppdinfo@mdea.mea.com

www.mitsubishi-presentations.com

Technical Support: Toll Free: 888-307-0309 Email: tsupport@mdea.mea.com

Canada:

Mitsubishi Electric Sales Canada Inc. Information Technologies Group Markham, Ontario 905-475-7728 www.mitsubishielectric.ca