







1200 ANSI LUMENS

6.5 POUNDS

DIGITAL KEYSTONE ADJUSTMENT

PICTURE-IN-PICTURE

600:1 CONTRAST RATIO

SVGA 800 x 600

600 VIEWABLE VIDEO LINES

HDTV-READY

The SL2 ColorView projector from Mitsubishi offers versatile features making it an ideal projector for basic office or entry-level home theater use. It comes packed with 1200 ANSI lumens of brightness with a remarkable 600:1 contrast ratio. And at 800 x 600 resolution and 600 video lines, along with the industry-leading three-year warranty, it takes on any presentation, video games or movies with an unmatched price performance value.

- Exclusive, award-winning ColorView Natural Color Matrix for rich, vivid colors
- sRGB color profile technology ensures standard uniform color reproduction regardless of the type of display used
- 3D CineView™, Mitsubishi's proprietary video technology, significantly reduces flickering, artifacts, crawling, or blinking, with the image as sharp and smooth as its native film
- Fully compatible with Mitsubishi's ProjectorView™ Networking system which enables a company's designated administrator and authorized users to remotely control, monitor, manage, and even diagnose a Mitsubishi projector
- Remarkable 600:1 contrast ratio for rich, deep colors great for home video viewing
- Versatile enough to support one computer and two video inputs simultaneously
- Three-year parts and labor warranty and 90-day warranty on the lamp (both warranties available in U.S. and Canada), toll-free technical support, plus two-year Express Replacement Assistance (ERA) program that guarantees free replacement product shipped overnight for next business day delivery when and where available











#### SPECIFICATIONS

Display Technology

Resolution

Brightness

Contrast Ratio

Projection Lens

Zoom/Focus



#### COLORVIEW™ NATURAL **COLOR MATRIX** Color\/iew

The SL2 produces vivid colors that precisely match MATURAL COLOR their real-life counterparts, as well as giving you the ability to precisely adjust color saturation and control color tones.





Without ColorView

With ColorView

### PRECISE COLOR REPRODUCTION WITH SRGB



Developed to ensure standard, uniform color reproduction regardless of the type of display used, sRGB color profile uses color coordinates common to all display technologies.







#### IRIS® (INTELLIGENT ROOM ILLUMINATION SENSOR)

Room illumination can have a significant effect on the quality and accuracy of color reproduction on-screen. The brighter the room, the duller the color. The SL2's builtin IRIS® automatically detects light volume and color density, automatically adjusting mid-range color tones as required for optimal color reproduction under any lighting conditions.





A change in external light makes the room brighter.

With IRIS

#### INPUT AND DUTPUT TERMINALS



- 1 RS-232C
- PC analog RGB input
- **③** PC analog RGB output
- 4 Audio input
- **6** S-Video input
- **(3**) Video input
- AC power input
- 8 Main power switch

Picture Size	40" ~ 300"	
Lamp	150 W high-performance compact lamp	
Computer Compatibility	VGA ~ SXGA 640 x 480 ~ 800 x 600, co True: 800 x 600, Sync on green available	
Video Compatibility	NTSC/NTSC 4.43/PAL (including PAL-M, HDTV (525p, 720p, 1080i)	
Input Terminals	RGB: mini D-sub 15 pin x 1, Video: RCA + Audio: RCA x 1	

Video Compatibility	NTSC/NTSC 4.43/PAL (including PAL-M, N)/SECAM/PAL-60/DVD (component) HDTV (525p, 720p, 1080i)	
Input Terminals	RGB: mini D-sub 15 pin x 1, Video: RCA + S video x 1, Audio: RCA x 1	
Output Terminals	RGB: mini D-sub 15 pin x 1	
Audio Speakers	1 W Mono	
Scanning Rates	Horizontal: 15 - 69 kHz, Vertical: 50 - 85 Hz, Dot clock: 100 MHz	
Remote Control	Wireless remote control for basic operation	
Power Consumption	230 W	
Dimensions	9.3" x 3.7" x 12.4" (237 x 94 x 315 mm)	
Weight	6.5 lbs. (2.9 kg)	
Power Supply	AC 100 ~ 240V / +10%, 50/60 Hz	
Safety Approvals	CSA, CSA NRT L/C, FCC Class-B	
Warranty	Three-year parts and labor warranty and 90 day warranty on lamp (both warranties available in U.S. and Canada). Also includes a two-year Express Replacement Assistance	

0.7" polysilicon LCD panel x 3

F = 1.9 - 2.2; f = 27 - 32 mm

Manual zoom and manual focus lens

1200 ANSI Lumens

SVGA 800 x 600 native, SXGA 1280 x 1024 max., 600 viewable video lines

 $800 \times 600$ , compressed  $1024 \times 768$ 


Accessories Standard: AC power cable; D-sub RGB cable; RS-232C cable; AV cable; remote control with battery; soft carrying case; lens cap; user and quick reference guide Spare lamp (Part No. VLT-XL1LP), ceiling mount bracket, upgraded carrying cases, ProjectorView" Networking System Special features

ColorView Natural Color Matrix; sRGB color compliance; digital keystone adjustment; zoom and focus lens; Picture-In-Picture; 3D CineView™; ProjectorView Networking System; IRIS® Contrast Control

program that guarantees free replacement projector shipped overnight for next day

For more information on the SL2 or any of Mitsubishi's other projectors or presentation products, contact Mitsubishi Digital Electronics today. Detailed technical specifications available upon request. Projector Part Number: SL2U

delivery when and where available



Screen Diagonal Size (inch)	Distance from scree Maximum zoom (WIDE) (inch)	n (L)/(approximate) Minimum zoom (TELE) (inch)	Height Projected (inch)
30	_	52	1.8
40	59	71	2.4
60	90	106	3.6
80	118	142	4.8
100	150	177	6.0
150	224	268	9.0
200	229	358	12.0
250	374	449	15.0
300	449	535	18.0

The above numbers are approximate, and may be slightly different from the actual

©2002 Mitsubishi Digital Electronics America, Inc. Standard features, options and specifications subject to change without notice. Microsoft, Windows, and the Windows logo are registered trademarks of Microsoft Corporation. Mac and the Mac logo are trademarks of Apple Computer, Inc, registered in the U.S. and other countries. All other trademarks or registered trademarks are the property of their respective holders.



Printed on 50% recycled paper including 20% post-consumer fibers.

## Mitsubishi Digital Electronics America, Inc.

Presentation Products Division 9351 Jeronimo Road Irvine, CA 92618 Toll Free: 888-307-0349

email: ppdinfo@mdea.mea.com

www.mitsubishi-presentations.com

# Technical Support:

Toll Free: 888-307-0309 Email: tsupport@mdea.mea.com

#### Canada:

Mitsubishi Electric Sales Canada Inc. Information Technologies Group

Markham, Ontario 905-475-7728

www.mitsubishielectric.ca