Fully-Featured For Maximum Versatility And Reliability.

True XGA

SXGA Maximum

2200 ANSI Lumens

Color Uniformity Correction

Exclusive, Award-Winning ColorView

Computers And HDTV-Ready The X390 from Mitsubishi Digital Electronics is a high performance XGA LCD projector with a full feature set for reliable, worry-free presentations.

- Up to 2200 ANSI lumens for super bright presentations
- 400:1 contrast ratio for exceptional color depth and clarity

MITSUE

- Polysilicon three-panel LCD system
- Power zoom and focus adjustment
- Projects images from 40 inches to 300 inches; suitable for front, rear and ceiling mount installations
- 250-watt short-arc NSH lamp
- Professional Presentation Features: Simultaneous live picture-in-picture, simultaneous video and RGB sourcing, intuitive on-screen graphic user-interface in seven languages, color temperature, built-in laser pointer, Cineview[™] video line doubler, digital keystone adjustment, and digital zoom
- Exclusive, award-winning Colorview[™] Natural Color Matrix for rich, vivid colors
- Direct access digital keystone correction
- RS-232C communication terminal (PC and MAC) for seamless system integration
- Simple, one-touch auto set-up function; plug and play compatibility supporting two computer and two video inputs simultaneously
- Accepts S-VHS, NTSC, NTSC 4.43, PAL and SECAM video formats, DVD, HDTV-ready and computer inputs from Apple[®], IBM[®], and many workstation computers
- Three-year parts and labor warranty, 90-day warranty on the lamp, toll-free support plus an
 exclusive 3-year Emergency Roadside Assistance (ERA) program that guarantees free replacement
 product shipped overnight for next business-day delivery when and where available














MITSUBISHI X390 DESKTOP PORTABLE XGA LCD COLORVIEW™ PROJECTOR



- 1. Wired Remote Control Input
- 2. RS-232 Input
- 3. USB Input
- 4. Video/Audio Inputs (Composite RCA)
- 5. 2 Audio Inputs (Video)
- 6. Computer Monitor Output
- 7. Computer 1 & 2 In/Component Video
- 8. Power Jack
- 9. Ground Terminal
- 10. Main Power

FULLY-FEATURED VERSATILITY

Brightness

2200 ANSI Lumens

Colors

Exclusive ColorView™

Warranty

3-years

Service

Exclusive 3-year ERA

Connections

Computers and HDTV-Ready

ODECIEICATIONO	111					
SPECIFICATIONS						
Display Technology	1.3" x 3 Polysilicon LCD panel					
Resolution	True XGA 1024 x 768 with compression for SXGA 1280 x 1024 maximum; 540 video lines					
Brightness (ANSI Lumens)	2200					
Colors	Exclusive Mitsubishi ColorView™ Natural Color Matrix supports 16.7 million colors (32-bit). Red, green, blue, cyan, yellow, magenta axis are independently adjustable; includes saturation adjustment.					
Contrast Ratio	400:1 on/off					
Lens	Power zoom and focus. All glass lens assembly. (zoom ratio: 1.26:1) F = 1.8 - 2.2; f = 52- 66 mm					
Picture Size	40" - 300" diagonal (aspect ratio 4:3 default, 16:9 anamorphic video option)					
Picture-In-Picture	Swappable simultaneous live video and computer display (5 P-I-P display modes)					
Lamp	Type: 250-watt short-arc NSH lamp					
Computer Compatibility	PCs, Macintosh® computers; supports sync on green					
Video Compatibility	NTSC, NTSC 4.43, PAL, PAL M, PAL N, SECAM, PAL 60, DVD component video, HDTV-ready up to 1080i					
Input Terminals	 Computer; mini D-sub 15 pin x 2 PC Audio; stereo mini jack x 2 Video; RCA x 1 + SVHS x 1 Video; RCA x 1 + SVHS x 1 Video Audio; stereo RCA x 2 					
Output Terminals	Computer: mini D-sub 15 pin x 1 Audio (3.5 mm)					
Communication Terminals	RS-232C x 1 (direct command is available); Wired remote terminal x 1; USB terminal for mouse; PS/2 (mouse function)					
Scanning Rates	H: 15 - 92 kHz; V: 50 - 85 Hz; Dot Clock: 160 MHz					
Audio	2 x 2W stereo					
Remote Control/ Laser Pointer	Wireless remote with direct input access. Full projector and computer control with built-in mouse and laser pointer.					
Height Adjuster	Two quick release legs (0-7° variable)					
Weight	14.7 lbs. (6.7 kgs) Net					
Dimensions (W x H x D)	11.8 x 5.2 x 14.5" (299 x 133 x 367 mm) (excluding legs and lens)					
Power	AC 100 - 240V ±10%, 50/60 Hz					
Power Consumption	360 watts					
Kensington Lock-Ready	For theft protection					
Safety Approvals	CSA, CSA NRT L/C, FCC Class-A					
Warranty	Three-year parts and labor; 90 days on lamp. Also includes three-year Emergency Roadside Assistance program that guarantees free replacement projector shipped overnight for next business day delivery when and where available.					
Accessories	 Standard AC power cable; RGB cable; RS-232C cable; remote control; wired cable for remote unit; lens cap; user manual; audio/video cable; PS/2 adapter USB cable Optional User replaceable spare lamp (VLT-X400LP), ceiling mount kit (X400CM), Mac adapter, Mac RS-232 adapter; optional lenses are also available 					
Other Special Features	Simultaneous live, swappable, picture-in-picture, simultaneous video and RGB sourcing, intuitive on-screen graphic user interface in seven languages, color temperature, built-in laser pointer, CineView™ Video Line Doubler, direct access digital keystone correction, Point-'n-Zoom Digital Magnification and exclusive ColorView Natural Color Matrix.					
GSA Federal Supply Schedule	e Contract number GS-35F-0592L. For ordering information call 888-307-0308					
For more information on the > Detailed technical specificatio	K390 or any of Mitsubishi's other projectors or presentation products, contact Mitsubishi Digital Electronics today. Ins available upon request.					
Projector Part Number: LVPX	390U H (Screen Height) L (distance between the screen end the band of the excited a)					

STANDARD PROJECTION THROW DISTANCE CHART

Screen			Distance from screen (L)/(Approximate)			
Diagonal Size (inch)	iagonal Size Height Width (inch) (inch) (inch)		Maximum zoom (cm) (inch)		Minimum zoom (cm) (inch)	
40"	24"	32"	155	61"	195	77"
60"	36"	48"	235	92"	296	116"
80"	48"	64"	315	124"	396	156"
100"	60"	80"	394	155"	496	195"
120"	72"	96"	474	187"	597	235"
140"	84"	112"	554	218"	697	274"
160"	96"	128"	634	250"	797	314"
180"	108"	144"	714	281"	898	353"
200"	120"	160"	794	312"	998	393"
300"	180"	240"	1194	470"	-	-

and the head of the projector)

The above numbers are approximate and may be slightly different than the actual measurements

©2001 Mitsubishi Digital Electronics America, Inc. Standard features, options and specifications subject to change without notice. Microsoft, Windows, and the Windows logo are registered trademarks of Microsoft Corporation. Mac and the Mac logo are trademarks of Apple Computer, Inc, registered in the U.S. and other countries. All other trademarks or registered trademarks are the property of their respective holders. Printed on 50% recycled paper including 20% post-consumer fibers, processed chlorine free. Printed with vegetable based inks.

Mitsubishi Digital Electronics America, Inc. Presentation Products Division 9351 Jeronimo Road Irvine, CA 92618 Toll Free: 888-880-6351 email: ppdinfo@mdea.mea.com

Technical Support: Toll Free: 888-307-0309 Email: tsupport@mdea.mea.com Canada: Mitsubishi Electric Sales Canada Inc. Information Technologies Group Markham, Ontario 905-475-7728



PP1087-10/01-5M-LITX390

www.mitsubishi-presentations.com