

Pro9500

HIGH BRIGHTNESS PERFORMANCE PROJECTOR

WITH 3LCD TECHNOLOGY



A Perfect Presentation.

The Pro9500 is an advanced high brightness LCD installation projector which includes 3LCD technology to produce more vibrant colors. The Pro9500 delivers 5000 ANSI lumens, 3500:1 contrast ratio (active IRIS) with a 1024x768 XGA native resolution, allowing it to shine in virtually any lighting situation. The Pro9500 provides maximum mounting flexibility with a wide 1.7x optical zoom, lens shift, automatic vertical keystone correction, wider throw ratio and advanced connectivity options including network display and USB plug-&-play display. Top load lamp and filter designs provide for easy maintenance.

VERSATILE PERFORMANCE

- > **Bright in virtually any setting with 5,000 ANSI lumens**
Ultra-bright 5,000 lumen output makes this the perfect choice for large boardrooms, conference halls and auditoriums
- > **Get Double Lumens**
Option for Stacking Dual Projectors to get up to 10,000 ANSI Lumens
- > **PC-Less Slide Show Presentation**
Project your pictures or images directly from a USB flash drive without a PC
- > **Network Display**
With its advanced management software, you can project up to 4 PCs at the same time with the ability to broadcast up to 8 projectors
- > **USB Display**
Project your presentations through any USB connection without the clutter of running a bulky VGA cable
- > **Network through RJ45**
Schedule, manage and monitor the projector remotely and receive e-mail alerts of projector lamp status. Use the unique integrated clock to perform commands even when the host PC is powered down
- > **Superior 16-Watt Stereo Sound**
Two power 8-watt speakers give your presentation great audio sound
- > **Eco-Mode For Green Savings**
Automatically dims projector lamp, lowers power consumption, extends lamp life up to 5000 hours
- > **Closed Captioning**
Integrated closed captioning decoder for the hearing impaired



VIEWSONIC
PRODUCTS, PROGRAMS,
AND SERVICES

ViewSonic®
See the difference® 

Pro9500

**HIGH BRIGHTNESS
PERFORMANCE PROJECTOR
WITH 3LCD TECHNOLOGY**



Optional Accessories

- > Replacement Lamp RLC-063
- > Universal Ceiling Mount Kit WMK-005
- > Wireless Presentation Gateway.....WPG-360
- > Extended Express Exchange® PRJ-EE-10-03

Projection Distance		4:3 Screen Size	
M	Feet	M	Inches
0.9	2.95	0.45-0.75	17.7-29.5
1.5	4.9	0.75-1.25	29.5-49
2	6.5	1.0-1.7	39-67
4	13.1	2-3.3	78.7-130
5	16.4	2.5-4.2	98.4-165
8	26.2	4-6.7	157.5-263.8



ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by TUV NORD.

Sales: (888) 881-8781 . SalesInfo@ViewSonic.com . ViewSonic.com

*Running eco-mode exclusively can extend lamp life. See ViewSonic.com for full Express Exchange details. Specifications subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2010 ViewSonic Corporation. All rights reserved [15424-00B-01/10] PRO9500

DISPLAY	Type	0.63" (x3) 3LCD Poly-Si TFT with Micro Lens
	Resolution	XGA 1024x768 (Native) / UXGA 1600x1200 (compressed)
	Color Depth	24 bits, 16.7 million colors (8+8+8)
	Lens	1.7x Manual optical zoom / Manual focus
	Lens Shift	Vertical 10:0-4:1 at Horizon 1:1 / Horizon 11:9-9:11 at Vertical 10:0-4:1
	Keystone	Vertical digital keystone correction: +/- 30 degrees
	Projection Size	30"-300" / 0.8m-7.6m diagonal
	Throw Distance	2.95ft-29.9ft / 0.9m-9.1m
	Throw Ratio	1.5-2.5:1
	Lamp	245 watt
	Lamp Life	3000 / 5000* hours (Normal / Eco-mode)
	Brightness	5000 Lumens
	Contrast Ratio	1800:1 (typ) 3500:1 (max)
	Aspect Ratio	4:3 (native)
INPUT SIGNAL	Computer & Video	NTSC M (3.58MHz), 4.43MHz, PAL (B, D, G, H, I, M, N), SECAM, SD (480i/576i), ED (480p/576p), HD (720p/1080i/1080p)
	Frequency	Fh: 31-106KHz, Fv: 56-120Hz
COMPATIBILITY	PC	Analog: VGA to UXGA
	Mac®	Analog: Up to WSXGA+
CONNECTOR	RGB Input	15-pin mini D-sub
	RGB Output	15-pin mini D-sub
	RGB-BNC	BNC-5 (x 1 set)
	Digital Input	HDMI 1.3
	Component	RCA (x3)
	Composite Input	RCA jack
	S-Video Input	4-pin mini-Din
	USB	Type A: for PC-less slide show presentation - support JPEG, BMP, TIFF, PNG, GIF from USB flash drive. Type B: for direct presentation from PC (not Mac compatible), Mouse Control
	Audio Input	3.5mm mini jack (x2), RCA (L/R) x1 Pair
	Audio Output	RCA (L/R) x1 Pair
Mic In	3.5mm mini jack (x1)	
Control	RS-232 (DB-9), 3.5mm mini jack (wired remote)	
Network	RJ45	
AUDIO POWER	Speaker	8W (x2)
	Voltage	100~240 VAC (Auto Switching), 50/60Hz (universal)
CONTROLS	Consumption	420W (typ) / <0.5W (stand-by mode)
	Basic	STANDBY/ON, INPUT, MENU
OSD		
PICTURE Menu: Brightness, Contrast, Gamma, Color Temp, Color, Tint, Sharpness, Active IRIS, My Memory		
IMAGE Menu: Aspect, Over Scan, V position, H position, H Phase, H size, Auto Adjust Execute		
INPUT Menu: Progressive, Video NR, Color Space, Component, Video Format, HDMI Format, HDMI Range, Computer IN, Frame Lock, Resolution		
SETUP Menu: Auto Keystone, Keystone H/V, Perfect Fit, Auto ECO Mode, ECO Mode, Mirror, Standby mode, Monitor out		
AUDIO Menu: Volume, Speaker, Audio Source, HDMI Audio, MIC Level, MIC Volume		
SCREEN Menu: Language, Menu Position, Blank, Start up, Myscreen, Myscreen Lock, Message, Source Name, Template, CC		
OPTION Menu: Auto Search, Auto Keystone, Direct Power ON, Auto Power OFF, USB Type B, Lamp Time, Filter Time, My Button, My Source, Service (Fan Speed, Auto Adjust, Ghost, Filter Message, Key Lock, Remote FREQ, Communication, Information, Factory Reset)		
NETWORK Menu: Setup, Projector Name, My Image, AMX D.D, Presentation, Information, Service		
SECURITY Menu: Security password change, Myscreen password, PIN Lock, Transition Detector, My Text Password, My Text Display, My Text Writing, Security Indicator, Stack Lock		
OPERATING CONDITIONS	Temperature	41°F-95°F (5°C-35°C)
	Humidity	10%-85% (non-condensing)
	Altitude	0 to 6,000 ft (1,800m), operational up to 10,000 ft (3048m) at reduced reliability and performance
NOISE LEVEL	Normal / Eco-mode	36dB / 29dB
DIMENSIONS (W x H x D)	Physical	15.8 x 4 x 12.5 (in) / 401 x 103 x 318 (mm)
	Packaging	22 x 7.7 x 16.5 (in) / 560 x 197 x 420 (mm)
WEIGHT	Net	10.4 lb. (4.7 kg)
	Gross	17.8 lb. (8.1 kg)
REGULATIONS	UL60950-1/C-UL, FCC part 15 Class B, CE approval: EN61000-3-2, EN61000-3-3, EN55022, EN55024 (EMC directive), EN60950-1 (low voltage directive); WEEE, RoHS C-Tick (Australia/New Zealand), NOM, ErP	
PACKAGE CONTENTS	ViewSonic Projector, power cable, RGB cable, remote control with batteries, Lens Cap, Quick Start Guide, ViewSonic Wizard CD (with User Guide)	
WARRANTY	3-year limited warranty on parts, 1-year limited warranty on lamp, 1st year Express Exchange® service.	

ViewSonic® See the difference®

For more product information, visit us on the web at ViewSonic.com