



**Versatility Embodied and Packed with Features**

Offering versatility and functionality, the Vivitek D859 XGA digital projector features DLP®/BrilliantColor™ technologies, a 6-segment color wheel and enhanced display modes for wall color adjustments. Featuring a top-loading lamp, rapid on/off and keypad lock functions, the D859 is a simple presentation solution. With 3600 lumens, 3D-ready capabilities and multiple connectivity options, the Vivitek D859 is presentation-ready in any environment.

**Features**

- 3600 lumens of brightness with a 3000:1 contrast
- 3D-Ready via DLP® Link™
- High-efficiency lamps that last up to 4000 hours (in economy mode)
- VGA-out to display on a secondary monitor
- Keypad lock prevents accidental system adjustments
- Network-ready for integration and system administration via RJ45
- Top-loading, cover for quick and easy lamp replacement
- 10 Watt Speaker
- Enhanced color and display adjustments

| Specifications         |  |
|------------------------|--|
| Brightness             | 3600 Lumens  |
| Native Resolution      | XGA (1024 x 768)   |
| Max. Resolution        | UXGA (1600 x 1200)   |
| Contrast Ratio         | 3000:1 (Full On/Off)   |
| Lamp Life and Type     | ≈2500/4000 Hours (Boost/Standard Mode), 230W   |
| Lamp Part #            | TBD  |
| Display Type           | Single 0.55" DLP® Technology by Texas Instruments  |
| Throw Ratio            | 1.6 to 1.92:1 (Distance/Width)   |
| Image Size (Diagonal)  | 30" to 300" (0.8 to 7.6 m)   |
| Projection Distance    | 3.28' to 32.8' (1.0 to 10.0 m)   |
| Projection Lens        | F = 2.52 - 2.73, f = 24.34 - 25.95 mm  |
| Zoom Ratio             | 1.2:1 Manual Zoom/Focus  |
| Aspect Ratio           | 4:3 Native, 16:9 / 16:10 Compatible  |
| Offset                 | 128%   |
| Keystone Correction    | ±15° Vertical  |
| Color Spectrum         | 16.7 Million   |
| Horizontal Scan Rate   | 15, 30 to 90 KHz   |
| Vertical Scan Rate     | 43 to 85 Hz  |
| Speaker                | 10 Watt Mono   |
| Projection Method      | Table Top or Ceiling Mount (Front or Rear)   |
| Uniformity             | 85%  |
| Computer Compatibility | UXGA, SXGA+, SXGA, XGA, SVGA, VGA Resized; VESA Standards; PC and Macintosh Compatible   |
| Video Compatibility    | SDTV (480i), EDTV (480p), HDTV (576i, 720p, 1080i/p), NTSC/NTSC 4.43, PAL B/G/H/I/M/N 60, SECAM  |
| I/O Connection Ports   | HDMI v1.3, VGA-In, VGA-Out, Composite Video, Mini-Jack Audio-In, Mini-Jack Audio-Out, RCA Stereo-In, Microphone - In, RJ45, RS-232c, USB (Service) |
| Security               | Kensington® Lock Port  |
| Weight                 | 6.0 lbs (2.7 kg)   |
| Dimensions (W x H x D) | 12.0" x 4.3" x 8.5" (305 x 109 x 216 mm)   |
| Noise Level            | 33dB/36dB (Standard/Boost Mode)  |
| Power                  | Supply: AC 100-240V, 50/60Hz<br>Consumption: 230W (Standard Mode), 280W (Boost Mode), <1W (Standby Mode)   |
| Operating Temperature  | 41 to 104°F (5 to 40°C)  |
| Warranty               | 1-Year Limited Warranty, 90-Day Lamp Warranty  |
| Standard Accessories   | AC Power Cord, VGA Cable, Remote Control, Batteries for Remote, Carrying Case, User's Manual (CD), Lens Cap, Warranty Card                         |
| Optional Accessories   | Replacement Lamp, Remote, Carrying Case  |
| UPC                    | 8 14964 33598 2  |

