

DATA PROJECTORS D508/D509

Ham: Output No scores

Spotlight the Presentation

The Vivitek D508 and D509 SVGA/XGA digital projectors offer 2600 lumens of brightness, 2300:1 contrast ratio and DLP® and BrilliantColor™ technologies for sharp, detailed images. These projectors are also 3D-ready to ensure future media content can be displayed. With a variety of functions and features, the Vivitek D508/D509 will put your presentation in the spotlight.

Features

- DLP® and BrilliantColor™ technologies for sharp and detailed image quality
- High-efficiency lamps that last up to 4000 hours (in economy mode)
- Native SVGA/XGA resolution and able to display up to UXGA (1600 x 1200)
- Keypad lock feature to avoid accidental changes to the setting
- Closed-caption and 3D-Ready
- Rapid on/off feature
- Enhanced color and display adjustments











Specifications	
Brightness	2600 Lumens
Native Resolution	D508: SVGA (800 x 600) D509: XGA (1024 x 768)
Max. Resolution	UXGA (1600 x 1200)
Contrast Ratio	2300:1 (Full On/Off)
Lamp Life and Type	≈3000/4000 Hours (Standard/Economy Mode), 180W
Lamp Part #	5811100760
Display Type	Single 0.55" DLP® Technology by Texas Instruments
Throw Ratio	1.98:1 (Distance/Width)
Image Size (Diagonal)	23" to 255" (0.6 to 6.5 m)
Projection Distance	3' to 30' (0.9 to 9.1 m)
Projection Lens	F = 2.62, f = 22.9 mm, Manual Focus
Aspect Ratio	4:3 Native, 16:9 Compatible
Offset	114%
Keystone Correction	±30° Vertical
Color Spectrum	1.07 Billion
Horizontal Scan Rate	15, 30 to 91.4 KHz
Vertical Scan Rate	43 to 87 Hz
Remote Control	Card-Type IR Remote
Projection Method	Table Top or Ceiling Mount (Front or Rear)
Uniformity	85%
Computer Compatibility	UXGA, SXGA+, SXGA, XGA, SVGA, VGA Resized; VESA Standards; PC and Macintosh Compatible
Video Compatibility	SDTV (480i), EDTV (480p), HDTV (576i, 720p, 1080i) thru RGB, NTSC/NTSC 4.43, PAL B/G/H/I/M/N 60, SECAM
I/O Connection Ports	VGA-In, Composite Video, USB (Service)
Security	Kensington® Lock Port
Weight	4.2 lbs (1.9 kg)
Dimensions (W x H x D)	10.3" x 3.0" x 7.8" (261.6 x 76.2 x 198.1mm)
Noise Level	31dB/28dB (Standard/Economy Mode)
Power	Supply: AC 100-240V Consumption: 205W (Economy Mode), 230W (Standard Mode), <1W (Standby Mode)
Operating Temperature	41 to 104°F (5 to 40°C)
Warranty	1-Year Limited Warranty, 90-Day Lamp Warranty
Standard Accessories	AC Power Cord, VGA Cable, Remote Control, Batteries for Remote, Carrying Case, User's Manual (CD), Lens Cap, Warranty Card
Optional Accessories	Replacement Lamp, Remote, Carrying Case
UPC	8 14964 33483 1/8 14964 33484 8 (D508/D509)