

W303

Big projection

- Bright projection 3200 ANSI Lumens
- WXGA resolution, 15,000:1 contrast ratio, HDMI input
- Low ownership costs up to 10,000 hours² lamp life
- Lightweight and portable, carry bag included

















W303


Widescreen and HD ready the W303 has a bright 3200L and 15,000:1 contrast allowing you to project bright, crystal clear images with superb colours using DLP® and BrilliantColor™ technologies. Incredible lamp life of up to 10,000 hours combined with Eco+ technology provides energy and money saving features. Installed or on the move with the included carry bag, the versatile W303 incorporates HDMI, built in speaker, Full 3D technology and optional wireless capabilities that are easy to use. Ideal for use in a meeting room or classroom.

Bright Images

Project in ambient light conditions with the ultra bright 3200 ANSI Lumens. Ideal for meeting rooms and classrooms.

Cost Saving - Long Lamp Life

Reduce the number of lamp changes with lamp life of up to 10,000 hours² using the Education Cycle.



Clear, Focused Images

Produce a stunning 15,000:1 contrast ratio for pin sharp graphics and crystal clear text using the unique Dynamic mode feature.

Combined with DarkChip3 technology for Texas Instruments, Dynamic mode automatically adjusts the lamp output, based on the brightness information of each frame; to create a stunning high contrast ratio. Bright scenes are crisp and clear, while dark scenes remain detailed with deep blacks which gives exceptional light and shade detail






Green Solutions



Eco⁺ technology from Optoma increases our commitment to reducing the impact we all make on the environment

Eco⁺ Mode

Saving energy saves money! Eco⁺ technology reduces the power consumption to as little as 30%. This intelligent feature can more than double your expected lamp life, lowering the total cost of ownership and reducing maintenance.



Auto Power Off

There may be instances when the projector is left running when not in use. To help save energy if the projector is left running and no source is detected, the "Auto Power Off" feature automatically turns off the projector after a set period of time.

Eco AV Mute

Stay in control of your presentation with the Eco AV mute feature. Direct your audience's attention away from the screen by blanking the image when no longer needed. This also instantly reduces the power consumption to 25%, further prolonging the life of your lamp.



Eco AV mute off 100% power consumption

Eco AV mute on 25% power consumption



We know that improving our products is the best way to reduce our impact on the environment. That's why at Optoma we design our products to have a long usable life, use fewer materials, ship with the minimum packaging and be free of all possible toxic substances. Naturally, energy efficiency and being recyclable are built in at the design stage. With each new product, we strive towards minimising our environmental impact.

Audio Capability

Built-in 2W speaker offers excellent audio support. The W303 is easy to set up without the need for costly external speakers.



Control

RS232 Compatibility - The W303 comes with an extensive RS232 command set making it simple and easy to control with any control system. AMX Compatibility - Dynamic Discovery Protocol is incorporated into the W303. This feature allows for easy installation with AMX control systems.



Amazing Colours

The W303 incorporates BrilliantColor™ technology to produce stunningly bright images with perfectly balanced life-like colours.

Colour Guarantee



We are so confident that the W303 image colour quality will remain as good as the day you bought it that we will guarantee it for five years.

BrilliantColor™



The W303 incorporates BrilliantColor™ multi-colour processing technology to bring stunning, vibrant colour to your screen. Using six separate primary and secondary colours to produce a new level of colour performance and control; BrilliantColor™ increases colour brightness by up to 50% over other technologies to create accurate true to life images.

Rapid Off

It takes less than 10 seconds for the projector to power up and shutdown, saving both time and energy.

Quick Resume

Save time by not waiting for the projector to cool down before it can power up again. If the projector is accidentally turned off, this feature allows the projector to be instantly powered on again, if selected within a period of 100 seconds.



Easy Lamp Replacement

Top loading lamp cover allows easy access to replace lamps without having to remove the projector from the mount.

Full 3D

Using the inherent speed of DLP technology, The Optoma W303. Full 3D projector can display true 3D content form any 3D display device, such as 3D Blu-ray, PS3, Xbox and Sky3D.



Remote Mouse

Keep your audience's attention focussed on the right things using the simple, yet powerful remote with USB mouse control.

Wireless Presenting (optional extra)

Making presentations couldn't be easier using the optional wireless features of the W303. Using the Wireless Adapter you can connect and display presentations and video material wirelessly from a laptop, PC or mobile device. (Additional power required)



True WXGA Resolution

The W303 is the perfect companion for widescreen laptops. Your presentations will appear as sharp and detailed as they do on your widescreen laptop in WXGA (1280 x 800), WXGA resolution gives 30% more pixels than XGA.

W303 Specification

Display Technology	Single 0.65" WXGA DC3 DMD chip DLP® Technology by Texas Instruments						
Native Resolution	WXGA 1280 x 800						
Brightness - BRIGHT mode ¹	3200 ANSI Lumens						
Contrast	15,000:1						
Noise Level	26dB (min)						
Weight	2.21 kg						
I/O Connectors	Ü						
I/O Connectors	Inputs: HDMI (v1.4a 3D), 2 x 15 Pin D-sub (RGB/YPbPr), S-Video, Composite, Audio In, USB (remote mouse)						
	Outputs: 15 Pin D-sub, Audio Out						
	Control: RS232 - 9 Pin						
Preset Mode	PC: For computer or notebook (Brightest image)						
	Movie: Maximum contrast and Colour accuracy						
	Game: Bright vivid colour						
	sRGB: For Standard PC Colour (Best Colour Reproductiion)						
	User: Memorises user's settings						
Maximum Resolution	UXGA 1600 x 1200						
Computer Compatibility	UXGA, SXGA, XGA, SVGA, VGA, Mac						
Video Compatibility	PAL (B, D, G, H, I, M, N, 576i/p), NTSC (M, 4.43/3.58 MHz, 480i/p), SECAM (B, D, G, K, K1, L) HD (1080i, 720p)						
Displayable Colours	1073.4 Million						
Projection Lens	F/2.57~2.84; f=21~25.6mm, 1.2x Manual Zoom						
Throw Ratio	1.47 - 1.83:1						
Projection Screen Size	0.77m – 9.63m (30.44" - 379") Diagonal 16:10						
Projection Distance	1.2 - 12 metres						
Horizontal Scan Rate	15.3 - 91.1kHz						
Vertical Scan Rate	24 - 85Hz						
Lamp Type/Lamp Life ²	190W, 10,000 hours ² (Education Cycle) 6500/6000/4500 hours (Eco+/Dynamic/BRIGHT mode)						
Keystone Correction	± 40° Vertical						
Audio	2W						
Dimensions (W x D x H)	316 x 224 x 124mm						
Remote Control	Full function remote with remote mouse and direct source selecting						
Power Supply	100-240V, 50-60Hz						
Power Consumption	226W BRIGHT mode < 0.5W Standby mode, 194W Eco+ mode < 0.5W Standby mode						
Operating Conditions	5°C - 40°C, Max. Humidity 85%, Max. Altitude 3000m						
Uniformity	85%						
Security	Security Bar, Kensington Lock, Password Protection						
Standard Accessories	Carry Bag, AC Power Cord, VGA Cable, Infra Red Remote Control with Batteries, Quick Start Card, CD User Manual, Warranty						
	Card						
Optional Accessories	Ceiling Mount Kit						
RoHS	Compliant						
3D Support	The 3D features of Optoma projectors can only be used with compatible 3D content. Typical applications include use with 3D						
	educational or 3D design and modelling systems. 3D TV broadcast systems, (SKY in the UK), Blu-ray 3D™ and 3D games						
	from the Sony® PS3 or Microsoft® Xbox 360 are now supported as part of the HDMI v1.4a specification.						
3D Viewing	Requires the Optoma DLP-Link shutterglasses - available separately.						
3D Compatibility	Side-by-Side:1080i50 / 60, 720p50 / 60						
	Frame-pack: 1080p24, 720p50 / 60						
0#	Over-Under: 1080p24, 720p50 / 60						
Offset	112%						

Easy To Use Remote

W303 Remote Control

- 1. Power
- 2. Mouse select
- 3. Source
- 4. Re-sync
- 5. Left mouse click
- 6. Right mouse click
- 7. Mouse control
- 8. Display mode
- 9. Page up/down control
- **10.** Vertical keystone correction
- 11. Volume control
- 12. Brightness
- **13.** Menu
- **14.** Direct input source select
- 15. Eco AV mute
- **16.** Eco+
- 17. 3D control



W303 Connections

- 18. Audio In (VGA)
- 19. S-Video
- **20.** VGA 1
- 21. VGA Out
- **22.** HDMI
- 23. RS232
- 24. USB (Remote Mouse)
- 25. Audio In (S-Video/Video)
- 26. KensingtonTM Lock
- 27. Audio Out
- 28. Video
- **29.** VGA 2

Exceptional Connectivity / Multiple Terminals



Projection Distance 1.2 - 12m (16:10 Aspect Ratio)											
Projection Distance (m)	Max. Horizontal Image Size (m)	Min. Horizontal Image Size (m)	Max. Vertical Image Size (m)	Min. Vertical Image Size (m)	Min Diagonal Image Size (m)	Max Diagonal Image Size (m)	Min Diagonal Image Size (inch)	Max Diagonal Image Size (inch)	Max. Image Offset (m)		
1.20	0.82	0.66	0.51	0.41	0.77	0.96	30.44	37.90	0.06		
2.00	1.36	1.09	0.85	0.68	1.29	1.60	50.74	63.17	0.10		
2.50	1.70	1.37	1.06	0.85	1.61	2.01	63.42	78.96	0.13		
3.00	2.04	1.64	1.28	1.02	1.93	2.41	76.11	94.75	0.15		
4.00	2.72	2.19	1.70	1.37	2.58	3.21	101.48	126.33	0.20		
5.00	3.40	2.73	2.13	1.71	3.22	4.01	126.85	157.92	0.26		
6.00	4.08	3.28	2.55	2.05	3.87	4.81	152.22	189.50	0.31		
7.00	4.76	3.83	2.98	2.39	4.51	5.62	177.59	221.08	0.36		
8.00	5.44	4.37	3.40	2.73	5.16	6.42	202.96	252.66	0.41		
9.00	6.12	4.92	3.83	3.07	5.80	7.22	228.33	284.25	0.46		
10.00	6.80	5.46	4.25	3.42	6.44	8.02	253.70	315.83	0.51		
11.00	7.48	6.01	4.68	3.76	7.09	8.82	279.07	347.41	0.56		
12.00	8.16	6.56	5.10	4.10	7.73	9.63	304.44	379.00	0.61		



Optoma Europe Ltd.

42 Caxton Way, Watford Business Park, Watford, Hertfordshire, UK. WD18 8QZ www.optoma.co.uk

¹Brightness and lamp lifetime will vary depending on the selected projector mode, environmental conditions and usage. As is common with all lamp based projectors, brightness will decrease over the lamp lifetime. ²Typical lamp life achieved through testing and will vary according to operational use and environmental conditions. 10,000 hours lamp life is based on a daily cycle that reflects projector usage in a typical education environment. Details of this cycle are available on request. ³Optoma guarantees that in normal use, Optoma DLP® colour quality will be indistinguishable from when new. Exclusions: (a) Guarantee is voided if the projector is subject to damage through misuse. (b) Guarantee may be void in industrial or commercial entertainment environments where dust or smoke is excessive (c) Guarantee will not apply if lamp brightness is below 50% due to wear or if the projector is not working due to other faults. (d) Over time worn lamps within all projector types will show a slight colour variance. Copyright © 2013, Optoma Europe Ltd. All other product names and company names used herein are for identification purposes only and may be trademarks or registered trademarks of their respective owners. Errors and omissions excepted, all specifications are subject to change without notice. DLP®, BrilliantColor™ and the DLP logo are registered trademarks of Texas Instruments. All images of products are for representation purposes only. Whilst every care is taken to provide accurate images of our products, actual products may differ slightly. Some product images may have been digitally altered by us to add an Optoma logo to the front panel. Optoma reserves the right to amend or alter actual product, product specifications or product images without notice. Some images may be simulated.

15/05/2013 06:38