





## **FEATURES**

Please see page 3 for lens options.

- Native XGA Resolution (1024 x 768)
- 5500 ANSI Lumens (Normal Mode), 90% Uniformity
- 800:1 Contrast Ratio
- Lens: f=48.4 to 62.8mm, F1.8 to 2.1, 1.3x Zoom
- Lens Shifting: 1:1 to 10:0
- Throw Distance: 3.7 to 29.1 ft. (1.4 to 14.7m)
- Projected Image Size: 31 to 400 in.
- Throw Ratio: 1.77 to 2.33:1 (D:W)
- Digital Keystone Correction (±35 degrees Vertical, ±15 degrees Horizontal)
- Image Adjustment Features: Color Management, Auto Picture Control, Gamma Adjustment
- 10 bit Digital Processing for Smoother Gradations and Color Reproductions
- Progressive Scanning (480i, 575i, 1080i) with 2:3 / 2:2 Pull Down Response (480i)
- Customize Logo Display with Lock Function
- DVI-D (RGB Digital) Terminal, HDCP Compatible
- VGA (RGB Analog) Input/Output
- Other Input Terminals: 5 BNC, Component, S-Video, Composite
- Quiet Operation: 36dB (Quiet Mode)
- Size (W x D x H): 12.6 x 16.9 x 6.6 in. (319 x 430 x 168mm)
- 3 Year Parts and Labor Warranty -120 Day Lamp Life Warranty

# KIT CONTENTS

- Projector Wireless/Wired Remote Control (AAA-size Batteries Included)
- VGA Computer Cable Wired Remote Cable
- Mouse Control Cable (USB) Lens Cap User's Manual
- Warranty Card
- \* See back cover for details on the "Triple P" Program.

## OPTIONAL PROJECTOR LENSES FOR THE LV-7575



#### Ultra Wide-Angle Lens LV-IL01

- Lens: f=22.33mm, F2.5
- Throw Distance: 3.7 to 6.4 ft. (1.13 to 1.96m)
- Projected Image Size: 70 to 120 in.
- Throw Ratio: 0.8:1 (D:W)



#### Wide-Angle Zoom Lens LV-IL02

- Lens: f=34.33 to 48.02mm, F2.5 to 3.06, 1.4x zoom
- Throw Distance: 3.2 to 25.4 ft.(0.98 to 7.74m)
- Projected Image Size: 40 to 300 in.
- Throw Ratio: 1.25 to 1.8:1 (D:W)



#### Long Focus Zoom Lens LV-IL03

- Lens: f=63.5 to 111.5mm,
  F2.03 to 2.89, 1.8x zoom
- Throw Distance: 8.9 to 46.7 ft. (2.73 to 14.23m)
- Projected Image Size: 60 to 300 in.
- Throw Ratio: 2.29 to 4.17:1 (D:W)



### Ultra Long Focus Zoom Lens LV-IL04

- Lens: f=111.6 to 155.2mm, F2.06 to 2.73, 1.4x zoom
- Throw Distance: 11.4 to 82.0 ft. (3.48 to 25.0m)
- Projected Image Size: 40 to 300 in.
- Throw Ratio: 4.15 to 5.78:1 (D:W)

Lens changes must be performed by an authorized Canon representative.