

DreamVision®

DreamWeaver Plus Specifications

Model	DreamVision DreamWeaver Plus
Projection system	New Texas Instruments Mustang HD2+™ 12° LVDS DMD
Enhancement	New Faroudja DCDi™ FLI2310
Optic	Carl Zeiss Projection Lens: F/1.9, 26.7 - 36.8mm focal length
Color Wheel	7 segments (RGBRGBG), 5 x (9000rps, 300Hz, 6500K color temperature)
Resolution	1280x720 16 :9
Contrast Ratio	2300:1 full on / full off
Lamp	220 Watt UHP (3000 hours life time)
Brightness	1200 lumens Dual light output mode with High Bright mode (+20%)
Colors	16.7 millions simultaneously displayable
Installation	Front, Rear, Table, Ceiling (Ceiling bracket in option)
Keystone Correction	Digital up to +/- 20° vertical, +/- 9° horizontal
Inputs	2 x components - gold RCA 1 x Component - 15-pin D Sub 2 x S-VHS - Mini Din 4-pin 1 x Composite Video - RCA 1 x DVI - M1-DA VESA 1 x HDTV Analog - 15-pin D Sub 1 x RS232 control - 9-pin D Sub 1 x IR Repeater (Niles / Xantech compatible) - 3.5 mm mini-jack 2 x 12 V trigger - 3.5 mm mini-jack 1 x USB 1 x Power supply
Video Compatibility	Component and RGB HDTV (720p, 1035i, 1080i, 1080p) Component EDTV (480p, 576p progressive scan), SECAM: M, Component, composite and S-Video standard video. (480i, 576i, 576i RGB SCART with adapter, NTSC, NTSC M 4.43, PAL: B, G, H, I, M, N)
Size	Ø439 mm - High 127 mm
Weight	4.4 Kg
Audible Noise	25 dB
Accessory	Learning Remote Control capable of controlling up to 10 different others electronic devices.
Option	Ceiling bracket horizontally and vertically adjustable in white or black finish.
Color option	Silver, White or Black



Silver Finish



White Finish



Black Finish