

# REALiS WUX5000 / WUX4000 PRO AV PROJECTORS

## Pro Performance

The REALiS WUX5000 and REALiS WUX4000 Pro AV Projectors are designed to display bright, high-resolution WUXGA (1920 x 1200) widescreen 16:10 video and still images in larger-venue environments. Rated at 5000 and 4000 lumens respectively, the REALiS WUX5000 and REALiS WUX4000 employ Canon's advanced AISYS-enhanced LCOS technology for vivid, seamless images with intricate detail, accurate color, crisp contrast, sharp blacks, and HD video with more natural motion. Built-in Canon Color-Correction IC, 3D color LUT (look-up table), dynamic gamma, and memory color-correction combine to provide advanced color refinements. The projectors offer a choice of three Genuine Canon lenses – which include a 1.5x Standard Zoom, 0.8x Ultra Wide-Angle, or a 1.7x Long Focus Zoom – to suit a variety of applications and environments. In addition, a motorized lens shift feature can compensate for moderate projector-placement obstacles and provide installation convenience.



## Key Features

- ▶ Native Widescreen WUXGA Resolution (1920 x 1200)
- ▶ 5000 Lumens and 4000 Lumens
- ▶ 1000:1 Contrast Ratio
- ▶ Canon AISYS-enhanced LCOS Technology
- ▶ Optional Interchangeable Genuine Canon Projection Lenses
- ▶ Motorized Horizontal and Vertical Lens Shift
- ▶ Easy-Maintenance Lamp, Air Filter, and Optical Filter
- ▶ Advanced Color Tools



*WUXGA resolution shows a significantly larger display area, delivering razor-sharp precision in projected images.*

- ▶ Full 10-Bit Color
- ▶ Versatile Connectivity (HDMI Version 1.3 and DVI-D)

## Recommended For:

- ▶ Educational Institutions
- ▶ Corporate Boardrooms
- ▶ Conference Centers
- ▶ Houses of Worship
- ▶ Government Offices
- ▶ Museums
- ▶ Photo Studios / Galleries

# REALiS WUX5000 / WUX4000 PRO AV PROJECTORS

PRODUCT NAME: REALiS WUX5000 / REALiS WUX4000 ITEM CODE: 5748B002 / 4964B002 UPC CODE: 013803142549 / 013803131642

## SPECIFICATIONS

PRODUCT NAME		WUX5000	WUX4000
BASIC	IMAGING DEVICE	0.7" LCOS Reflective LCD panels x 3	
	ASPECT RATIO	16:10	
	NATIVE RESOLUTION	1920 x 1200 (WUXGA)	
	BRIGHTNESS (LUMENS)	5000	4000 (Normal), 3500 (Quiet)
	UNIFORMITY	88%	
	CONTRAST RATIO	1000:1	
	KEYSTONE CORRECTION	VERTICAL	-11° ~ +20° for Standard Zoom Lens ±20° for Long Focus Zoom Lens ±13° for Fixed Short Focus Lens
HORIZONTAL		±20° for Standard and Long Focus Zoom Lenses / Ultra Wide-Angle Lens	
IMAGE ADJUSTMENTS	IMAGE MODES	PC: Standard, Presentation, Vivid Photo, Photo/sRGB, User 1-5 Video: Standard, Dynamic, Photo/sRGB, Video, Cinema, User 1-5	
	COLOR PROCESSING	Color (Level, Temperature, Balance), Gain & Offset (R,G,B), 3D-LUT	
	MOUNTING	Ceiling, Rear, Rear-Ceiling, Upwards, Downwards	
	TILT ANGLE	Adjustable feet up to 6 degrees	
INPUT SIGNALS	DIGITAL PC INPUT	WUXGA / UXGA / WSXGA+ / SXGA+ / WXGA+ / WXGA / SXGA / XGA / SVGA / VGA	
	ANALOG PC INPUT	WUXGA / UXGA / WSXGA+ / SXGA+ / WXGA+ / WXGA / SXGA / XGA / SVGA / VGA	
	SCANNING FREQUENCY	H:15~75 KHz, V:50 ~ 85 KHz	
	DOT CLOCK	162 MHz or less	
	DIGITAL VIDEO INPUT	1080p / 1080i / 720p / 576p / 480p	
COMPONENT INPUT	1080p / 1080i / 720p / 576p / 576i / 480p / 480i		
TERMINALS	INPUTS	ANALOG PC INPUT	Mini D-sub 15pin (VGA)
		DIGITAL PC INPUT	HDMI, DVI-D 24pin
		ANALOG VIDEO INPUT	Mini D-sub 15pin (Component)
		DIGITAL VIDEO INPUT	HDMI, DVI-D 24pin
		AUDIO INPUT	3.5mm (Stereo) x 2
	CONTROL	9-pin D-Sub (RS-232C) Network (RJ-45)	
	OUTPUTS	AUDIO OUTPUT	3.5mm (Stereo)
SPEAKER		5W (Mono)	
LAMP	TYPE	330W NSH (AC)	310W NSH (AC)
	LAMP POWER	336W	300W (Normal), 264W (Quiet)
	LAMP LIFE (HOURS)	3000	3000 (Normal) / 4000 (Quiet)
	FAN NOISE	40dB	39dB (Normal), 36dB (Quiet)
RATINGS	POWER CONSUMPTION	450W	410W (Normal), 365W (Quiet)
	POWER REQUIREMENT	AC100 to 240V, 50 / 60Hz	
	OPERATING TEMPERATURE	41° to 95° F (5° to 35° C)	
	STORAGE ENVIRONMENT	14° to 140° F (-10° to 60° C) 5%RH - 90%RH	
	DIMENSIONS (W x D x H)	15.0" x 16.9" x 6.7" including protruding parts, without lens	
WEIGHT	18.7 lbs without lens		
PACKAGING	BOX	DIMENSIONS (L x W x H)	21.30" x 19.60" x 11.80"
		WEIGHT	25.20 lbs
	CARTON	DIMENSIONS (L x W x H)	21.30" x 19.60" x 11.80"
		WEIGHT	25.20 lbs
PALLET	DIMENSIONS (L x W x H)	48" x 40" x 53.20"	
	WEIGHT	403.20 lbs	

## LENS SPECIFICATIONS

PRODUCT NAME		WUX5000	WUX4000
3 LENS OPTIONS	RS-IL01ST STANDARD ZOOM LENS	PROJECTION LENS	F1.89 - 2.65 / f= 23.0 - 34.5 mm
		LENS SHIFT*	(Vertical) Down 15% ~ Up 55% / (Horizontal) Left 10% ~ Right 10%
		ZOOM	1.5 x Optical Zoom (Powered)
		FOCUS	Powered
		SCREEN SIZE	40" - 600"
	RS-IL02LZ LONG FOCUS ZOOM LENS	PROJECTION LENS	F1.99 - 2.83 / f= 34.0 - 57.7 mm
		LENS SHIFT*	(Vertical) Down 15% ~ Up 55% / (Horizontal) Left 10% ~ Right 10%
		ZOOM	1.7 x Optical Zoom (Powered)
		FOCUS	Powered
		SCREEN SIZE	40" - 600"
	RS-IL03WF ULTRA WIDE-ANGLE LENS	PROJECTION LENS	F2.0 / f= 12.8 mm
		LENS SHIFT*	(Vertical) Down 5% ~ Up 5% / (Horizontal) Left 2% ~ Right 2%
		ZOOM	Fixed
		FOCUS	Powered
		SCREEN SIZE	40" to 300"
PROJECTION DISTANCE	2.3 - 17.1 ft (0.7 - 5.2 m) / 100": 5.6 ft (1.7 m)		
THROW RATIO	0.8:1		

\*The maximum upward shift and the maximum horizontal shift cannot be used simultaneously.

## OPTIONAL ACCESSORIES


Item Code No.	Description
4966B001	Standard Zoom Lens RS-IL01ST
4967B001	Long Focus Zoom Lens RS-IL02LZ
4968B001	Ultra Wide-Angle Lens RS-IL03WF
5017B001	Replacement Lamp RS-LP07 (WUX5000)
4965B001	Replacement Lamp RS-LP06 (WUX4000)
4971B001	Replacement Air Filter RS-FL01
4970B001	Remote Controller RS-RC04
4969B001	Ceiling Mount RS-CL11
3096B001	Ceiling Extension RS-CL08 (16" - 24")
3097B001	Ceiling Extension RS-CL09 (24" - 39")
5471B001	Top Cover RS-TC01 (Dark Grey)

## Accessories



Three high-resolution interchangeable lenses are available for the REALiS WUX5000 and REALiS WUX4000. These include a 1.5x Standard Zoom Lens, 0.8x Ultra Wide-Angle Lens, and 1.7x Long Focus Zoom Lens. All lenses incorporate advanced low-distortion and high-resolution optical technologies originally developed for Canon's EOS DSLR camera lenses.

## Connectability



©2012 Canon U.S.A., Inc. All rights reserved. Not responsible for typographical errors. Specifications subject to change without notice. Canon and REALiS are registered trademarks of Canon Inc. in the United States and may also be trademarks or registered trademarks in other countries. IMAGEANYWARE is a trademark of Canon. All other products and brand names may be registered trademarks, trademarks or service marks of their respective owners in the United States and/or other countries.

