

PLUS

U2-1150 | U2-X1130 | U2-813



THE U2 SERIES FROM PLUS GIVES YOU AN EXCELLENT ARRAY OF POWERFUL DIGITAL PROJECTORS THAT EACH WEIGH IN AT 5.6 POUNDS.

THE U2s ARE GREAT FOR ANY CONFERENCE OR CLASSROOM, BUT STILL PORTABLE ENOUGH TO TAKE ON THE ROAD.

THIS ENTIRE LINE OF PROJECTORS CONNECTS WITH VIRTUALLY ANY VIDEO SOURCE AND IS INCREDIBLY EASY TO SET UP. THEY ALL HAVE DIGITAL KEYSTONE CORRECTION FOR A PERFECTLY EVEN PROJECTION AND COME WITH A HYPERZOOM REMOTE CONTROL THAT LETS YOU ZOOM IN ON THE TINIEST DETAILS.



Ultraportable
at just 5.6 lbs.

Up to 1500 ANSI lumens
corner-to-corner brightness

Digital zoom instantly targets and
enlarges the fine print at the touch
of a button

Connects to virtually any computer
or video source

Digital keystone correction

Built-in control panel and wireless
remote control

PLUS Vision Corp.

9610 SW SUNSHINE CT.
SUITE 300
BEAVERTON, OR 97005
800-211-9001 • 503-748-8700
www.plus-america.com



U2-1150 | U2-X1130 | U2-813

Specifications	U2-1150	U2-X1130	U2-813
Resolution	XGA, 1024 x 768 pixels	XGA, 1024 x 768 pixels	SVGA, 800 x 600 pixels
RGB Signal	XGA (true)	XGA (true)	XGA (true)
	SVGA (compressed)	SVGA (compressed)	SVGA (compressed)
	SVGA/VGA (expansion/true)	SVGA/VGA (expansion/true)	SVGA/VGA (expansion/true)
Brightness	1500 ANSI lumens	1300 ANSI lumens	1300 ANSI lumens
Contrast Ratio	800:1 (Full on/off)	800:1 (Full on/off)	800:1 (Full on/off)
Aspect Ratio	4:3	4:3	4:3
Projection Lens	F=2.7-3.0, f=35-42 mm	F=3.0-3.3, f=28-33 mm	F=3.0-3.3, f=28-33 mm
	1:1.2 manual zoom	1:1.2 manual zoom	1:1.2 manual zoom
	Manual focus	Manual focus	Manual focus
Digital Keystone Correction	30 degrees	30 degrees	30 degrees
Digital Zoom	4x	4x	4x
Light Resource	150-watt lamp	150-watt lamp	150-watt lamp
Color Palette	16.7 million colors	16.7 million colors	16.7 million colors
Projecting Position	Front/rear, table/ceiling	Front/rear, table/ceiling	Front/rear, table/ceiling
Projection Distance	3.9-40.3 ft./1.2-12.3 m	3.9-40.3 ft./1.2-12.3 m	3.9-40.3 ft./1.2-12.3 m
Image Size	25"-300" diagonal/.63-7.62 m	25"-300" diagonal/.63-7.62 m	25"-300" diagonal/.63-7.62 m
Video Signal	NTSC/PAL, NTSC4.43/SECAM	NTSC/PAL, NTSC4.43/SECAM	NTSC/PAL, NTSC4.43/SECAM
Audio	Mono 1-watt	Mono 1-watt	Mono 1-watt
Dimensions Excluding Lens and Stand:			
Height	2.3 in./58 mm	2.3 in./58 mm	2.3 in./58 mm
Width	9.3 in./235 mm	9.3 in./235 mm	9.3 in./235 mm
Length	11.7 in./297 mm	11.7 in./297 mm	11.7 in./297 mm
Weight	5.6 lb./2.6 kg	5.6 lb./2.6 kg	5.6 lb./2.6 kg

Included accessories:

- Wireless remote control
- Power cable (3 ft./1.8 m)
- VGA cable (3 ft./1.8 m)
- S-video cable (3 ft./1.8 m)
- PC Audio cable (3 ft./1.8 m)
- Video/audio cable (3 ft./1.8 m)
- Soft carrying case
- Users manual

Optional accessories:

- ATA shipping cases
- VGA cables (6 ft., 9 ft., 12 ft.)
- Serial mouse cables (6 ft., 9 ft., 12 ft.)
- Ceiling mount kits
- AverE-Pack 300



Shipping and Carry-on Cases

Keep your projector safe from the rigors of travel with an ATA-certified shipping case. Or take your laptop and projector on the road in one bag with a rolling soft case.



Presentation Screens

Choose from a variety of portable presentation screens from PLUS. They will save the day when you can't control your presentation environment.



Replacement Bulbs

PLUS offers a wide array of replacement bulbs so you can carry a spare anywhere.



Presenter-to-Go

A new presentation solution from PLUS Vision Corp. and MARGI Systems lets you leave your laptop at the office and use a PDA instead.