



**Model Name** **MW663 Digital Projector**

**Unique selling point** **Trade Mark**


- \* Designed for Business
- \* Easy carrying & Control
- \* Easy Maintenance
- \* Wireless display with Qpresenter App



<b>Projection System</b>	DLP	
<b>Native Resolution</b>	WXGA(1280x800)	
<b>Brightness</b>	3000AL	
<b>Contrast Ratio</b>	13000:1	
<b>Display Color</b>	1.07 Billion Colors	
<b>Lens</b>	F2.59-2.87, f=16.88-21.88 mm	
<b>Aspect Ratio</b>	Native 16:10 (5 aspect ratio selectable)	
<b>Throw Ratio</b>	1.21-1.57(76.5"@ 2m)	
<b>Image Size (Diagonal)</b>	44"-300"	
<b>Zoom Ratio</b>	1.3:1	
<b>Lamp Type</b>	210W	
<b>Lamp(Normal/Economic/SmartEco Mode)*</b>	4000/5000/6500 hours	
<b>Keystone Adjustment</b>	1D, Vertical +/- 40 degrees	
<b>Projection Offset</b>	120% ±5%	
<b>Resolution Support</b>	VGA(640 x 480) to UXGA(1600 x 1200)	
<b>Horizontal Frequency</b>	31K~102KHz	
<b>Vertical Scan Rate</b>	23~120Hz	
<b>Compatibility</b>	HDTV Compatibility	480i, 480p, 576i, 576p, 720p, 1080i, 1080p
	Video Compatibility	NTSC, PAL, SECAM
<b>Interface</b>	Computer in (D-sub 15pin)	x 2(Share with component)
	Monitor out (D-sub 15pin)	x 1
	HDMI	x 1
	Composite Video in (RCA)	x 1
	S-Video in (Mini DIN 4pin)	x 1
	Audio in (Mini Jack)	x 1
	Audio L/R in (RCA)	x 1
	Audio out (Mini Jack)	x 1
	Speaker	2W x 1
	USB (Type A)	x 1 (USB Reader & Wireless Display)
	USB (Type mini B)	x 1 (Download & UBS display)
	RS232 (DB-9pin)	x 1
	IR Receiver	x2 (Front+Top)
<b>Dimensions</b>	Dimensions(W x H x D)	312 x 104 x 244 mm
	Weight	2.75KG
<b>Power</b>	Power Supply	AC100 to 240 V, 50 to 60 Hz
	Power Consumption	303W, Standby<0.5W
<b>Audible Noise</b>	32/28 dBA (Normal/Economic mode)	
<b>On-Screen Display Languages</b>	Arabic/Bulgarian/ Croatian/ Czech/ Danish/ Dutch/ English/ Finnish/ French/ German/ Greek/ Hindi/ Hungarian/ Italian/ Indonesian/ Japanese/ Korean/ Norwegian/ Polish/ Portuguese/ Romanian/ Russian/ Simplified Chinese/Spanish/ Swedish/ Turkish/ Thai/ Traditional Chinese (28 Languages)	
<b>Picture Modes</b>	Dynamic/Presentation/sRGB/Cinema/User 1/User 2	
<b>Accessories</b>	<b>Standard</b>	<b>Optional</b>
	Remote Control w/ Battery	Presentation Plus P/N: 65J9306.002
	Power Cord (by region)	Spare Lamp Kit P/N: 5JJB05.001
	User Manual CD	Ceiling Mount P/N: 5JJ2K01.001
	Quick Start Guide	3D Glasses P/N: 5JJ0T14.011
	Warranty Card (by region)	Carry bag
	VGA(D-sub 15pin) Cable	


\*Lamp life results will vary depending on environmental conditions and usage. Actual product's features and specifications are subject to change without notice.

## Distance Chart



Screen size				Distance from screen (mm)			Vertical offset (mm)
Diagonal	W	H	Min length	Average	Max length		
Inch	mm	(mm)	(max. zoom)		(min. zoom)		
40	1016	862	538	1046	1203	1359	54
50	1270	1077	673	1307	1503	1699	67
60	1524	1292	808	1569	1804	2039	81
80	2032	1723	1077	2092	2405	2719	108
100	2540	2154	1346	2614	3007	3399	135
120	3048	2585	1615	3137	3608	4078	162
150	3810	3231	2019	3922	4510	5098	202
200	5080	4308	2692	5229	6013	6797	269
220	5588	4739	2962	5752	6614	7477	296
250	6350	5385	3365	6536	7516	8497	337
300	7620	6462	4039	7843	9020	10196	404

## Wall mount/Ceiling mount Chart



## Dimension



Unit: mm

