

SHARP

print



DT-400 | Home Theater

The DT-400 high definition DLP™ projector is a stylish, feature-packed projector ideal for the dedicated home theater or any viewing room in the home.

Utilizing the DLP™ HD2+ chip from Texas Instruments and with a resolution of 1280 x 720, the DT-400 boasts a 2500:1 contrast ratio and a brightness rating of 1200 ANSI lumens, delivering one of the best pictures available in consumer home theater today.

Features

- **High Contrast Ratio 2500:1 (in High Contrast Mode)**
enhances the DT-400's ability to discern fine, detailed differences between the darkest and lightest colors and provides superior black level reproduction.
- **1200 ANSI Lumens (in High Brightness Mode)**
is a high ANSI lumens rating that delivers a bright, beautiful picture.
- **Native 720p High Definition Capability**
compatible with 1080i and 720p HD signals.
- **Display Method**
DLP™ 0.8" HD2+ from Texas Instruments.
- **1.5 Powered Zoom and Focus**
simplifies adjustments without the need for changing the mounting position.
- **Powered Optical Iris System (High Contrast Mode/High Brightness Mode)**
instantly changes brightness and contrast settings with the push of a button. This allows the greatest flexibility for varying home theater environments.
- **DVI-I with High-bandwidth Digital Content Protection (HDCP)**
Terminal ensures compatibility with the new generation of high definition set-top boxes.
- **Home Theater Conveniences**
include easy installation and whisper quiet operation.

Specifications

- **HDTV Compatible** Yes, 1080i (in Intelligent Compression), 720p, 480i/p
- **Aspect Ratio** 4:3/16:9
- **Resolution** 1280 x 720
- **Brightness** 1200 ANSI Lumens (in High Brightness Mode)
- **Contrast Ratio** 2500:1 (in High Contrast Mode)
- **Maximum Screen Size** 300" (Diagonally Measured using 16:9 Aspect Ratio)
- **Projection Distance** 100" (16:9 widescreen) Throw Distance 8'7" – 12'11"
- **Display Method** DLP™ 0.8" HD2+ from Texas Instruments
- **Inputs** 2 Component (Y, Pb, Pr)
1 Composite Video (RCA)
1 S-Video (4-Pin DIN)
1 DVI-I/HDCP (Component and Digital/Analog RGB)
1 RS-232C Serial Port (9-Pin D-Sub)
- **Anamorphic DVD Capable** Yes
- **Computer Compatibility** XGA, MAC® 19" (in Intelligent Compression)

■ Video System	NTSC/NTSC4.43/PAL/PAL (60Hz)/PAL-M/PAL-N/SECAM
■ Lens Type	1-1.5x Power Zoom and Focus
■ Projection Lamp Type/Life	275W SHP/up to 3,000 Hours
■ Gamma Correction	Yes
■ 2-D Digital Keystone Correction	Yes
■ Color Temperature Adjustment	Yes
■ Detachable AC Cord	Yes
■ Optional Ceiling Bracket	AN-CM270
■ Wireless Glow Remote Control	Yes
■ Optional Digital Decoder Required	Yes (for HDTV)
■ Built-In Audio	None
■ Power Source	100-240V AC, 50/60Hz (Multi-Voltage)
■ Power Consumption	360W (6W Standby)
■ Dimensions (w x h x d)	12 7/32" x 3 33/64" x 11 7/64" (Main Body Only) 12 7/32" x 4 7/64" x 11 5/16" (Including Terminal Cover)
■ Weight	9.5 lbs.
■ UPC	074000364332

The DLP™ logo and the DLP™ medallion are trademarks of Texas Instruments.

Product specifications and design are subject to change without notice.