










CONVENIENCE AND FULL CONTROL WITH MULTI-PC PROJECTION.

Combining dynamic image quality with exceptional versatility, this Epson projector series boasts a high colour brightness to deliver vibrant and realistic colour projections. Equipped with a host of advanced features including multi-PC projection, optional Wi-Fi connectivity, Colour Universal Design, a high contrast ratio and a sliding horizontal keystone adjuster, this projector series empowers you to deliver vivid, sharp presentations every time.



EB-S21/97/945/965

EB-955W

- 
Wi-Fi*
- 
iProjection
- 
Multi PC Connection
- 
Horizontal Keystone Adjuster
- 
HDMI
- 
3-in-1 USB Display
- 
Power Savings

ENGINEERED FOR BUSINESS

Impeccable Performance

Deliver flawless presentations with multi-PC projection, optional Wi-Fi connectivity, high contrast ratio, HDMI connection and the horizontal keystone adjuster.

Made for Everyone

Designed with a Colour Universal Design for those with various types of colour vision, and equipped with eco-friendly features.

Stunning Colour Brightness

Achieve dazzling, sharp and colourful images with the high Colour Light Output.



*Optional with Wireless Adaptor ELPAP07

MODEL NUMBER	EB-S21	EB-97	
Projection Technology	RGB liquid crystal shutter projection system (3LCD)		
Specifications of Main Parts			
LCD	Size	0.55" without MLA (D7)	0.55" without MLA (D8)
	Native Resolution	SVGA	XGA
Projection Lens	Type	NA	Optical Zoom (Manual) / Focus (Manual)
	F-Number	1.44	1.58 - 1.72
	Focal Length	16.7mm	16.9 - 20.28 mm
	Zoom Ratio	1.0 - 1.35 (Digital Zoom)	1 - 1.2
	Throw Ratio	1.45 - 1.96 (Wide - Tele)	1.48 - 1.77 (Wide - Tele)
Lamp	Type	200W UHE	
	Life (Normal / Eco) ¹	5,000 hours / 6,000 hours	
Screen Size (Projected Distance)			
Zoom : Wide	30" - 350" [0.88 - 10.44 m]	30" - 300" [0.9 - 9.0 m]	
Zoom : Tele	23" - 260" [0.88 - 10.44 m]	30" - 300" [1.08 - 10.8 m]	
Standard Size	60" screen 1.77 - 2.4 m	60" screen 1.8 - 2.17 m	
Brightness²			
Colour Light Output	3,000lm	2,700lm	
White Light Output (Normal / Eco)	3,000lm / 2,100lm	2,700lm / 1,890lm	
Contrast Ratio	10,000:1		
Internal Speaker(s)			
Sound Output	5W Monaural	16W Monaural	
Keystone Correction			
Vertical / Horizontal	±30° / ±30°		
Auto Keystone Correction	Yes (Vertical)		
Connectivity			
Analog Input	D-Sub 15pin	2 (Blue)	
	Component	D-Sub 15pin x 2 (Blue molding) (common with Analog RGB connector)	
	Composite	RCA x 1 (Yellow)	
	S-Video	Mini DIN x 1	
Digital Input	HDMI	1	
Output Terminal	D-Sub 15pin	1 (Black molding) (Output signal: Computer 1 only)	
Audio Input	RCA (White/Red)	1 Pair	
	Stereo Mini Jack	2	
Audio Output	Stereo Mini Jack	1	
Others	USB Type A	1	
	USB Type B	1	
	Microphone Input	N/A	1
CONTROL I/O	RS-232C	D-Sub 9pin x 1	
	USB	Type B	
Network	Wired Lan	N/A	RJ45 x 1, 100Mbps
	Wireless	ELPAP07	
Wireless Specifications			
Supported Speed For Each Mode ³	IEEE 802.11b: 11 Mbps, IEEE 802.11g: 54 Mbps, IEEE 802.11n: 130 Mbps		
Wireless Lan Security	WPA/WPA2-Personal (with optional Wireless LAN Unit)		
Operating Temperature			
	5 - 35 °C <41 - 95 °F> (0m / 0ft - 2,286m / 7,500ft)		
	5 - 30 °C <41 - 86 °F> (over 2,286m / 7,500ft)		
	(20% - 80% humidity, unfrozen)		
Operating Altitude			
	0 - 3,000 m <0 - 9,843 ft> (over 1,500m / 4,921ft: with high altitude mode)		
Direct Power On / Off	Yes		
Start-Up Period	About 5 seconds, Warm-up Period: 30 seconds		
Cool Down Period	Instant Off or 0 second		
Air Filter	Type	Normal (ELPAF32)	
	Maintenance Cycle	3,000 hours ⁴	
Power Supply Voltage	100 - 240 V AC ±10%, 50/60 Hz		
Power Consumption (220 - 240V)			
Lamp On (Normal / Eco)	273W / 204W	287W / 215W	
Standby (Network On / Off)	3.1W / 0.29W		
Dimension Excluding Feet (D X W X H)	244 x 297 x 87 mm		
Weight	2.5kg	2.7kg	
Fan Noise (Normal / Eco)	37dB / 29dB		

¹ Lamp life will vary depending upon mode selected, environmental conditions and usage. Lamp brightness decreases over time.

² Colour brightness (colour light output) and white brightness (white light output) will vary depending on usage conditions. Colour light output measured in accordance with IDMS 15:4; white light output measured in accordance with ISO 21118.

³ Maximum speed and range is achievable when used with same enhanced mode technology. Actual data rates, features and performance may vary depending on your computer system, the environment and other factors.

⁴ When used in the general office environment (the amount of floating dust: 0.04 - 0.2 mg/m³). Based on the Epson's in-house test results. 25°C (77°F).

Supplied Accessories

- Power Cable: 1.8m
- Computer Cable (VGA Cable): 1.8m
- Remote Control: Yes, with Alkaline AA Battery x 2
- Cable Cover: Attached
- Bundled Software: Projector Software (CD-ROM)
- User's Manual Set: CDROM
- Soft Carrying Case: ELPKS67

Optional Accessories

- Spare Lamp: ELPLP78
- Air Filter: ELPAF32
- Wireless LAN Adaptor: ELPAP07
- Quick Wireless Connection USB Key: ELPAP09
- Ceiling Mount: ELPMB23

EB-S21



EB-97



©2013 Epson Singapore Pte Ltd. All Rights Reserved. Reproduction in part or in whole, without the written permission from Epson, is strictly prohibited.

EPSON and EXCEED YOUR VISION are registered trademarks of Seiko Epson Corporation.

All other product names and other company names used herein are for identification purposes only and are the trademarks or registered trademarks of their respective owners.

Epson disclaims any and all rights in those marks. Projected images shown herein are simulations. The actual product design and contents may vary. Specifications are subject to change without notice and may vary between countries. Please check with local Epson offices for more information.

Apple, iPad and iPhone are trademarks of Apple Inc., registered in the U.S. and other countries. App Store is a service mark of Apple Inc.

Android is a trademark of Google Inc.

Information correct as at September 2013