

# M-Vision LED 1000 1080p

1,000 ANSI Lumens | Contrast Ratio: 10,000:1 | Part No:114-432

## M-Vision Cine LED Series Digital Projectors



<b>Colour System:</b> R, G and B LEDs	<b>DMD Specification:</b> 1920 x 1080 pixels native, +/- 12° tilt angle Fast transit pixels for smooth greyscale and improved contrast.
<b>Display Type:</b> 1 x 0.95" DarkChip™ DMD™	<b>Aspect Ratio:</b> 16x9 <b>Fill Factor</b> 87%

### Key Features

#### Video & Graphics Processing

- 3rd Generation LEDs provide wide color gamut and deep color saturation.
- High Bandwidth Digital & Analogue Receiver with 10 Bit A-D.
- 24p and 1080p native display.
- BrilliantColor™ for increased system brightness.
- Adaptive Contrast with frame-by-frame content analysis.
- The projector automatically detects interlaced video and implements 3:2 or 2:2 extraction as appropriate, with pixel based, motion adaptive interpolation and auto cadence correction.
- Image enhancement for MPEG, Mosquito noise & Colour Transients in composite sources.

<b>Source Compatibility:</b> HDMI including Deep Color™ processing. Graphics standards up to 1920 x 1200 resolution at 60Hz via HDMI or VGA. Component Video (SD and HD) via YPrPb, RGB or RGBS. S-Video (PAL, NTSC & SECAM) Composite Video (PAL, NTSC & SECAM)
---

### Inputs/Outputs

Video & Computer			Communication & Control		
Type	Connector	Qty	Type	Connector	Qty
HDMI 1.3	HDMI	2	RS232	9-pin D Sub	1
VGA / Analog RGB	15-pin D-Sub	1	IR Input	3.5mm Stereo Jack	1
Component Video	3 x RCA	1	12V Trigger	3.5mm Stereo Jack	2
Component Video	3 x BNC	1			
S-Video	4-pin Mini DIN	1			
Composite Video	RCA	1			

<b>3D Formats Supported</b> Not applicable	<b>HDTV Formats Supported</b> 1080p (24Hz, 25Hz, 30Hz, 50Hz, 60Hz), 1080i (50Hz, 60Hz), 720p (50, 60Hz)
---	--

Computer Compatibility	Bandwidth
------------------------	-----------

Up to 1920 x 1200	200 MHz on analog RGB 165 Megapixels per second on HDMI
-------------------	--

Remote Control	Automation Control
----------------	--------------------

IR Remote Control On-Board keypad	RS232
--------------------------------------	-------

Colour Temperature
--------------------

User selectable from 5500 to 9300K
------------------------------------

Lamp Type	Typical Lamp Life
-----------	-------------------

LED Illumination Module	60,000 hours
-------------------------	--------------

Lenses
--------

Lens	Part No.	Focus Range	Lens Shift
0.73 fixed	110-171	0.97m - 1.3m	none
0.84 - 1.03 : 1 zoom	112-762	1.5m - 4m	Vert: 0.45 (U) 0.45 (D) frame, Hor: 0.12 (L) 0.12 (R) frame
1.56 - 1.86 : 1 zoom	110-157	2m - 7m	Vert: 0.6 (U) 0.6 (D) frame, Hor: 0.15 (L) 0.15 (R) frame
1.85 - 2.40 : 1 zoom	110-172	2.5m - 10m	Vert: 0.6 (U) 0.6 (D) frame, Hor: 0.15 (L) 0.15 (R) frame
2.40 - 4.00 : 1 zoom	112-319	4m - 12m	Vert: 0.6 (U) 0.6 (D) frame, Hor: 0.15 (L) 0.15 (R) frame

Lens Mount
------------

Manual shift, zoom & focus.
-----------------------------

Mechanical Mounting	Orientation
---------------------	-------------

Front/Rear Table Front/Rear Ceiling Adjustable Front/Rear Feet	<b>Table Top or Inverted:</b> Yes <b>Pointing Up:</b> Yes <b>Pointing Down:</b> Yes <b>Roll (Portrait):</b> Yes
--	--

Power Requirements	Power Consumption
--------------------	-------------------

100-240VAC 50/60Hz single phase	330W
---------------------------------	------

Thermal Dissipation	Fan Noise
---------------------	-----------

1126 BTU/Hour	30 dBA
---------------	--------

Operating/Storage Temperature	Operating Humidity
-------------------------------	--------------------

Operating: 10 to 40C (50 to 95F) Storage: -20 to 60C (-4 to 140F)	20% to 85% non condensing
--	---------------------------

Weight (Chassis Only)	Dimensions
-----------------------	------------

15 kg 33.1 lb	L: 41.8 cm W: 44.7 cm H: 18.2cm L: 16.5 in W: 17.6 in H: 7.2 in
------------------	--

Safety & EMC Regulations
--------------------------

CE, FCC Class B, UL, C-UL
---------------------------

Accessories
-------------

Accessory	Part No.
M-Vision LED Illumination Module	109-683
Infrared Remote (replacement)	112-961
Ceiling Mount Kit w/plate & 500mm pole	112-943
Gyrolock Ceiling Mount Kit w/plate & 230 - 300mm adjustable pole	112-411
Swivel Truss Mount Kit - fully adjustable for up to 50kg	116-201

*\*Dimensions included for reference only and are subject to change. Please download the full set of CAD files for this display for more accurate information.*

Downloads
-----------

<a href="#">PDF CAD Drawings</a>	<a href="#">User Guides</a>
<a href="#">AUTOCAD Drawings</a>	<a href="#">Important Information</a>

**DIGITAL PROJECTION, LTD** GREENSIDE WAY, MIDDLETON MANCHESTER, UK. M24 1XX  
T: +44.161.947.3300 | F: +44.161.684.7674 | [www.digitalprojection.co.uk](http://www.digitalprojection.co.uk)

**DIGITAL PROJECTION, INC** 55 CHASTAIN ROAD, SUITE 115 KENNESAW, GA. 30144  
T: 770.420.1350 | F: 770.420.1360 | [www.digitalprojection.com](http://www.digitalprojection.com)

**DIGITAL PROJECTION, CHINA** TOWER C, RM C1202, CAI FU JIA YUAN, NO. 19 XIAO YING STREET, CHAOYANG DISTRICT BEIJING,  
PR CHINA 100101  
T: +86.10.58239771 | F: +86 10 58239770

**DIGITAL PROJECTION, ASIA** 16 NEW INDUSTRIAL ROAD, #02-10 HUDSON TECHNOCENTRE SINGAPORE 536204  
T: +65.6284.1138 | F: +65.6284.1238