EMP-735 WIRELESS PROJECTOR





Catch the new wave in projectors



Wireless & PC Free

- 2000 ANSI lumens
- Automatic keystone correction
- Card player for PC free presentation
- 1.9kg



EPSON°



Network Screen

Lose the cables for the waves

Use wireless technology in place of cables to connect the projector to your wireless LAN-capable computer. Messy cables are a thing of the past. Make the most of the new found speed in wireless projectors, with the EPSON EMP-735.

Project your computer screen in real-time

Keep the table clear by using wireless technology instead of cables to project your images. Projections are swift, smooth and natural, keeping everyone focused on the business at hand without ever noticing the technology.

Make wireless multi-screen presentations

In a big room, laying the wiring to show presentations on multiple screens can be a major task. So we took the wiring out of the picture, along with the complicated settings. Connect up to four projectors at a time to the computer wirelessly - less time, no hassles.

Change presentations with just two clicks

No more fumbling with wires and computers to change presentations. Move to the next presentation with just two clicks of a computer. Make the most of your meeting time.







Control the projector from behind the scenes

Wireless technology allows you to make various settings and adjustments from a separate computer located away from the projector and screen. Enhance presentations in real-time without being noticed.



[These functions are also available when using wired LAN cards. Selected major wired LAN cards are supported.]

Would you like to clean the meeting room of those messy cables around the projector, make smoother transitions from one presentation to the next, maybe get by with a few less computers in the room. Now you can, with the new EPSON EMP-735 wireless projector.

The leading-edge wireless technology integrated in the EMP-735 helps to enhance your presentation experience while maintaining the superior image quality and speed synonymous with EPSON. Smooth image changes never before available with wireless connections. Instant presentation changeovers at the push of a button or the insertion of a memory card. Screen adjustments in real-time without interrupting presentations.

So if you are looking to streamline your presentation proceedings, look no further than the new EPSON EMP-735 wireless projector.

Card Player*

Give presentations from a memory card

No need to lug around a bulky computer, anymore. Just slip a memory card with your presentation data into the projector's slot and off you go. The presentation even starts automatically.



Edit from the projector


Use the projector's remote control to make presentation settings, such as page effects or the order of your slides and photos. Again, no need for the computer.



Application runs inside the projector; you control it with the remote control.

Instant digital photo presentations

Showing your digital photos on the big screen is as easy as inserting your digital camera's memory card into the projector. No need for a computer here, either. Compatible with photos from virtually any digital camera.



Additional Features

Auto keystone correction

No need to worry about unwanted slants and angles. Just place the projector and turn it on. The four screen corners are automatically adjusted to right angles-no settings, no buttons.

Lightweight and bright

The best of both worlds: Weighs in at a mere 1.9 kg; sends out an eye-opening 2000 ANSI lumens.

Six selectable projection modes

Simple image quality settings for every situation. Select one of six preset settings for optimally adjusted colours.

- Meeting
- Presentation
- RGB
- Normal
- Theatre
- Game

Broad range of colour reproduction with LCDs

The liquid crystal panels reproduce beautiful colours realistically and with high image quality.

Additional functionality

Further enrich your presentation experience with yet more built-in conveniences. For example, get a closer look with E-zoom or set up in an instant with "Plug and Present" Auto Setup.

*Card is not supplied.

SYDNEY

3 Talavera Road North Ryde NSW 2113 Tel: (02) 8899 3666 Fax: (02) 8899 3777

MELBOURNE

Ground Level 1155 Malvern Road Malvern Vic 3144 Tel: (03) 8823 9200 Fax: (03) 8823 9250

BRISBANE

Level 3, Waterfront Place 1 Eagle Street Brisbane QLD 4000 Tel: (07) 3360 0219 Fax: (07) 3360 0289

Suite 20, Level 3 1060 Hay Street West Perth WA 6005 Tel: (08) 9480 0418 Fax: (08) 9480 0443

ADELAIDE

Level 1, Carrington House 61-63 Carrington Street Adelaide SA 5000 Tel: (08) 8237 0518 Fax: (08) 8237 0519

AUCKLAND

245 Hobson Street Auckland NZ Tel: (09) 366 6855 Fax: (09) 366 6865

WELLINGTON

Level 6, City Tower 95 Custom House Quay Wellington NZ Tel: (04) 473 3494 Fax: (04) 473 4631

ABN 91 002 625 783 02/03

Visit our website:

www.epson.com.au www.epson.co.nz

MULTIMEDIA PROJECTOR

EPSON EMP-735 Projector



Specifications

RGB Liquid Crystal Shutter Projection System Front / Rear / Ceiling Mount	
Size Driving Method Pixel number Native Resolution Aspect ratio Pixel Arrangement Type F-number	Manual: zoom / focus 1.9 to 2.1
Zoom ratio Lens cover	31 to 36 mm 1:1.16 Attached
Type Life	150W UHE 1500H
Dichroic Mirror Separation & Prism combine method	
30 to 300inch (1.0 to 11.7m)	
9:1	
2000 ANSI lumens	
400:1	
85%	
Full Colour (16.77m	nillion colours)
1W	
ANGE	
13.5MHz to 162MH 15KHz to 92KHz 50Hz to 85Hz	lz
00112 10 00112	
Keystone (Vertical) / Brightness / Contrast / Tint / Saturation / Sound / Input signal etc.	
0 to 11 degrees Vertical: -15 to +15 degrees Yes	
Native Resize Signal type Video Signal	1024 x 768 1600 x 1200 / 1280 x 1024 / 800 x 600 / 640 x 480 Separate signal Analogue (0.7Vp-p,75 ohm /
Sync. Signal	Mac 0.714Vp-p, 75 ohm) Separate (positive & negative, bi-polarity 1-5Vp-p) / Composit (positive & negative, bi-polarity 1-5Vp-p) / Sync-on-green (negative, 0.3Vp-p) 500mVrms / 47Kohm
Video	Mini D-sub 15pin x1
Audio	Stereo mini jack
NTSC: 550 line (Depend on observa	PAL: 550 line ation of the multi burst pattern)
Video Standard	NTSC / NTSC4.43 / PAL / M-PA / N-PAL / PAL60 / SECAM
video Signal	Composite Video (1.0Vpp / Synnegative, 75 ohm) / S-Video (Luminous 0.714Vpp,
	Chrominous 0.286Vpp, 75 ohn / Component Video (Analogue Y level 0.7V 75 ohm / Cr Cb le+/-0.35V 75 ohm / sync.negat 0.3V or 3-state+/-0.3V on 7) / Video-RGB (0.7Vp-p, 75 ohm / Mac 0.714Vpp, 75 ohm)
	Size Driving Method Pixel number Native Resolution Aspect ratio Pixel Arrangement Type F-number F-number F-number Type Life Dichroic Mirror Sep J 30 to 300inch (1.0 9:1 2000 ANSI lumens 400:1 85% Full Colour (16.77n TW ANGE 13.5MHz to 162MH 15KHz to 92KHz 50Hz to 85Hz Keystone (Vertical) / Saturation / Sound 0 to 11 degrees Vertical: -15 to +15 Yes Native Resize Signal type Video Signal Sync. Signal Audio Signal Video Audio NTSC: 550 line (Depend on observate)

INPUT TERMINAL	Video	Composite Video: RCA x1 S-Video: Mini DIN Component Video: Mini D-sub 15pin (in common with Analogue RGB connector) Video-RGB: Mini D-sub 15pin (in common with Analogue RGB connector)	
	Audio	Stereo mini jack (in common with Analogue RGB audio jack)	
CARD I/O			
PCMCIA	Type Supported	Type I / II x1	
	Memory Card*	Compact Flash / Smart Media / Memory stick / SD / MMC / 3.3 volts type ATA Flash card / 5 volts type ATA Flash card / Micro Drive	
	Supported Wireless LAN card	Standard accessory only	
CONTROL I/O			
	I/O terminal	USB connector series B x1 (for mouse, K/B, control)	
OPERATING TEMPERATURE	5°C to 35°C <41°F to 95°F>		
COOL-DOWN PERIOD	about 45 seconds	about 45 seconds	
POWER SUPPLY VOLTAGE	100-120V / 200-240V ±10%, 50/60Hz AC		
DIMENSION			
EXCLUDE PROJECTION LENS & FEET MAXIMUM DIMENSION	276(W) x 70(H) x 190(D) mm 276(W) x 78.5(H) x 190(D) mm		
WEIGHT	Approx. 4.4lbs / 1.9Kg		
FAN NOISE	39dB		
ACCESSORIES			
POWER CORD COMPUTER CABLE	1.8m 1.8m, Mini D-sub 15pin (Male) - Mini D-sub 15pin (Male)		
VIDEO CABLE MOUSE CABLE REMOTE CONTROL SOFT CARRYING BAG WIRELESS LAN CARD CD USER'S MANUAL	RCA (Yellow) USB Mouse cable Card Type Supplied Supplied Application software Supplied	e & Driver software	
WARRANTY			
STANDARD	2 years		

^{*}Memory card and/or adaptor not supplied.



