

The high-value portable that doesn't sacrifice performance.

At Epson, we're committed to bringing you quality, reliability, and user-friendly solutions. With the EPSON PowerLite 7600p, we've gone one step further! This portable XGA projector offers remarkable performance-at a value you're sure to love. Weighing less than 15 lb, it boasts an incredible 2200 lumens and award-winning technology for bright, vivid colors and well-defined images. You already know us for printers that deliver world class image quality. And, you've probably used our innovative LCD technology in cell phones, PDAs, and camcorders. What you might not know is that Epson is also a world leader in LCD projector technology, which means you get superior images every time you present. As an added benefit, the EPSON PowerLite 7700p operates at a remarkably quiet 38db, so your audience is sure to hear every word you say. And, with multiple input capabilities, you'll have the flexibility to present from a variety of sources.

Brilliant images you've come to expect and worry-free operation you can count on–it's all within reach with the high-value EPSON PowerLite 7600p.

Ultra bright 2200 lumens; weighs just 14.9 lb

 Astonishing brightness, wherever you go, from a lightweight, travel-friendly projector

Superior detail and razor-sharp contrast

- Three 1.3" high aperture LCD's for evenly distributed color across the screen
- XGA (1024 x 768) resolution for sharp, vivid detail
- · 400:1 contrast ratio for blacker blacks and whiter whites
- · 200W UHE lamp

Quiet and unobtrusive

- Whisper-quiet performance (38db)
- · Minimal light leakage

State-of-the-art video performance

- Digital comb filter for extraordinary video clarity, reduced noise and improved contrast
- · Multiple video input capability
- HDTV-ready, supports 480i, 480p, 720p, 1080i and 1080p formats
- Digital Visual Interface (DVI) for convenient digital connectivity and plug and play operation

Easy installation, setup and operation


- Bayonet style twist-and-pull lens mount for quick, easy changes on site
- 30° digital keystone correction maintains distortion-free images
- EPSON SizeWise™ resizing technology supports virtually any computer (Mac or PC) up to UXGA (1600 x 1200)
- · Full-featured remote control
- · USB mouse with hot swap capability
- · Optional hard wired remote control adapter
- Lockable with Kensington[™] style locks
- RS-232 communication works with control systems and installation accessories from leading manufacturers like Crestron,™ Panja™ and Extron™
- Start Here Kit gets first-time users projecting in just minutes

Renowned EPSON service and support

- International warranty in over 45 countries, offered exclusively by Epson
- · 90-day bulb warranty for added dependability
- EPSON Road Service Program provides a replacement projector, typically within 24 hours
- EPSON PrivateLineSM dedicated toll-free support line is available from 6 a.m. to 6 p.m. PST Monday - Friday



Front View



EPSON PowerLite 7600p Specifications

| Projection System | EPSON (| original LCD prism technology | Video I/O | NTCO FFO ! | |
|---|---|---|--|--|--------------------------|
| Projection Method Front/rear/ceiling mount | | Display performance | NTSC: 550 line PAL: 550 line | | |
| LCD | 4.01 | | | (Depend on observation | |
| Size Driving method Pixel number | 1.3" EPSON Poly-silicon TFT Active Matrix 786,432 dots (1024 x 768) x 3 | | Input signal | of multi-burst pattern) NTSC/NTSC4.43/NTSC50/ PAL/M-PAL/N-PAL/PAL60/SECAM | |
| Aspect ratio Pixel arrangement | xel arrangement Stripe | | Input terminal | Composite video: RCA x 1 S-video; Mini D-sub 15pin x 1 Component video: | |
| Projection Lens Type F-number | Manual: zoom/focus 1.7 to 2.3 | | | Mini D-sub 15pin x 1 (common with component vi | ideo) |
| f-number Zoom ratio Lamp | 49 to 63mm 1:1.3 | | Audio terminal | RCA x 2 (for composite video S-video/component video) Stereo mini jack (for video-Ro | |
| Type Life (typical) | 200W UHE 1500H | | Output signal | Analog RGB (composite video, S-video, component video, Video-RGB are converted) | |
| Screen Width Ratio | · · · · · · · · · · · · · · · · · · · | 1.78 to 2.35:1 | | Separate HV (TTL) | |
| Screen Size (project Keystone Correction | · · · · · · · · · · · · · · · · · · · | 22" to 300" (1.0m to 14.5m) ±30° | Output terminal | Mini D-sub 15pin x 1 (Common Analog RGB) | |
| Brightness (typical) | | 2200 ANSI lumens | Control I/O | | |
| | | 400:1 | Mouse/serial I/O I/O terminal | D-Sub 9pin x 1 (RS-232C) | |
| Brightness Uniformity (typical) | | 85% | Mouse compatibility | PS/2, USB | |
| Color Reproduction | | 24 bit; 16.7 mil | Input terminal | | |
| Sound Output | | 3W + 3W SRS | Remote control | Stereo mini jack | |
| Operating Tempera | ture | 5°C to 40°C (41°F to 104°F) | Security | Kensington-style lo | ck provision |
| Power Supply Volta | | 100-240V ±10%, 50/60Hz AC | Warranty | anty international warranty 00 a | day lama |
| Power Consumption | | 285W/9W at stand by mode | | anty, international warranty, 90-c Program and EPSON PrivateLine c ada only) | |
| Dimensions | | 15.8"D x 10.9"W x 6.9"H | Supplied Accessories | add offig) | |
| Weight Approx. 14.9 lbs/6.8Kg | | Power cord, RCA audio cable, RCA video cable, remote control, | | | |
| Fan Noise | | 38db | 2 batteries, computer cable HD PS/2 mouse cable, USB mouse | 15/HD15, audio cable, video/aud | lio cable, |
| Effective Scanning I Pixel Clock Horizontal Vertical | Frequency Range | 14MHz to 230MHz 15KHz to 107KHz 43Hz to 120Hz | Product/Accessory Part Num Epson PowerLite 7600p Project Wide angle attachment lens | bers | EMP-7600 |
| Remote Control Fea | | urce selection, power, resize, | 1.4:1 to 1.8 Long throw attachment lens 2.3 to 3.0 | | ELPAW01 ELPAL01 |
| right/left mouse, click | | | Remote control receiver | | ELPST02 |
| RGB | | | Hard-wired remote control rece Replacement lamp | eiver kit | ELPST04 ELPLP12 |
| Display performance | Analog RGB I/O | Digital RGB Input | Component video cable(Dsub1 | 5 to 3RCA) for 5600 and 7600 | ELPKC19 |
| Native | 1024 x 768 | 1024 x 768 | ATA molded hard shell case Samsonite wheeled soft case | | ELPKS38 ELPKS35 |
| Resize | 1600 x 1200 1280 x 1024 | 1280 x 1024 800 x 600 | ATA shipping case Digital video cables | | ELPKS39 |
| | 800 x 600 640 x 480 | 640 x 480 | DVI to DVI, 3m DVI to DFP, 3m | | ELPKC20 ELPCK21 |
| Input terminal Video | MULD LAFT. A | DWT - D 4 | Ceiling mount | | ELPMB34 |
| | Mini D-sub 15pin x 1 (Select with manual switch) | DVI Type D x 1 (Select with manual switch, | Mac adapter set Kensington security lock Portable screens | | ELPAP01 ELPSL01 |
| | 5-BNCx1 | Exclusive to D-sub15) | 50" 60" | | ELPSC06 ELPSC07 |
| Audio | Stereo mini jack | | 70" | | ELPSC07 |
| Addio | (for Mini D-Sub 15) RCA x2 (for 5-BNC) | | Support-The Epson Connect Pre-Sales Support U.S. and Car Automated Technical Support | ada 80 | 0-463-7766 0-922-8911 |
| | | | | | |
| Output terminal Video | Mini D-sub 15pin x 1 | | Internet Web Site | WWW | v.epson.com |



Epson America, Inc.

3840 Kilroy Airport Way, Long Beach, CA 90806

Epson Canada, Ltd.

550 McNicoll, Willowdale, Ontario M2H 2E1

Epson Latin America

6303 Blue Lagoon Drive, Miami, FL 33126