

PJ-LC5

HITACHI'S NEW PJ-LC5 HOME CINEMA PROJECTOR WILL MAKE YOU THINK AGAIN ABOUT THE WAY YOU ENJOY MOVIES AND TELEVISION AT HOME.

The PJ-LC5 is a stylish, compact and portable LCD projector ideally suited for use in the home. Easy to set up to watch sports events or even to enjoy computer games on a bigger screen. It offers high quality performance at excellent value for money.

The PJ-LC5 can display a 60" diagonal image from only 1.8m away. It is also one of the quietest LCD projectors available generating just 27dB* of acoustic noise.

Hitachi's advanced Motion Adaptive Progressive Scan technology delivers high quality, flicker-free pictures. You can also customise and save your own projector settings.

- Low acoustic noise: 27dB*
- 60" diagonal image at only 1.8m distance
- 1200 ANSI Lumens
- 1.2x Optical Zoom
- Motion Adaptive Progressive Scan
- Digital Keystone Correction
- Pin Code Security Function

*Whisper Mode

HITACHI
Inspire the Next



PJ-LC5

Technical Specifications

HITACHI

Inspire the Next

OPTICAL

Optical Structure	0.55" P-Si active matrix TFT x 3
LCD Panel	0.55" P-Si TFT with MLA x 3
Resolution	800 dots x 600 lines
Lens	F1.6-1.8 (f=16.8-20.2mm), x 1.2 Manual Zoom
Lamp	130W UHB
Lamp Life	2000 (4000 Whisper Mode)
Brightness	1200 ANSI Lumens, Normal Mode 960 ANSI Lumens, Whisper Mode
Contrast Ratio	300:1 (typ)
Focus Distance	0.9-9.2m wide, 1.1-11.0m tele
Display Size	30"-300" diagonal
Colour	8 Bits/colour, 16.7M colours

COMPATIBILITY

Composite Video	NTSC, PAL (-BGDHI), SECAM, PAL-M, PAL-N, NTSC4.43, PAL60
Component Video	SDTV: 525i (480i), 525p (480p), 625i (575i) HDTV: 750p (720p@60Hz), 1125i (1080@50/60Hz, 1035i@60Hz)
Computer	IBM Compatible VGA, SVGA, XGA, (Smart Resizing), SXGA Capability, MAC 13", MAC 16" (PixelWorks Chip PW168)
Plug & Play	DDC1/2B
Frequency Range	Horizontal: 15-91kHz, Vertical: 50-120Hz

FEATURES

Keystone Correction	Fixed 9:1 upward shift
Image Control	4x Digital Magnification, Freeze Frame, Mirror Reverse & Invert Image
Speakers	1W
Other	MENU: 15 Language: (English, French, German, Spanish, Italian, Norwegian, Dutch, Japanese, Portuguese, Simplified Chinese, Korean, Swedish, Russian, Finnish, Polish), Freeze Function, Magnifying Digital Gamma Correction, My Memory, 3D Y/C separation, 2-3 pull down Electrical v Keystone Correction, Auto Configuration (H-Size, Position) PIN Lock System

CONNECTORS

Computer Input	1 x RGB analogue - 15-pin HD D-sub 1 x Audio - stereo mini-jack
Audio Input	2 x RCA Jack for Video Input 1 x Stereo Mini Jack for Data Input
Video Input	1 x RCA Jack 1 x S-Video Jack 3 x RCA Jack for Component
Control	1 x 9-pin D-sub for RS232 Control

POWER

Power Supply	100-120/220-240V AC
Power Consumption	220W

PHYSICAL


Dimensions	332 x 92 x 254mm (W x H x D)
Weight	2.9Kg
Noise Level	31dB/27dB (Whisper Mode)

SUPPLIED WITH


Remote Control
Safety Instructions
Quick Guide
Power Cord
Batteries
RGB Cable
User Manual (English, German, French, Italian, Spanish, Dutch, Norwegian, Portuguese, Korean, Chinese)

OPTIONS

Aluminium flight case (FLC200), Wheeled aluminium flight case (FLC300A), Fabric Wheel Case (FLC800) accommodates projector and notebook computer



Projector Dimensions



All brand or product names are trademarks or registered trademarks of their respective owners. Design and specifications are subject to change without notice.

Image Size		Projection Distance	
Diagonal	Width (m)	PJ-LC5	
		Min (m)	Max (m)
30" (0.76)	0.61	0.9	1.1
40" (1.02)	0.81	1.2	1.4
60" (1.52)	1.22	1.8	2.2
80" (2.03)	1.63	2.4	2.9
100" (2.54)	2.03	3.0	3.6
120" (3.05)	2.44	3.6	4.4
150" (3.81)	3.05	4.6	5.5
200" (5.08)	4.06	6.1	7.3
300" (7.62)	9.9	9.1	10.9

HITACHI DIGITAL MEDIA
Hitachi Europe Ltd
Whitebrook Park
Lower Cookham Road
Maidenhead
Berkshire SL6 8YA
Tel: 01628 585 000
Fax: 01628 585 500
www.hitachidigitalmedia.com

The specification above and photography is for reference only and may be subject to change.