

Due to constant product development, specifications and design migh to change without notice. DOMINO Catalog - WORLD - August 2003



WWW.SIMZ.COM

Headquarters: SIM2 MULTIMEDIA S.p.A.

Viale Lino Zanussi, 11 33170 Pordenone - Italy Tel. +39.0434.383256 Telefax +39.0434.383260 E-mail: info@sim2.it Web site: www.sim2.com

USA: SIM2 SELECO USA INC. 10108 USA Today Way

Miramar, FL 33025 Tel. +1.954.442.2999 Telefax +1.954.442.2998 E-mail: sales@sim2usa.com Web site: www.sim2usa.com

UK: SIM2 UK LTD

Steinway House Worth Farm, Gewerbepark, 17 Little Horsted Nr. Uckfield East Sussex TN22 5TT Tel. +44.01825.750850 Telefax +44.01825.750851 Web site: www.sim2.co.uk

Germany: SIM2 DEUTSCHLAND GmbH

D 35606 Solms Tel. +49.0800.8007462 Telefax +49.0800.9007462 E-mail: info.de@sim2.it Web site: www.sim2.com









It's in black and white...

The perfect synergy between high quality video projection and audio hi-fi, will transform your living room into a movie theatre, sports stadium or even the front row of an opera house or concert hall. The projector, an essential part of any true home theatre concept, can create the ultimate viewing experience, changing your perception of home theatre forever. The digital home theatre revolution is here, bringing with it an awesome combination of digital surround sound and big screen picture with a clarity and fidelity never before achievable in this exciting evolving industry.

The new SIM2 DOMINO delivers an outstanding image quality synonymous to SIM2 Multimedia and has many distinguished features: blacks & whites are exceptional on and off screen, creating an impressive depth of vision; a true cinema experience can be created with the addition of a long throw lens, allowing the projector to be positioned behind the viewer - equally, the projector is so versatile, it can be placed on a bookshelf or installed on the ceiling opposite the screen; an exceptionally quiet mechanical design has been developed by SIM2 for extremely low acoustic noise.



...Outstanding home theatre!





Picture perfect.



Digital Light Processing is the cinema standard to project film & video and is based on the DMD™ developed by Texas Instruments.

DLP™ technology delivers bright, crisp and precise image clarity with superior resolution and colour rendition.



DOMNO we lead, others follow.







Connect a world of possibilities.

DOMINO features a wide selection of inputs, enabling connection to all video and PC devices and complete compatibility with all video sources including high definition ATSC with both 4:3 and 16:9 display modes.

Sit back, relax & enjoy the action.

■Easy to install.

Easy to use.

Easy to enjoy.







Big screen, feel the passion.

■ The best white: Superior optics and white uniformity.

■ The best black: Optimum contrast and black level detail.



Even in black and white.









A name you can trust.

SIM2 Multimedia is a world-leading manufacturer with more than 10 years experience in cutting edge technology. Recognised worldwide for their innovation and excellence, SIM2 is dedicated to bringing a cinema-quality picture into your home. You can be confident that a SIM2 projector is the right choice for style, colour and picture clarity.



Technical features.

Domino 20 - Domino 30

LIGHT FNGINE

DLP™ type: Proprietary sealed optical engine based on 1-chip DMD™ Resolution: 1024x576 pixels (Domino 20)

1280x720 pixels (Domino 30)

Lens: High quality, high resolution optics with both motorised zoom and focus adjustments

Throw ratio Domino 20: 2.2 - 3.1:1 (16:9 mode) 3.0 - 4.1:1 (4:3 mode)

Throw ratio Domino 30: 1.8 - 2.4:1 (16:9 mode) 2.4 - 3.0:1 (4:3 mode)

Lamp power consumption & life time: 120W, 6000 hours*

INSTALLATION

Lens shift: +/-8°

Digital keystone adjustment:+/-38° ver., +/-14° hor. (Domino 20) +/-19° ver., +/-12° hor. (Domino 30)

Picture size: 50-250 inches diagonal Aspect Ratio: 4:3, 16:9, anamorphic, letterbox plus 3 custom-user adjustments + panoramic & pixel to pixel

ELECTRONICS

Horizontal & vertical scan freq.: 15-80 KHz/48-100 Hz

Video standards and graphic resolution: PAL B,G,H,I,M,N,60, SECAM, NTSC 3.58 & 4.43 automatically selected. HDTV ATSC standards (480p, 1080i, 720p)
PC input: VGA, SVGA, XGA, SXGA, UXGA DCDi™ by Faroudja
Contrast ratio (Full On/Full Off): 2000:1
Colour temperature: 3 preset colour temperatures selectable by remote control + 1 user adjustment
Special video adjustment: Luma − Choma delay adjustment by OSD

INPUT/OUTPUTS

- 1 Composite video via RCA connectors
- 1 S -VHS via mini Din 4 pin
- 1 RGBHV via Dsub 15 (PC input)
- 1 x RGBS/YCrCbS via 4xRCA connectors
- 1 x RS232 on Dsub 9 pins connector

GENERAL SPECIFICATIONS

Control: control software upgradable via RS232 serial interface Power consumption:170W max

<u>Mains Voltage range</u> and frequency:

120-240 Vac +/-10%, 48/62 Hz

Weight: 5.0 Kg (11 lbs)

Cabinet dimensions (WxHxD): 350x167x318mm

(13.8"x6.6"x12.5")

Standard cabinet colours: Black shadow or White evolution

Safety – in compliance with EN 60950/UL1950 Emission – in compliance with EN 55022 class B/150 KHz – 30 MHz Recyclable packaging

SUPPLIED ACCESSORIES

AC power cords (EU,UK, and USA) length 3m User standard remote control with batteries Installation and user manual





(*) Lamp life: the hours have been calculated under strict test conditions. Misuse or improper conditions may alter it.

