

TS350 Projector

Delivering the Big Picture

The Optoma TS350 data projector offers a balance between price and performance. The TS350 comes with the features and functionality to deliver a comprehensive presentation solution. Compact, lightweight and practical, the TS350 fits today's demanding applications and environments.



Features

- Native SVGA (800 x 600) resolution professional projector
- 2000 lumens of brightness for dazzling images in any environment
- 2000:1 contrast ratio
- User password security locking system
- HDTV compatible (720p, 1080i)

Specifications

Brightness

2000 Lumens

Resolution

Native SVGA (800 x 600)

Contrast Ratio

2000:1

Lamp Life and Type

2000/3000 Hours (STD/ECO)
180W UHP

Display Type

Single 0.55" DDR DMD™ DLP®
Technology by Texas Instruments

Throw Ratio

1.94 - 2.13:1 (Distance/Width)

Projection Distance

3.9' to 39' (1.2 to 11.9 m)

Image Size

34" to 306" (0.9 to 7.8 m)

Aspect Ratio

4:3 Native, 16:9 & 5:4 Compatible

Vertical Refresh Rate

56 to 85 Hz

Keystone Correction

± 16° Vertical

Displayable Colors

16.7 Million, 256 Shades of Gray

Uniformity

85%

Remote Control

Full Function IR Remote

Computer Compatibility

All Resolutions Supported up to SXGA+;
PC and Macintosh Compatible

Video Compatibility

NTSC: M (3.58MHz), 4.43 MHz, 480i;
PAL: B, D, G, H, I, M, N, 576i;
SECAM: B, D, G, K, K1, L;
HDTV: 480p, 576p, 720p, 1080i

Projection Lens

F= 2.7~3.0, f = 21.83~23.81 mm,
1:10X Manual Zoom and Focus

User Controls

Advanced Adjustability Options Through
the On-Screen Display

I/O Connection Ports

VGA-In, S-Video, Composite RCA Video,
RS-232

Projection Method

Front, Rear, Table Top and Ceiling Mount

Weight

4.5 lbs

Power Supply

100-240 Volts, 50 to 60 Hz

Operating Temperature

5 to 35°C, 80% Max Humidity

Storage Temperature

-20 to 60°C, 80% Max Humidity

Dimensions (W x H x D)

9" x 3.74" x 8.26"
(230 x 95 x 210mm)

Noise Level

32dB (ECO)

Power Consumption

190W, <10W Standby Power

Warranty

Three Years Optoma Express
Replacement Service,
One Year on Lamp

Standard Accessories

AC Power Cord, VGA to VGA Cable,
Lens Cap, Remote Control, Batteries
for Remote, Carrying Case, CD-ROM
User's Manual, Quick Start Guide and
Warranty Card

Optional Accessories

15-pin to 3 RCA Component-HDTV
Adapter, S-Video Cable, Composite
Video Cable, RS-232 Cable, SCART
Adapter and GrayWolfII™ Series
Screens

UPC

796435 11 311 7

