

ELM R12 DIRECTOR

Ultimate Power and Brightness

Barco's ELM R12 DIRECTOR combines exceptional light output and high resolution with advanced signal processing to deliver remarkable performance breakthrough for large screen video projection. Equipped with an innovative Digital Light Processing™ (DLP™) sub-system, and state-of-the-art optical system, the ELM R12 DIRECTOR delivers an ultra-high light output of 12,000 ANSI lumens. The Barco ELM R12 DIRECTOR offers the ultimate display solution for big and bright environments.

Ultra high brightness

12,000 ANSI lumens

• Unique edge-blending software: ScenergiX

Increase the amount of information by displaying panoramic images.

Obtain smooth overlaps when projecting with multiple projectors.

• High Contrast Mode

Enhances contrast ratio up to 900:1 for high demanding applications

• Seamless source switching

Switch sources on the fly Use special transition effects like dissolve, wipe in/out ...

• Modular future-proof structure

Allows quick set-up and easy serviceability

• Optional Network Interface

Remote control & diagnostics





ELM R12 Director Specifications

Light Output

12,000 ANSI lumens*

Brightness Uniformity

> 90% for the total screen area

Digital MicroMirror Device™

3 high resolution SXGA DMDs

Resolution

1280 x 1024 pixels

Lamp

3.0 kW Xenon

Typical lifetime: 750 hours Maximum lifetime: 1000 hours

Contrast Ratio

Standard mode: 450:1 (full field) High contrast mode: 900:1

Lens Shift

Motorized V shift: up to 100% Motorized H shift: up to 85%

Available Lenses Order No.

Fixed - QLD (1.2:1)	R9840120
Zoom - QLD (1.5 - 2.0:1)	R9840130
Zoom - QLD (2.0 - 2.5:1)	R9840140
Zoom - QLD (2.5 - 4.0:1)	R9840150
Zoom - QLD (4.0 - 7.0:1)	
Zoom - OLD (5.6 - 12:1)	R9840430

Remote Control

All controls are accessible through a soft-touch panel or a userfriendly back-lit infrared remote

- Source switching
- User settings per source
- Installation and service adjustments

Other Features

- Seamless switching with crossfade effects
- Built-in light shutter
- Modular construction
- ScenergiX: optional
- Network connection: optional

* measured with QLD 1.5 - 2.0:1, on axis

Compatibility

- Pixel map processor for computers and workstations with a resolution of up to 1600 x 1280
- All current video sources in Composite, S-VHS, RGB or Component or Serial Digital Format
- All currently proposed HDTV, extended and improved television standards (Eureka 95, Hi-Vision, ACTV, IDTV, EDTV,...)
- Most Macintosh computers
- Two digital input slots to allow for direct digital interfacing with current and future digital inputs

Fixed Inputs

- 2 Multifunctional 5-cable inputs for the connection of RGB analogue signals with standard sync (BNC connectors) or tri-level sync, sync on green or separate sync, Standard Video signals, S-VHS
- 2 Multistandard DVI

Modular Inputs

Two input slots for digital input modules:

- SDI (Serial Digital Input) (one provided standard)
- HD SDI (optionally available)

Power Consumption

Max. 3750 Watt

AC Power

230 V +-10%

Weight

Net weight 135 kg / 298 lbs (including rigging gear)

Order Information


Projector body R9002860 Spare lamp (including housing) R9840190


Refurb lamp (returned housing) R9840220

Video input with decoder

	R9841170
SDI input card	R9840110
HD-SDI input card	R9840450
SCENERGIX	R9840870

Dimensions	inch	mm
L W H	55.9 24.9 24.6	1,420 632 624







BARCO Projection Systems is an ISO 9001 registered company.

The information and data given are typical for the equipment described. However any individual item is subject to change without any notice.

The latest version of this Product Sheet can be found on www.presentations.barco.com







BarcoProjection - Intelligent Displays Noordlaan5 - 8520 Kuurne - Belgium Fax (32) (56) 36-8651 E-mail: info.presentations@barco.com

BarcoProjection

3240 Town Point Drive Kennesaw, GA 30144

Phone 770-218-3200 Fax 770-218-3250 E-mail: BPSmarketing@barco.com

