


3M™ Digital Projector DX70




Utilizing the XGA DarkChip3™ DLP® Technology from Texas Instruments, the 3M Digital Projector DX70 offers a bright 3800 ANSI Lumen video and data display that will make your images command attention. The full connectivity makes this an ideal projector for larger conference or training rooms, boardrooms, ballrooms or virtually any multi-purpose environment that requires crisp, clear multi-media display. For customers looking to the DLP technology for longer projector life, the DX70 is also the only 3M projector to offer a High-Usage Warranty Upgrade for unlimited hours of usage during the 3-year warranty term.



Features

- XGA (1024 x 768) Resolution
- 3800 ANSI Lumens
- Lightweight at only 8 lbs.
- Digital Keystone Correction
- 2 RGB Inputs, 1 RGB Output
- 4:3 native aspect ratio; 16:9 supported
- DVI-D Input
- Network Control
- 30" - 350" Image Range
- 3-Year Standard Warranty Included
- High Usage Warranty Upgrade Available



1-800-328-1371
www.3m.com/meetings



3M™ Digital Projector DX70 Specifications & Accessories

Optical

Resolution:	Native: True XGA (1024 x 768) Maximum: UXGA (1600 x 1200)
Imager set:	Single 0.7" XGA DarkChip3™ DLP® Technology by Texas Instruments
Aspect Ratio:	4:3 Native and 16:9 Supported
Colors:	16.7 Million True Colors (24 bit)
Brightness:	3800 ANSI Lumens (Maximum Rating)
Contrast Ratio:	2500:1
Projection Lens:	F2.4-2.6 (f=28 - 33.6 mm)
Screen Size (range):	30-350" Diagonal
Zoom / Focus:	Manual
Zoom Ratio:	1.2:1
Optional Lenses:	NA
Lamp:	Osram 300W (Normal Mode), 250W (Whisper)
Lamp Life:	2000 Hours (Normal Mode), Up to 3000 Hours (Whisper Mode)

System Specifications

Video Compatibility:	NTSC, NTSC 4.43, PAL (B, D, G, H, I, M, N) SECAM (B, D, G, K, KI, L)
SDTV/HDTV:	525i (480i), 525p (480p), 625i (576i), 750p (720p@60Hz), 1125i (1080i@60Hz)
Computer Resolution:	640x480 (VGA), 800x600 (SVGA), 1024x768 (XGA), 1280x1024* (SXGA), 1400x1050* (SXGA), 1600x1200* (UXGA), 832x624 (MAC 16")
<small>*resolution digitally compressed</small>	
Digital Keystone Correction:	Vertical & Horizontal: +/- 15°
Audio:	2x2W
Noise Level:	Normal 38dB; Whisper 35dB
Horizontal Scan:	31.5-91 KHz
Vertical Scan:	56-85 Hz
Power Consumption:	385W (Normal Mode), 320W (Whisper)
Power Supply: Universal:	100-120V/220-240V, 50/60 Hz
Regulatory Approvals:	UL, cUL, FCC Part 15 Class B, CE, EN60950-1, WEEE
Operating Temperature/Altitude:	5°-35° C/0-2500 Ft 5°-30° C/2500-5000 Ft 5°-25° C/5000-10000 Ft
Storage Temperature:	-4°-140° F (-20° to 60° C)
Maximum Humidity:	80% RH with No Condensation

Size

Dimensions (W x H x D):	13.2" x 3.9" x 9.8" (335 x 100 x 250 mm)
Weight:	8 lbs/3.6 Kg

Technical Support

- Free unlimited software downloads and updates available on our website at www.3m.com/meetings
- Toll-free 24/7 Technical Support by calling **800.328.1371**

Specifications subject to change without notice.

3M is a trademark of 3M Company. Used under license in Canada. All other trade names referenced are the service marks, trademarks, or registered trademarks of their respective companies.

© 3M 2007. All Rights Reserved. V061807

3M Visual Systems
Building A 147-5N-01
6801 River Place Blvd.
Austin, TX 78726-9000

3M Canada
P.O. Box 5757
London,
Ontario, Canada
N6A 4T1

3M Mexico, S.A. de C.V.
Apartado Postal 14-139
Mexico, D.F. 07070
Mexico

Hg — LAMP CONTAINS MERCURY. Manage in accord with disposal laws. See www.lamprecycle.org or call 1-800-328-1371 (USA), 1-800-364-3577 (Canada). For product disposal see www.eiae.org (USA) or www.epsc.ca (Canada).

Screen Size (Diagonal)	Image Size 4:3		Image Size 16:9	
	Projection Distance		Projection Distance	
	Minimum (m)	Maximum (m)	Minimum (m)	Maximum (m)
40 (1.0)	64 (1.6)	77 (2.0)	70 (1.8)	84 (2.1)
60 (1.5)	96 (2.4)	115 (2.9)	105 (2.7)	125 (3.2)
100 (2.5)	160 (4.1)	192 (4.9)	174 (4.4)	209 (5.3)
150 (3.8)	240 (6.1)	288 (7.3)	261 (6.6)	314 (8.0)
200 (5.1)	320 (8.1)	384 (9.8)	348 (8.8)	418 (10.6)
300 (7.6)	480 (12.2)	576 (14.6)	522 (13.3)	627 (15.9)

Note: These sizes are ±10 percent. This is due to variations in the manufacture of the lens. If you are close to one of the endpoints you should verify with your unit that the image is the proper size at the proper distance.

Warranties

See www.3m.com/us/meetings/warranties for details on warranties.

Projector:	3 Years (or 2500 Hours) Standard
Lamp:	90 days or 180 Hours Remainder of 1st Year Prorated
Optional Coverage:	<i>Ultra Value Warranty Enhancement</i> — Includes free lamp, free loaner while unit is being repaired and expedited service. Not available outside U.S. <i>High-Usage Warranty Upgrade</i> — Covers unlimited hours of usage during 3 year term. <i>Note: Standard Warranty covers 2500 hours of usage during 3 year term.</i>

Connections

Computer

- 3 - Analog RGB (2 inputs, 1 output)
- 1 - USB Mouse (M1-D)
- 1 - Serial Control
- 1 - Network Control
- 1 - DVI-D Input

Video

- 1 - Composite (RCA Jack)
- 1 - S-Video (Mini-Din 4 pin)
- 1 - Component (RCA Jacks x3)
- 1 - Video/Audio (1 In/Out -shared)

Audio in/out

- 2 - Mini Stereo Jack Ins
- 1 - Mini Stereo Jack Out

Accessories Included

- Power Cords (US, UK, Europe)
- Remote Control (with 2 AA batteries)
- Multi-language Operator's Guide CD
- Free unlimited software downloads and updates available on our website at www.3m.com/meetings
- VGA/RGB Cable
- S-Video Cable
- USB Cable

Optional Accessories

- Ultra Value Enhanced Warranty (WDX70)
[U.S. Only] 78-6969-9920-6
- Lamp Replacement Kit (LKDX70) 78-6969-9918-0
- Universal Ceiling Mount 78-6969-9874-5
- High Usage Warranty (HUWDX70) 78-6969-9921-4

Important Notice

All statements, technical information, and recommendations related to 3M's products are based on information believed to be reliable, but the accuracy or completeness is not guaranteed. Before using this product, you must evaluate it and determine if it is suitable for your intended application. You assume all risks and liability associated with such use. Any statements related to the product which are not contained in 3M's current publications, or any contrary statements contained on your purchase order shall have no force or effect unless expressly agreed upon, in writing, by an authorized officer of 3M.

Warranty; Limited Remedy; Limited Liability

This product will be free from defects in material and manufacture for a period of 3 years or 2500 hours from the date of purchase. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. If this product is defective within the warranty period stated above, your exclusive remedy shall be, at 3M's option, to replace or repair the 3M product or refund the purchase price of the 3M product. Except where prohibited by law, 3M will not be liable for any indirect, special, incidental or consequential loss or damage arising from this 3M product, regardless of the legal theory asserted.