## **BumbleBee**



BRIGHTNESS 150 ANSI Lumens (28" diagonal) RESOLUTION 800x600 native 1280x1024 compressed DISPLAY TYPE Single 0.55 12° DDR DMD CONTRAST RATIO 1000:1 ASPECT RATIO 4:3 Native 16:9 Compatible LAMP OSRAM Ostar LED Module LAMP OSRAM Ostar LED Module LAMP LIFE 10,000 hours DIAGONAL IMAGE SIZE 12" - 60" inches PROJECTION LENS Fixed zoom with focus adjustment	Special features of the BumbleBee include:   Utra Portable—Weighing in at 1 lb—this tiny 'Bee' can be taken anywhere!   DE Lamp—A 10,000 hour lamp life will last for years and years.   D Card Slot—Versatility for ultimate presentations and slide shows on the go.   Rechargeable Battery—Connect to power or run from a battery. Use it outside or where power isn't available.
OPTIONAL ACCESSORIES: Extended Warranty Battery Pack Composite Video Cable Remote	SHIPS WITH: User Manual AC/DC Adaptor—Power Cord Composite Video Cable Remote Control Soft Nylon Case
THROW DISTANCE 1.3' - 6.6' feet 40 - 200 cm THROW RATIO 1.32:1 (fixed lens) INPUTS Audio in Component Composite Video S-Video SD Card VGA OUTPUTS Audio out COMPATIBILITY VGA, SVGA, XGA, SXGA, Mac KEYSTONE +/- 15° vertical VIDEO NTSC, PAL, SECAM	PWR. CONSUMPTION 30 W Standard mode HDTV / EDTV / SDTV 480p, 720p, 1080i AUDIO 1 X 0.3 watt speakers DIMENSIONS (WXDXH) 4.7" x 1.8" x 3.8" inches 121 x 47 x 99 mm WEIGHT 1.0 lbs without battery 2.0 with battery DECIBEL RATING 30 dB WARRANTY 2 year parts & labor FCC CERTIFICATION Class B POWER SUPPLY 100-240 AC 50-60 Hz
<b>BOXLIGHT</b> ® CORPORATION	www.boxlight.com Direct 800.762.5757 International 360.779.7901

19462 Powder Hill Place, Suite 101 Poulsbo, WA 98370

Partners 866.688.3636