

P1265 PROJECTOR

DLP Technology – Ultra portable

Acer P1265 combines extra portability and excellent colour reproduction to form the ultimate presentation tool. The Acer P1265 is well suited for the most demanding Multimedia presentation applications

Why a P1265 Projector?

- Resolution XGA (1024 X 768), SXGA (1400 x 1050)
- Contrast Ratio 2000:1
- Brightness 2,400 ANSI Lumens
- Projection Distance
3.3' (1.0m) ~ 39.0' (11.9m)



P1265 PROJECTOR

DLP Technology – Economic and Mobile

Features	Specifications
Resolution	Native SVGA (800 x 600) Maximum SXGA (1,280 x 1,024), WXGA+ (1,440 x 900)
Computer Compatibility	IBM PC and Compatibles, Apple Macintosh, iMac, and VESA Standards WXGA+ (1,440 x 900), WXGA (1,280 x 800, 1,280 x 768), SXGA (1,280 x 1,024), XGA (1,024 x 768), SVGA (800 x 600), VGA (640 x 480)
Video Compatibility	NTSC (3.58/4.43), PAL (B/D/G/H/I/M/N), SECAM (B/D/G/K/K1/L), HDTV (720p, 1080i), EDTV (480p, 576p), SDTV (480i, 576i)
Aspect Ratio	4:3 (Native), 16:9
Contrast Ratio	2000:1
Displayable Colors	16.7 Million Colors
Brightness	2,400 ANSI Lumens (Standard), 1,920 ANSI Lumens (ECO)
Projection Lens	F = 2.41 ~ 2.55, f = 21.79mm ~ 23.99mm 1:1.1 Manual Zoom and Manual Focus
Projection Screen Size	23" (58cm) ~ 300" (762cm)
Projection Distance	3.3' (1.0m) ~ 39.0' (11.9m)
Throw Ratio	50"@2m (1.95 ~ 2.15:1)
Horizontal Scan Rate	56 ~ 85 Hz
Vertical Scan Rate	56 – 85Hz
Lamp Type	180 W user replaceable P-VIP lamp
Lamp Life	3,000 Hours (Standard), 4,000 Hours (ECO)
Keystone Correction	+/-40 Degrees (Vertical)
Projection Mode	Front, Rear, Front-Ceiling, Rear-Ceiling
Audio	One Internal Speaker with 2 watts Output
Weight	3.0kg
Dimensions	299 x 229 x 93 mm (11.8" x 9.0" x 3.7")
IR Remote Control	IR remote control with laser pointer & PgUp/PgDn functions
Digital Zoom	2xYes
Power Supply	AC input 100~240V auto-switching power supply
Power Consumption	230 Watts (Operation), 10 Watts (Standby)
Operating Temperature	5 – 35 Degrees
Noise Level	28 dBA (Standard mode), 24 dBA (ECO mode)
Uniformity	90%