

BenQ Digital Projector

BenQ
Specifications

MP511



HIGHLIGHTS

- **2000 AL Ultra High Brightness**
- **2000:1 High Contrast Ratio**
- **SVGA Native Resolution**
- **Golden Ratio Color Wheel**
- **BrilliantColor**
- **Wall Color Correction**
- **3D Color Management**
- **Quick Auto Search**
- **Presentation Timer**
- **Panel Keylock**
- **11 sets of Application Modes**
- **Digital Zoom**
- **OSD FAQ**

Projection System	DLP™ technology by Texas Instruments®	
Panel	SVGA DMD™ x 1	
Native Resolution	SVGA (800 x 600)	
Brightness	2000 ANSI lumens	
Contrast Ratio	2000:1 (Full on/Full off)	
Aspect Ratio	4:3 Native, 16:9 Selectable	
Color	Full 16.7 billion color palette	
Lens	F=2.57 (Fixed)	
Zoom Ratio	Fixed	
Image Size (Diagonal)	31" to 300"	
Throw Ratio	2.0:1 (50"@2m)	
Lamp	180W, 2000/3000 hours (Normal/Economic mode)	
Computer Compatibility	VGA(640 x 350) to SXGA (1280 x 1024)	
HDTV Compatibility	480i, 480p, 576i, 576p, 720p, 1080i	
Video Compatibility	NTSC, PAL, SECAM	
Horizontal Frequency	31-82 kHz	
Vertical Scan Rate	42-85 Hz	
Input Terminals	PC	Analog RGB: D-sub 15 pin x 1(shared)
		Component Video: D-sub 15 pin x 1(shared)
	A/V	S-Video: Mini Din 4 pin x 1 Composite Video: RCA x 1
Control Terminal	USB Connector: USB x 1, Type mini B RS232: D-sub x 1	
Dimensions(L x W x H)	277 x 95x208 mm	
Weight	5.7 lbs (2.6 kg)	
Power Supply	100 to 240 VAC, 50 to 60 Hz	
Power Consumption	Max 260W	
Audible Noise	TBD	
On-Screen Display languages	English/ French/ German/ Italian/ Spanish/ Russian / Traditional Chinese/ Simplified Chinese/ Japanese / Korean/ Swedish/ Dutch/ Turkish/ Czech/ Portuguese / Thai / Polish	
Application Modes	PC Input:	A/V Input :
	Dynamic	Dynamic
	Presentation	Cinema
	Cinema	Standard
	sRGB UserI/ UserII	UserI/ UserII
Functions	Golden Ratio Color Wheel	Presentation Timer
	BrilliantColor	Panel Keylock
	Wall Color Correction	2 User application modes
	3D Color Mgmt	Digital zoom
	Quick Auto Search	OSD FAQ
Accessories (Standard)	User's Manual CD	Battery for R/C
	Quick Start Guide	VGA Cable
	Remote Control	Power Cord
Accessories (Optional)	Lamp Module	Soft Carry Case
	Ceiling Mount Kit	