

PJ759

**LIGHT, BRIGHT AND
PORTABLE PROJECTOR
WITH KEYSTONE CORRECTION**

Versatile performance leader.

The ViewSonic® PJ759 projector is a performance leader with a rich feature set at an affordable price. The PJ759 delivers 2,600 LUMENS AND 1024x768 XGA RESOLUTION, scalable up to 1600x1200 UXGA, for crisp, detailed images in any lighting situation. With SEVEN PICTURE MODES, including daylight and blackboard, whiteboard, greenboard, you can adjust the light output for any given environment. This versatile projector is easy to set up and its DIRECT OFF FEATURE allows you to unplug it and go. A wide array of PC AND VIDEO CONNECTIVITY OPTIONS let you deliver dynamic, versatile presentations and the easy lamp and filter replacement make maintenance a breeze. The PJ759 is ideal for table-top or mounted use in the office, classroom or on the road.



PORTABLE WITH EASY SET UP

- > **Bright in virtually any setting**
Packs 2,600 lumens in 7.8 pounds. It's the bright choice for mobile presenters.
- > **Quick set up**
Auto vertical keystone correction automatically squares the image for quick set up. The direct off feature lets you just unplug the projector and go.
- > **Enhanced security features**
Security bar and user-assigned PIN code protect your projector from theft and unauthorized use.
- > **Ultimate display source flexibility**
With two RGB inputs you can connect a computer or add a video source for dynamic meetings and presentations.
- > **Easy maintenance**
The sliding filter cover and simple lamp replacement from the top of the unit make maintenance a breeze.
- > **Whisper-mode extends lamp life and reduces noise output**
- > **The best warranty in the business**



VIEWSONIC
PRODUCTS, PROGRAMS,
AND SERVICES

ViewSonic®
See the difference® 

PJ759

LIGHT, BRIGHT AND PORTABLE PROJECTOR WITH KEYSTONE CORRECTION



PROJECTOR	Type	0.63 Poly-Si TFT with micro-lens	
	Pixel Format	1024x768 XGA	
	Lens	Manual zoom, manual focus	
	Zoom Factor	1.2	
	Keystone	Vertical $\pm 15^\circ$	
DISPLAY	Size	30"–300" (diagonally)	
	Throw Distance	35"–354"	
	Throw Ratio	1.5–1.7:1	
	Lamp	220W, 2,000 hrs. normal, up to 3,000 hrs. whisper-mode*	
	Brightness (max)	2,600 ANSI lumens	
	Contrast Ratio	500:1	
	Aspect Ratio	4:3 (native), 16:9	
AUDIO	Speakers	1x7W	
INPUT SIGNAL	Video	RGB analog, NTSC M, NTSC 4.43, PAL, SECAM, HDTV (480i, 480p, 576i, 720p, 1080i)	
	Frequency	F _H : 31~106kHz, F _V : 56~120Hz	
COMPATIBILITY	PC	Analog: from VGA up to UXGA (scaled)	
CONNECTOR	Mac®†	Analog: up to UXGA	
	RGB (input)	15-pin HD, D-sub (2)	
USB	Composite Video (input)	RCA jack (1)	
	S-video (input)	Mini-Din 4-pin	
	Component Video (input)	VGA DB-15 to component adapter**	
	Audio (input/output)	Stereo mini-jack 1-in, 1-out	
POWER	Voltage	For mouse control only	
CONTROLS	Consumption	100–240VAC, 50–60Hz (universal)	
	Basic	320W (typ)	
OPERATING CONDITIONS	OnView®	Standby, input, reset, V. keystone	
	Temperature	Language, brightness, contrast, gamma, color temperature, color, tint, sharpness, progressive, My Memory, aspect, overscan, V. position, H. position, H. phase, H. size, auto adjust, video NR, color space, component, video format, frame lock, computer in, resolution, auto keystone, information, V. keystone, whisper, mirror, volume, speaker, audio, language, menu position, OSD bright, blank color, start up, My Screen, My Screen Lock, message, source name, auto search, auto on/off, lamp time, filter time, My Button, service menu, security	
	Humidity	41–95°F (5–35°C)	
	Normal	10–85% (non-condensing)	
	Whisper-mode	36 dB (typ)	
	Physical (W x H x D)	30 dB (typ)	
	Net	13.4" x 3.9" x 10.6" (340mm x 100mm x 270mm)	
	Gross	7.8 lb. (3.5 kg)	
	REGULATIONS		17.0 lb. (7.7 kg)
	OTHER		UL 60950, C-UL, FCC-B, UL-DEMKO/GS, CCC, CB, CE, C-TICK, GOST, NOM, PSB, TUV-S
WARRANTY		Short throw, auto vertical digital keystone correction, progressive scan, 3:2 pull down, auto adjust, remote control, direct off, low noise (30 dB), unplug and go, white board, black board, green board, daylight mode, adjustable fan speed	
		Three-year limited warranty on parts and labor, first-year Express Exchange® Service. One-year limited warranty on lamp***	



ISO 9001:2000
FM 40187



ISO 14001:1996
FM 40968

ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.

ViewSonic®
See the difference® 

ProSelecta

View :: Compare :: Select - www.ProSelecta.com