

PLC-XF42

Brilliant Ideas for Great Images.

SANYO

- Brightness 9,000 ANSI lumens
- XGA Resolution (1,024 x 768)
- Contrast 1,100 : 1
- Horizontal and vertical lens shift function
- 11 interchangeable lenses, 7 adapter boards
- Four lamp system
- Network integration (optional)
- Real Colour Manager



ProSelecta

View :: Compare :: Select - www.ProSelecta.com

TECHNICAL DETAILS

PLC-XF42

Category	Professional
Panel	3 x 1.8" TFT p-Si (4:3)
Lamp	4 x 250 W UHP (LMP-49)
Brightness ANSI lumens	9,000
Lamp Service Life	2,000 h (Eco mode) / 1,000 h (Normal mode)
Standard Lens	Delivery without lens
Throw Distance Ratio	Depending on lens
Throw Distance	Depending on lens
Contrast Ratio	1,100 : 1
Resolution in pixels	1,024 x 768 (XGA)
Horizontal Resolution	800 TV lines
Uniformity	90 %
Bandwith/Frequency	230 MHz, horizontal 15–120 kHz, vertical 50–120 Hz
Colour Systems	PAL, SECAM, NTSC, NTSC4.43, PAL-M/N
Connections	Input 1: DVI-I (digital/analog); Audio: 2 x RCA (R/L mono); Control Input: Mini DIN 8-pin (RS232) Input 2: 5 BNC (RGBHV/Y-Pb/Cb-Pr/Cr); Audio: 2 x RCA (R/L mono); Control Input: Mini DIN 8-pin (RS232) Input 3: D-Sub15 (RGB); Audio: 2 x RCA (R/L mono) Input 4: freely configurable Control Input: Mini DIN 8-pin (RS232) Audio Output: 2 x RCA (R/L mono) Control Input 1: D-Sub9 (RS232) Control Input 2: USB type B (mouse control) Control Input 3: 3.5 mm Stereo Jack (IR remote control) Control Output: D-Sub9 (RS232)
Audio	–
Keystone Correction	vertical +/- 40°
Lens-Shift	10 : 0 to 0 : 10 vertical (for LNS-S02Z) 1 : 1 vertical (for LNS-W03) 1 : 8 to 8 : 1 vertical (for all others lenses) 1 : 1 horizontal (for LNS-W03/W04/W06) 2 : 3 to 3 : 2 horizontal (for all others lenses)
HDTV Signals	480i, 480p, 575i, 576p, 720p, 1,035i, 1,080i
Computer Compatibility	U-XGA/S-XGA+/S-XGA/W-XGA/XGA/S-VGA/VGA
Zoom/Focus	Depending on lens
Power Consumption/Voltage	1,500 W (Normal mode) / 120 – 240 V
Warranty	3 years
Dimensions (W x H x D)	581 x 252 x 783 mm
Weight	36.5 kg
Standard Accessories	IR remote control, batteries, operating manual, computer cable (D-Sub15/D-Sub15), power cable, software for Real Colour Manager PRO
Optional Accessories	7 optional adapter boards: DVI-I-Board (POA-MD18DVI); 5 BNC-Board (POA-MD16VD1); Y/C-Board (POA-MD03VD2A); D-Sub15-Board (POA-MD04VGA); HD-SD-SDI-Board (POA-MD17SDI); Network-Board (POA-MD13NET2); SDI-Board (POA-MD15SDI)
Lenses	11 interchangeable lenses Optional wide angle lenses: LNS-W01Z, LNS-W02Z, LNS-W03, LNS-W04, LNS-W06 Optional standard lenses: LNS-S03, LNS-S02Z Optional tele zoom lenses: LNS-M01Z, LNS-T01Z, LNS-T02, LNS-T03



Technical specifications subject to change without notice. Status 03/2007

