

High brightness, full-featured projector.

The ViewSonic® PJ557D DLP® projector features 2,200 lumens, native 1024x768 resolution, ultra-high 2000:1 contrast ratio and BrilliantColor™ for precise images in virtually any setting. This full-featured projector includes MULTIPLE INPUTS for connecting a computer or video source, DUAL 5-WATT SPEAKERS for complete multimedia presentations, VERTICAL KEYSTONE CORRECTION for easy image adjustment and DIRECT OFF FEATURE. Choose from whiteboard, blackboard or greenboard mode for the best picture on your projected surface. Eco-mode extends lamp life and reduces fan noise as low as 32 dB. Protect your projector from theft and unauthorized use with the Kensington® security port.

PJ557D

LIGHT, BRIGHT AND PORTABLE PROJECTOR

with BrilliantColor™



BRILLIANT PRESENTATIONS MADE EASY

- > **Bright in virtually any setting with 2,200 lumens**
Packs 2,200 lumens in just 6 pounds. It's the bright choice for mobile presenters.
- > **BrilliantColor™ technology**
DLP® projectors with BrilliantColor™ feature multi-color processing to produce nearly 50% brighter colors for a vibrant image on the screen that won't fade over time.
- > **Ultimate video source flexibility**
Connect a computer or add a video source for dynamic meetings and presentations.
- > **Supports HD signals including 720p and 1080i**
Capable of displaying HDTV signals as well as other video and data sources.*
- > **Multiple color correction picture modes**
Blackboard, greenboard, whiteboard and daylight picture modes give you the best possible picture regardless of the projection surface.
- > **OnView® controls for superior screen adjustability**
Screen geometry and color adjustments are precisely made via an easy-to-use on-screen menu.
- > **Eco-mode extends lamp life**
Extend the life of your lamp up to 4,000 hours** and reduce noise output.
- > **My Screen Startup**
Customize your startup with a company logo or favorite picture using the MyScreen function.



VIEWSONIC
PRODUCTS, PROGRAMS,
AND SERVICES

ViewSonic®
See the difference® 

PJ557D

LIGHT, BRIGHT AND PORTABLE PROJECTOR WITH BrilliantColor™



PROJECTOR	Type	0.55 DDR DMD, DLP®
	Pixel Format	1024x768 XGA
	Lens	Manual zoom, manual focus
	Zoom Factor	1.1
	Keystone	Vertical ± 40°
DISPLAY	Size	27.2"–250" (diagonally)
	Throw Distance	47.2"–393.6"
	Throw Ratio	1.97–2.16:1
	Lamp	180W, 3,500 hrs. normal, up to 4,000 hrs. eco-mode**
	Brightness (max)	2,200 ANSI lumens
	Contrast Ratio	2,000:1
	Aspect Ratio	4:3 (native), 16:9
AUDIO	Speakers	2x5-watt
INPUT SIGNAL	Computer and Video	RGB analog, NTSC, NTSC 4.43, PAL, SECAM, HDTV (480p, 720p, 1080i)
	Frequency	F _H :31–79kHz; F _V :50–85Hz
COMPATIBILITY	PC	Analog: from VGA up to SXGA (scaled)
	Mac®†	Analog: up to SXGA
CONNECTOR	RGB (input/output)	15-pin HD, D-sub (x2)
	Composite Video (input)	RCA jack
	S-video (input)	Mini-Din 4-pin
	Component Video (input)	VGA DB-15 to HDTV/component cable*
	Audio (input/output)	Stereo mini-jack
	RS-232	6-pin D-sub
USB		Type B for mouse control only and for firmware upgrade
POWER	Voltage	100–240VAC, 50–60Hz (universal)
	Consumption	250W (typ)
CONTROLS	Basic	Standby/on, input, menu
	OnView®	Display mode, brightness, contrast, keystone, aspect ratio, blank screen, gamma, white peaking, color temperature, user color, video (sharpness, saturation, tint), display (phase, tracking, H. position, V. position), advance (auto source, select, rear, ceiling, eco-mode, lamp hours, lamp reset, auto shutdown, OSD timeout, menu position, factory reset), audio (audio mute)
OPERATING CONDITIONS	Temperature	32–104°F (0–40°C)
	Humidity	10–90% (non-condensing)
	Altitude	0–10,000 ft.
NOISE LEVELS	Normal / Eco-mode	36 dB (typ) / 34 dB (typ)
DIMENSIONS	Physical (W x H x D)	8.9" x 4.3" x 8.8" (277mm x 109mm x 223mm)
WEIGHT	Net	6.0 lb. (2.7 kg)
	Gross	13.0 lb. (5.9 kg)
REGULATIONS		UL/cUL, FCC-B, CE, CB, CCC, IRAM, NOM, C-UL, ICES 003
RECYCLE/DISPOSAL		The lamp in this product contains mercury. Please dispose of in accordance with local, state or federal laws.
PACKAGE CONTENTS		Projector, power cable, VGA cable, RCA video cable, S-video cable, remote control with built-in laser, soft case, lens cap, Quick Start Guide, ViewSonic Wizard CD (with User Guide)
WARRANTY		3-year limited warranty on parts and labor, 1-year limited warranty on lamp, 1-year free Express Exchange® service.***

Optional Accessories

- Replacement lamp..... RLC-034
- Soft case with wheels..... CASE-006
- Extended Express Exchange® PRJ-EE-05-03
- Universal ceiling mount kit WMK-005
- VGA to component video adapter... ADPT-002
- Wireless G Presentation Gateway.... WPG-150



ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.

Sales: (888) 881-8781 • SalesInfo@ViewSonic.com • ViewSonic.com

*Optional cables required. **Running eco-mode exclusively can extend lamp life. ***See ViewSonic.com for full details. †Adapter may be required. Analog adapter available from ViewSonic. DLP® and the DLP logo are registered trademarks of Texas Instruments and BrilliantColor™ is a trademark of Texas Instruments. Specifications subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2007 ViewSonic Corporation. All rights reserved. [13726-008-10/07] PJ557D-1

ViewSonic®
See the difference® 

For more product information, visit us on the web at ViewSonic.com