

The ViewSonic PJ551 projector offers high performance in an ultra-light 2.5 kg package. Displaying 1,500 lumens and a high contrast ratio, the PJ551 delivers vibrant and rich colors with life-like depth, even in well-lit rooms. True 1024x768 resolution (1280x1024 maximum) produces exceptional image quality for both data and video. Short focal length and zoom let you set up just about anywhere. For performance and value, choose the projector that shines, the ViewSonic PJ551.





Ideal for mobile professionals.

Packs 1,500 lumens in just 2.5 kg. It's the bright choice for the mobile professional who demands brilliant images in virtually any setting.

Keystone Correction

Techniques used in the projector to minimize the visible effect of keystoning. Images are typically trapezoidal in shape and keystone correction is used to square the image.

Displays HDTV signals

ViewSonic projectors project a wide variety of content which including HDTV signals (480i, 480p, 575i, 720p and 1080i).

Automatic source detection for easy setup

Identify and project RGB and video inputs sources automatically, this is no need to switch source modes before projection.

Support 4:3 and 16:9 aspect ratio Offering increased flexibility for multiple viewing formats.

Easy setup and auto tuning One-touch setup button for fast, easy sync and sharp focus.

• Whisper Mode

Whisper-mode allows the user to operate the projector at two settings - "normal" for maximum performance and "whisper" for low noise levels plus extended lamp life.

Digital Gamma Correction

The 10-bit digital gamma correction circuits enable fine tonal expressions that cannot be reproduced by conventional technologies. Being able to reproduce fine differences in light and shade gives images a more 3D feeling and permits a rich range of image expressions.

Best Service & Support

At ViewSonic, we are devoted to customer satisfaction. We strive constantly to understand your interests and concerns, and treat you with respect, courtesy and consideration. For the warranty information, please contact your local ViewSonic distributor or ViewSonic service center.

ViewSonic Service Center : Taiwan - service@tw.viewsonic.com China - service@cn.viewsonic.com Japan - service@jp.viewsonic.com S. Asia & S. E. Asia - service@sg.viewsonic.com Australia & New Zealand - service@au.viewsonc.com H.K & S. Africa & other countries - service@em.viewsonic.com



		Model No : VPROJ25049-1W
LCD	Туре	0.7" PolySilicon TFT active matrix LCD
	Resolution	XGA 1024 x 768 compressed to 1280x1024
	Pixel Format	XGA 1024 (H) x 768 (V)
	Lens	Manual zoom/focus (1:1.2X)
DISPLAY	Size	30"- 300" (Diagonal)
	Throw Distance	0.7m-9m (2.3' - 29.5')
	Lamp	150W UHB Compact,
		4,000 hour rating (Whisper-mode Operating)
	Brightness	1,500 Lumens
	Contrast Ratio	400:1
	Keystone Correction	± 10 degrees
	Aspect Ratio	4:3, 16:9
AUDIO	Speakers	1W monospeaker x1
INPUT SIGNAL	RGB	RGB analog
	Video	NTSC, PAL, SECAM
	HDTV	HDTV 480i, 480p, 575i, 720p, 1080i
	Frequency	Fh:15 - 80kHz; Fv:56 - 120Hz
COMPATIBILITY	PC	From VGA up to SXGA
	Mac®	Up to SXGA (may require Mac Adapter)
CONNECTOR	RGB Input	15-pin HD, D-sub x1
	Composite Video	RCA x1
	Component Video	RCA x3
	S-Video	Mini-Din 4 pin x1
	Audio	3.5mm Mini Stereo Plug x1
POWER	Voltage	100-240 VAC, 50-60Hz (Universal)
	Consumption	210W (typ), 130W (whisper-mode)
USER CONTROLS	Basic	Standby On/Off, Menu (Left, Right, Up, Down), Input, Reset, keystone

USER CONTROLS	Basic	Standby On/Off, Menu (Left, Right, Up, Down), Input, Reset, keystone
	Remote	Standby On/Off, Video, RGB, Menu, Position, Keystone, Arrow/Select (Left, Right, Up, Down), Enter, Escape, Reset, Magnify (On, Off), Freeze, Volume, Mute, Auto, Blank, Aspect, and Search Buttons
	OSD	Main : Brightness, Contrast, Aspect, Pict., Pos., Gamma, Mirror, Language
		Picture-1 : Color Bal R, Color Bal B, Sharpness, Color, Tint
		Picture-2 : V-Position, H-Position, H-Phase, H-Size
		Input : Auto (Execute), Video, HDTV, Sync On Green
		Screen : Blank, Start Up
		Option : Volume, Auto Off, Whisper, Lamp Time, Filter Time
OPERATING	Temperature	0-35°C (32-95°F)
CONDITION	Humidity	10% to 85% (non-condensing)
DIMENSIONS	Physical	289mm x 210mm x 60mm
(W x D x H)		
WEIGHT	Net	2.5 kg (5.4lbs)
REGULATIONS		UL, c-UL, FCC-Class B, CB, CE, TUV/GS, C-Tick
WARRANTY		Three-year limited warranty on parts and labor One-year warranty on lamp

OTHER

Specifications subject to change without notice

Selection, offers, warranties and programs may vary by country; see your ViewSonic representative for complete details.

keystone correction, DDC 1/2B

Mirror reverse image, upside down image, digital

Headquarters : 381 Brea Canyon Road, Walnut, CA91789, U.S.A Tel:(800)888-8583 (909)444-8888 Fax:(909)839-7922 E-mail:salesinfo@viewsonic.com www.viewsonic.com

Asia Pacific : 9F, No. 192 Lien Chien Road, Chung Ho, Taipei, R.O.C Tel:886-2-2246-3456 Fax:886-2-8242-3666 www.viewsonic.com.tw

www.viewsonic.com