# Play Big IN83

Full-HD 1080p

· InFocus



## Go Beyond The Surface.

Stunning pictures in high-definition? High contrasts and optimized colour reproduction through HDMI? With the Play Big IN83 full-HD 1080p projector from InFocus nothing is impossible. Featuring the latest DarkChip4 DLP® technology from Texas Instruments and Pixelworks<sup>TM</sup> DNX 10-bit video processing, the IN83 delivers the out-of-the-box, film-quality color fidelity InFocus is known for, without compromising contrast ratio, brightness, or subtle grayscale details. Its HDMI 1.3 interface, the state of the art in home theatre technology, supports Deep Color<sup>TM</sup> and can display up to 1.07 billion colors without color banding artifacts for a smooth, lifelike picture.

Whatever you're watching --- whether your favorite HD-DVD or Blue-ray<sup>TM</sup> movie, sports, or Discovery HD Theater's "Shark Week" — you will be completely awed when it's displayed in perfect clarity on a huge screen with the IN83.

Experience the thrill of cinema!

## **InFocus Play Big IN83 Features:**

- Native 15,000:1 contrast ratio (using iris)
- Video optimized brightness up to 1600 Max ANSI lumens
- Connect to any HD video source using HDMI 1.3, DVI and Component inputs
- Swivel base allows simple setup on tabletop, or removes for ceiling mounting
- Sleek and elegant with a piano black finish to complement any room



 The IN83 is capable of turning multi-use rooms into theater experiences.

The Play Big remote control is a model of simplicity, functionality, and good looks.



### **Enduring Quality**

If you're happy, InFocus is happy. That's why the InFocus Play Big IN83 projector comes with a standard 3-year limited factory warranty (including parts and labor), a zero-dead-pixel guarantee and a 1-year lamp replacement warranty. For service program details in your region please visit: **www.infocus.com/service** 



### **Optional Accessories**

Ceiling Mount (SP-CEIL-UNIV)
Projection Screens
Performance Cables for Digital and HDTV
Cable Adapters

For more information about the IN83, any InFocus home projector, optional accessories or service programs please visit: **www.infocus.com** 

#### INFOCUS TECHNICAL SPECIFICATIONS\*

	Full HD 1080p (1980 x 1080)
Display Technology	DarkChip4 DLP® by Texas Instruments 7-segment (RGBRGBndG) color wheel
Brightness	Video Optimized 1600 Max ANSI lumens (1100 typical) SMPTE brightness up to 14.25 ft (4.3m) diagonal/1.0 gain screen
Contrast Ratio	Max 15,000:1 using iris
Video Processing	Digital Natural Expression™ (DNX) by Pixelworks™ 10-bit video decoder with Motion- Adaptive De-Interlacing, Rich Color Processing, Video Enhancement Processing, Noise Reduction
Color Features	Up to 1.07 billion displayable colors with Deep Color™ (requires HDMI 1.3 source) Texas Instruments BrilliantColor™ Preset color gamma tables optimized by source-type Individually adjustable RGB colors: D6500K color accuracy
Advanced Features	Automatic black level calibration, Digital vertical image shift, InFocus Color Gamut Calibrator utility support, ISF Day/Night modes (requires ISF Certified Calibration by professional installer)
Lamp Life and Type	2500 hrs (2000 hrs normal mode), 300W UHP
Compatibility	1080p/60/50/30/24, 1080i/60/50/35/24, 720p, 576p, 576i, 480p, 480i NTSC, PAL, SECAM, VESA, SXGA, XGA, SVGA, VGA
Digital Keystone Correction	±13° Vertical
I/O Connections	(1) HDMI (version 1.3) with HDCP (1) Component Video, YPbPr/RGBHV, RCA (1) Composite Video, RCA (1) S-Video, 4-pin mini DIN (1) Auxiliary input for 2nd video source (HDMI 1.3, DVI, VGA, or Component), M1-DA (2) 12V screen/aspect ratio trigger, 3.5mm mini jack (1) IR repeater input, Niles/Xantech compatible 3.5mm mini jack (1) RS232, male DB9
Projection Lens	Manual 1.2x zoom, F 2.6 - 2.8, f 39.1 - 46.9m, 136% offset Threaded focus ring for 72mm neutral density filter (available separately)
Throw Ratio	1.85 - 2.22:1 (Distance/Width)
mage Offset	136%
Aspect Ratio	16:9 (native), 4:3, 2.35:1 widescreen (requires anamorphic lens, available separately)
Projection Modes	Ceiling mount (built-in ceiling-mode sensor) and tabletop, using swivel base (included)
Projection Distance	4.92' - 32.8' (1.5m - 9.9m)
Audible Noise	30 dB (33 dB normal mode)
Power Consumption	350W typical (375W Max)
Power Supply	100 - 240 Volts at 50 - 60 Hz
Operating Temperature	50 - 95° F (10 - 35° C) at 7500 ft (2286 m)
Storage Temperature	-7 - 140°F (-20 - 60°C), 80% Maximum Humidity
Dimensions	18.75" x 5.83" x 17" (476mm x 148mm x 432mm)
Weight	14.1 lbs (6.4kg)
Menu Languages	English, German, Spanish, French, Italian, Norwegian, Portuguese, Swedish, Russian, Japanese, Korean, Chinese (Simplified and Traditional)
Included	IN83 projector, AC Power Cord, 2M HDMI 1.3 cable, M1-to-HDMI adapter, detachable cable cover, Base, Polishing Cloth, Play Big Remote Control with batteries, multi-language User's Guide,



<sup>\*\*</sup> Actual lamp life may vary based on the ambient environment. Conditions that may affect lamp life include temperature, altitude, and rapidly switching the projector on and off.

















