

## TX775 Data Projector

### Robust, Bright and Designed for Performance

With 3500 lumens, a 2300:1 contrast ratio and a sleek new design, the Optoma TX775 offers the ultimate solution for presentations. The TX775 features a new form factor that is intended to integrate easily into installations. Its built-in audio means the Optoma TX775 provides a complete multimedia experience for demanding applications.



### Features

- Bright 3500 ANSI lumens with 2300:1 contrast ratio
- New form factor allows for ease of lamp replacements
- Native XGA (1024 x 768) with support up to SXGA+ (1400 x 1050)
- Designed to integrate cleanly into installations
- Fully featured remote control with laser pointer and mouse
- Recessed focus and zoom controls prevent accidental adjustments

### Specifications

#### Brightness

3500 ANSI Lumens

#### Resolution

Native XGA (1024 x 768)  
SXGA+ (1400 x 1050) Maximum

#### Contrast Ratio

2300:1 (Full On/Full Off)

#### Lamp Life and Type

2000/3000 Hours (STD/ECO)  
230W SHP

#### Display Type

Single 0.7" DDR DLP® Technology  
by Texas Instruments

#### Throw Ratio

1.8 - 2.1:1 (Distance/Width)

#### Projection Distance

3.2' to 32.8' (1.0 to 10.0 m)

#### Image Size

27.5" to 306" (0.7 to 7.8 m)

#### Aspect Ratio

4:3 Native, 5:4 and 16:9 Compatible

#### Audio

One internal 3-Watt Speaker

#### Displayable Colors

16.7 Million, 256 Shades of Gray

#### Remote Control

Fully Featured IR Remote with Laser  
Pointer and Mouse

#### Computer Compatibility

XGA, SVGA, VGA, SXGA+ Resized,  
VESA, PC and Macintosh Compatible

#### Video Compatibility

NTSC, PAL, SECAM, EDTV (480p),  
HDTV (576i/p, 720p, 1080i)

#### Monitor Loop Through

D-Sub 15pin VGA Output (Functional  
in Both Normal and Standby Modes)

#### User Controls

Advanced Adjustability Options  
Through the On-Screen-Display

#### I/O Connection Ports

VGA-In, DVI-D w/HDCP, Composite  
Video, S-Video, Two Audio-In (RCA &  
Mini-Din), USB, RS-232, VGA-Out,  
Audio-Out, +12V Trigger

#### Projection Method

Front, Rear, Table Top and Ceiling  
Mount

#### Vertical Refresh Rate

50 to 85 Hz

#### Keystone Correction

± 15° Vertical Keystone

#### Weight

7.3 lbs (3.3 kg)

#### Uniformity

85%

#### Operating Temperature

5 to 35°C, 80% Max Humidity

#### Storage Temperature

-20 to 60°C, 80% Max Humidity

#### Dimensions (W x H x D)

11.81" x 3.46" x 9.61"  
(300 x 100.5 x 244mm)

#### Noise Level

33dB/31dB (STD/ECO)

#### Power Supply

100-240 Volts, 50-60Hz

#### Power Consumption

295W, <5W Standby Power

#### Standard Accessories

AC Power Cord, VGA to VGA Cable,  
RS-232 Cable, Composite Video  
Cable, Remote Control, Batteries for  
Remote, CD-ROM User's Manual,  
Lens Cap, Carrying Case, Warranty  
Card and Quick Start Guide

#### Optional Accessories

Bering Ceiling Mount, DVI to HDMI  
Adapter and GrayWolfll™ Series  
Screens

#### Warranty

3 Years Optoma Express Replacement  
Service, 1 Year on Lamp

#### UPC

796435 11 126 7