



PLC-XE50

- Ultra-short Focus Projector: enabling an 80" projection from a distance of only 8cm
- Brightness: 2,000 ANSI lumens
- Resolution, native: 1,024 x 768 (XGA), maximum: 1,600 x 1,200 (UXGA)
- Versatile use, including floor space, tabletop and wall-mounted projection
- No external buttons
- MyLogo Function for custom logo transfer
- Anti-theft function: audio alarm feature



TECHNICAL DETAILS PLC-XE50

Category	Education
Panel	0.8 inch TFT p-Si x 3
Lamp	Single 275W Lamp
Brightness	ANSI lumens 2000
Lamp Service Life	3,000 h (eco mode)/2,000 h (normal mode)
Fan Noise	25 dB (eco mode)/30 dB (normal mode)
Standard Lens	F = 1.65-1.83 / f = 22.5-27.0 mm*
Contrast Ratio	600:1
Resolution in pixels	2,359,296 (1024 x 768 dots)
Uniformity	80%
Bandwidth/Frequency	H/V sync ~ 15-100kHz ~ 50-100Hz, Dot clock 140 MHz
Colour Systems	PAL / SECAM / NTSC / NTSC4.43 / PAL-M/N
Connections	Input 1: 1 x Dsub15 Input 2: 1 x Dsub15 (Switchable) Input 3: 3 x RCA (Component) - S-Video 1 x RCA (Composite)
Audio Out:	Computer: Minijack stereo.
Communication Terminal:	RS232C (Mini DIN 8 Pin)
Keystone Correction	Vertical +/- 5°
Computer Compatibility	UXGA/ SXGA+ / SXGA/WXGA/ SVGA/ VGA/ MAC
Power Consumption/Voltage	100V-240V AC (auto voltage)
Dimensions	(W x H x D) 374 x 196.8 x 495 mm
Weight	7.6kg

