

480p Home Theater DLP™ Projector

We're taking LCD & DLP™ projection to a whole new level!

E1P-1000T

1000 ANSI Lumens!

Get the film-like imaging of DLP™ technology in a quiet, bright, high contrast video projector.



EIKI
PROJECTORS

EIKI MEANS PROJECTORS ... AND MORE!



KEY FEATURES:

- ▼ Native 480p resolution. 1080i, 1035i, 576i/p, 540p and 480i compatible.
- ▼ Two Component inputs and one output, plus S-Video and Composite in.
- ▼ Up to a 2500:1 Contrast Ratio. Up to 1000 ANSI Lumens Brightness.
- ▼ 5X Speed, 6 Segment Color Wheel for minimum color artifacts.
- ▼ Air Bearing Color Wheel for quiet operation: only 30 dBA in Eco mode.
- ▼ Installation flexibility: 1.15X Manual Zoom and Focus Lens.
- ▼ Preset image offset. Vertical Keystone Correction.
- ▼ Sealed optics: no air filter to maintain.
- ▼ Compatible with computer resolutions from SXGA+ to VGA, and MAC.
- ▼ Smart data compression / expansion, & video scaling.
- ▼ Color Temperature adjustment.
- ▼ Built-in 2W sound system. Audio-follows-video variable line output.
- ▼ **3 YEAR* PROJECTOR WARRANTY!**

EIP-1000T



Lamp Contains Mercury.
Do not put in trash. Dispose-of-as
Hazardous Waste, according to
the laws in your jurisdiction.



SPECIFICATIONS: EIP-1000T

Screen Brightness up to 1000 ANSI Lumens / 870 in Eco mode
Illumination Uniformity 85%
Size of Color Palette 16.7 Million
Contrast Ratio up to 2500:1 (Full ON/OFF)
Horizontal Resolution 520 TV Lines (DTV720P)
Projection Lamp 275 Watt Short Arc SHP
Estimated Lamp Life Standard: 2,000 /Eco 3,000 Hours of Use
Imaging System 0.55 in. DDR WVGA DMD™
Color System 6-segment, 5X speed color wheel
Color Pixels (854 x 480) in stripe configuration
Total Pixels 409,920
Lens Type Manual Zoom and Focus
Lens Specs Speed: f:2.4~2.6; FL: 0.75~0.86 in. (19.0~21.9 mm)
Lens Zoom Ratio 1.15:1
Lens Throw:Width Ratio 1.72 ~ 1.99:1 (+/- 3.5%)
Image Diagonal 40~300 in. (102~762 cm)
Image Width 2.67~ 20 ft. (0.81~6.1 m)
Throw Distance 4.6~39.8 ft. (1.4~12.2 m)
Front Elevation / Maximum Tilt up to 8° up
Anti Keystone Fixed Lens Offset, 110.5% of Image Height, up
Vertical Keystone Correction Digital: up to 13° up or down
Scanning Frequency Auto: H Sync. 15-70 kHz; V Sync. 43-85 Hz
Dot Clock 12~108 MHz
Image Orientation Normal, Reversed, Inverted
Local Control / Power Management Full Function / Auto Shut-Off
Remote Projector Control Wireless (Infra Red) x 1
RS-232 Control Port Mini DIN 9 Pin x 1
Video: Native Resolution 480p
Video Color Systems NTSC, PAL, SECAM, NTSC 4.43, PAL-M & N
Video Aspect Ratios Supported 4:3 and 16:9
Video Image Resizing Video Scaling Technology
Video Resolutions Supported	
SDTV 480i, 540p, 576i
EDTV 480i, 576i
HDTV 720p (50/60), 1035i (50/60), 1080i (50/60)
Computer: Compatibility SXGA+, SXGA, XGA, SVGA, VGA & MAC 13~21
Computer: Formats Supported 1400x1050 through 640x480
Computer: Image Sizing Normal, or Smart Compressed or Expanded
Signal Inputs:	
1: Component (with breakout cable)/ Computer HD15 x 1
2: Component (with breakout cable)/ Computer HD15 x 1
plus: Audio: shared - Inuts 1 & 2 Stereo: Mini Stereo x 1
3: S-Video 4-Pin Mini DIN x 1
plus: Audio: shared - Inuts 3 & 4 Stereo: RCA x 2 (L&R)
4: Composite RCA x 1
Signal Outputs:	
Component/Computer shared between Inpu 1 & 2 HD15 x 1
plus: Audio shared - Inputs 1~4 Stereo: Mini Stereo x 1 (Variable)
Audio: Amplifier Mono: 2 Watt
Audio: Built-in Speaker 1.6 x 1.1 (4 x 2.85 cm.) Oval x 1
Fan Noise 33 dBA Standard, 30 dBA in Eco mode
Cabinet Size (HxWxD) 4.3 x 12.4 x 11.0 in. (109 x 315 x 280 mm.)
Overall Size (HxWxD) 4.7 x 12.4 x 11.6 in. (120 x 315 x 295 mm.) including leg and lens
Weight 8.6 lbs. (3.9 kg)
Packaged Size (HxWxD) 10.7 x 17.4 x 18.1 in. (272 x 441 x 459 mm)
Packaged Weight 16.3 lb (7.4 kg)
UPC 4571194670257
Power Requirements 100-240V AC, 50/60Hz
Power Consumption / Heat 350 W, 922 BTU/hr (233 Kcal/hr)
Power Consumption / Heat - Eco 196 W, 669 BTU/hr (169 Kcal/hr)
Power Cord 6' (1.8 m) Type 3, Detachable
Safety Compliance UL / cUL, CE
Security Facilities Kensington® Security Slot
Operating Temperature 41~95°F (5~35°C)
User Maintenance Replace Lamp
Warranty: (to the original end-use customer)	
Projector 3 Years / 6000 Hour Use* (Parts & Labor to Correct Defects)
Warranty: Lamp 90 Days (Failed Lamp Replaced Pro-Rata)
 * Whichever occurs first

INCLUDED ACCESSORIES:

Owner's Manual. Quick Guide. AC Power Cord. Lens Cover.
Wireless Remote Control & Batteries (AAx2). Component Video
Input Cable (HD15~3RCA). RS-232 Control Adapter (DB9~9 Pin
DIN).

OPTIONAL ACCESSORIES:

Replacement Lamp. Ceiling Mount. Ceiling Post and Plate. VGA-type
Computer Input Cable (HD15~HD15). Additional Component Video
Input Cable. (HD15~3~RCA). EZ-250 Local Control. NPC-1 Network
Control.

EIKI
PROJECTORS