


# 3M™ Digital Projector X90




With its 4000 lumens\*, crisp video and data image display and wide selection of connectors, the 3M™ Digital Projector X90 is ideal for boardrooms, classrooms, multi-media and multipurpose environments. Advanced features like personalized settings, video enhancements and anti-theft deterrents, make the 3M X90 a great tool for presenting a professional image.



## Features

- 4000 lumens\*
- Wired LAN
- Optical Zoom
- Full Connectivity
- Quick Start and Instant Off
- Auto Vertical Keystone
- Input source naming
- SRS WOW™ Sound
- *My Screen, My Memory, My Button* personalized settings
- Whiteboard and Blackboard modes
- Anti-Theft Deterrents:
  - Security Bar
  - PIN-Lock
  - *My Screen Lock*
  - Transition Detector
- Free Downloadable Software
- Picture Freeze, Image Blank and Magnify (4x)

\*indicates maximum lumens rating



- Hear audio the way it was intended – with amazing highs, full bass from the lows and realistic immersion. SRS WOW™ improves audio dynamics, and perception of low frequency bass and will make your presentations command attention.

1-800-328-1371  
www.3m.com/meetings



# 3M™ Digital Projector X90 Specifications & Accessories

## Optical

Resolution:	Native: True XGA (1024 x 768) Maximum: UXGA (1600 x 1200)
Imager set:	0.8", P-Si TFT Panel
Aspect Ratio:	4:3 native and 16:9 supported
Colors:	16.7 million true colors (24 bit)
Brightness:	4000 lumens (maximum rating)
Contrast Ratio:	1000:1
Projection lens:	F1.7-2.1, (f=24-29mm)
Lens Shift:	1:1 to 9:1 (vertical); 6:4 to 4:6 (horizontal)
Screen Size (range):	30-350 inches diagonal
Zoom / Focus:	Manual
Zoom Ratio:	1.2:1
Optional Lenses:	Short Throw, Long Throw & Ultra Long Throw
Lamp:	UHB 285W (Normal Mode), 228W (Whisper)
Lamp Life:	2000 hours (Normal Mode) Up to 3000 hours (Whisper Mode)

## System Specifications

Video compatibility:	NTSC, NTSC 4.43, PAL, PAL-M, PAL-N, SECAM
SDTV/HDTV:	525i (480i), 525p (480p), 625i (576i), 750p (720p@60Hz), 1125i (1080i@60Hz)
Digital Keystone Correction:	Vertical: ±40° Horizontal: ±20°
Audio:	4 x 4W
Startup Screen:	Customizable
Noise level:	Normal 39dB; Whisper 33dB
Horizontal scan:	31.5-106kHz
Vertical scan:	56-120Hz
Power consumption:	460W
Power supply:	Universal: 100-120V/220-240V, 50/60Hz
Regulatory approvals:	UL, cUL, FCC Part 15 Class B, CE, EN60950, WEEE
Operating temperature:	41°-95°F (5°-35°C)
Storage temperature:	-4°-140°F (-20°-60°C)
Altitude:	Sea level to 6000 ft. (1,829m)

## Size

Dimensions (W x H x D):	16.5 x 5.5 x 12.6 in. (418 x 139 x 319mm)
Weight:	15.6 lbs / 7.1kg

## Warranties

See [www.3m.com/us/meetings/warranties](http://www.3m.com/us/meetings/warranties) for details on warranties.

Projector:	3 Years Standard
Lamp:	90 days or 180 hours Remainder of 1 Year Prorated
Ultra Value Warranty Enhancement:	Includes free lamp, free loaner while unit is being repaired and expedited service. Not available outside U.S.

## Minimum System Requirements

Software Requirements:	Microsoft® Windows® XP Home Edition or Windows 2000 Professional
Hardware Requirements:	Minimum RAM: 64MB - 2000 / 128M - XP
Hard Drive Space:	10MB
CD:	CD-ROM Drive

## Connections

<b>Computer</b>
3 - Analog RGB (2 inputs, 1 output)
1 - Digital RGB (1 input = M1-D)
1 - USB Mouse (M1-D)
1 - Serial Control
1 - Network Port

<b>Video</b>
1 - Composite (RCA Jack)
1 - S-Video (Mini-Din 4 pin)
1 - Component (RCA Jacks x3)

## Audio in/out

2 - RCA Audio Ins (Red RCA/White RCA)
2 - Mini Stereo Jack Ins
1 - Mini Stereo Jack Out

## Wired LAN

Standard:	10 BASE-T / 100 BASE-TX
Connection:	1 - RJ-45

## Accessories Included

- Power Cords (US, UK, Europe)
- VGA/RGB Cable
- Wireless Remote Control with laser pointer
- Multi-language Operator's Guide CD
- Free unlimited software downloads and updates available on our website at [www.3m.com/meetings](http://www.3m.com/meetings)

## Optional Accessories

• Ultra Value Enhanced Warranty (WX90) [U.S. Only]	78-6969-9907-3
• Lamp Replacement Kit (LKX90)	78-6969-9893-5
• Ceiling Mount (CM X90)	78-6969-9905-7
• Universal Ceiling Mount	78-6969-9874-5
• Soft Rolling Bag	78-6969-9906-5
• Short Throw Lens	78-6969-9890-1
• Long Throw Lens	78-6969-9891-9
• Ultra Long Throw Lens	78-6969-9892-7

## Technical Support

- Free unlimited software downloads and updates available on our website at [www.3m.com/meetings](http://www.3m.com/meetings)
- Toll-free 24/7 Technical Support by calling 800-328-1371

Screen Size (Diagonal)	Image Size 4:3		Image Size 16:9	
	Projection Distance		Projection Distance	
	Minimum (m)	Maximum (m)	Minimum (m)	Maximum (m)
40" (1.0)	47" (1.2)	57" (1.4)	51" (1.3)	62" (1.6)
60" (1.5)	71" (1.8)	86" (2.2)	78" (2.0)	94" (2.4)
100" (2.5)	120" (3.0)	144" (3.7)	131" (3.3)	157" (4.0)
150" (3.8)	181" (4.6)	217" (5.5)	197" (5.0)	237" (6.0)
200" (5.1)	241" (6.1)	291" (7.4)	263" (6.7)	317" (8.0)
300" (7.6)	363" (9.2)	437" (11.1)	395" (10.0)	476" (12.1)

Note: These sizes are +10 percent. This is due to variations in the manufacture of the lens. If you are close to one of the endpoints you should verify with your unit that the image is the proper size at the proper distance.

Specifications subject to change without notice.

3M, the 3M logo and the Vikuiti logo are trademarks of 3M Company. Used under license in Canada. All other trade names referenced are the service marks, trademarks, or registered trademarks of their respective companies.

WOW, SRS and ● are trademarks of SRS Labs, Inc. WOW technology is incorporated under license from SRS Labs, Inc.

©3M 2008. All Rights Reserved.

V11.30.07

## 3M Projection Systems

Building A 147-5N-01  
6801 River Place Blvd.  
Austin, TX 78726-9000

## 3M Canada

P.O. Box 5757  
London,  
Ontario, Canada  
N6A 4T1

## 3M Mexico, S.A. de C.V.

Apartado Postal 14-139  
Mexico, D.F. 07070  
Mexico

Hg—LAMP CONTAINS MERCURY. Manage in accord with disposal laws. See [www.lamprecycle.org](http://www.lamprecycle.org) or call 1-800-328-1371 (USA), 1-800-364-3577 (Canada). For product disposal see [www.eiae.org](http://www.eiae.org) (USA) or [www.epsc.ca](http://www.epsc.ca) (Canada).

## Important Notice

All statements, technical information, and recommendations related to 3M's products are based on information believed to be reliable, but the accuracy or completeness is not guaranteed. Before using this product, you must evaluate it and determine if it is suitable for your intended application. You assume all risks and liability associated with such use. Any statements related to the product which are not contained in 3M's current publications, or any contrary statements contained on your purchase order shall have no force or effect unless expressly agreed upon, in writing, by an authorized officer of 3M.

## Warranty; Limited Remedy; Limited Liability

This product will be free from defects in material and manufacture for a period of 3 years from the date of purchase. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. If this product is defective within the warranty period stated above, your exclusive remedy shall be, at 3M's option, to replace or repair the 3M product or refund the purchase price of the 3M product. Except where prohibited by law, 3M will not be liable for any indirect, special, incidental or consequential loss or damage arising from this 3M product, regardless of the legal theory asserted.