3M[™] Multimedia Projector MP8649



Value workhorse

Great performance for education


Use it at the front of the room with the built-in wide angle lens

Ideal for medium size meetings

C O N N E C T I O N S

COMPUTER

- > RGB (x2 input) (x1 output)
- Audio (x2 input) (x1 output)
- > Serial Control
- <u>VIDEO</u>
- > Component (3)
- > S-Video
- > RCA Composite
 > RCA Audio (L,R)
- Mouse Emulation (USB x1)



1-800-328-1371

BASIC SPECS

- > 2200 lumens
- > 7.0 lbs / 3.2 kg
- > SVGA (800x600) resolution
- > 400:1 Contrast ratio
- > Digital keystone
- > Whisper mode
- > HDTV ready

WARRANTY

Important Notice

Before using this product, you must evaluate it and determine if it is suitable for your intended application. You assume all risks and liability associated with such use.

Warranty; Limited Remedy; Limited Liability.

This product will be free from defects in material and manufacture for a period of 3 years from the date of purchase. 3M MAKES NO OTHER WARRANTIES INCLUDING, BUT NOT LIMIT-ED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTIC-ULAR PURPOSE. If this product is defective within the warranty period stated above, your exclusive remedy shall be, at 3M's option, to replace or repair the 3M product or refund the purchase price of the 3M product. Except where prohibited by law, 3M will not be liable for any loss or damage arising from this 3M product, whether direct, indirect, special, incidental or consequential regardless of the legal theory asserted.

www.3M.com/meetings

3M Presentation Solutions

S P E C I F I C A T I O N S

MP8649

OPTICAL

- > Brightness: typical (whisper mode): 2200(1800)lumens
- > Imager set: 0.9" Polysilicon LCD
- > Resolution (native): SVGA (800x600)pixels
- > Resolution (maximum): SXGA (1280x1024)pixels
- > Aspect ratio: 4:3 native, 16:9
- > Colors: 16.7 million
- > Screen size (range): 30-300 inches
- > Zoom / Focus: Manual
- > Zoom ratio: 1.2: 1
- > Projection lens: F (focal length): 1.7-2.1 (f =27.3 -32.8mm)
- > Optional lenses: No
- > Contrast ratio (on/off): 400:1
- > Lamp: W, Type: 200w UHB
- > Lamp life (average): 2000

ELECTRICAL

- > Video compatibility: NTSC, NTSC 4.43, PAL, PAL-M, PAL-N, SECAM
- > HDTV: 480i, 480p, 525i, 525p, 720p, 1080i
- > Keystone Correction: Vertical, -15 $^{\circ}$ to +15 $^{\circ}$
- > Audio: 2 x 1w
- > Startup Screen: Standard
- > Picture in Picture: No
- > Noise level: normal (whisper): 41 (35)dB
- > Feature set: Auto off, 4x digital magnification, blank, mouse emulation(optional)
- > Horizontal scan: 15-80 kHz
- > Vertical scan: 50-120 Hz
- > Power consumption: 310w
- > Power supply: Universal: 90-264V AC, 50/60 Hz
- > Regulatory approvals: UL, cUL, FCC Part 15 Class B, CE, TUV, EN60950
- > Operating temperature: 32 95 F (0 35 C)
- > Storage temperature: -4 140 F (-20 60 C)

SIZE

Please visit us at 3M.com/meetings

- > Dimensions (WxDxH): 11.7x9 x3 in. (298x228x76mm)
- > Weight: 7.0 lbs / 3.2 kg

WARRANTIES

- > Projector: 3 Years Standard
- > Lamp: 1 Year Prorated

ACCESSORIES INCLUDED

- $\,>\,$ Power Cords (x3 US, UK, Euro)
- > RGB computer cable
- > Slim remote control
- >~ RCA audio & video cable
- > Component video cable
- > Multilanguage Quick Start Guide
- > Multilanguage Operator's Guide CD
- > Handle strap

OPTIONAL ACCESSORIES

- > Lamp (EP8749LK) 78-6969-9464-5
- > Ceiling Mount, Gyrolock style (EP8746CM) 78-6969-9261-5
- > 26-47" Adjustable Extension for GyroLock Style Ceiling Mount (EPGyroExt) 78-6969-9564-2
- > Soft Carry Case with Shoulder Strap Projector & Notebook Computer (EP7640CC) 78-6969-9203-7
- > Rolling Hard Shipping Case (EP8746SC) 78-6969-9259-9



Projection Distance Chart - MP8649

| Distance to Screen | | Screen Size | | |
|--------------------|-----------|-------------|----------|----------|
| Min. | Max | Diagonal | Width | Height |
| 3.92 ft. | 4.58 ft. | 40 in. | 32 in. | 24 in. |
| 1.2 m | 1.4 m | 101.6 cm | 81.3 cm | 61.0 cm |
| 5.92 ft. | 7.25 ft. | 60 in. | 48 in. | 36 in. |
| 1.8 m | 2.2 m | 152.4 cm | 121.9 cm | 91.4 cm |
| 7.92 ft. | 9.5ft. | 80 in. | 64 in. | 48 in. |
| 2.4 m | 2.9 m | 203.2 cm | 162.6 cm | 121.9 cm |
| 9.83 ft. | 11.83 ft. | 100 in. | 80 in. | 60 in. |
| 3.0 m | 3.6 m | 254.0 cm | 203.2 cm | 152.4 cm |
| 11.83 ft. | 14.42 ft. | 120 in. | 96 in. | 72 in. |
| 3.6 m | 4.4 m | 304.8 cm | 243.8 cm | 182.9 cm |
| 14.75 ft. | 17.75 ft. | 150 in. | 120 in. | 90 in. |
| 4.5 m | 5.4 m | 381.0 cm | 304.8 cm | 228.6 cm |
| 20 ft. | 24 ft. | 200 in. | 160 in. | 120 in. |
| 6.1 m | 7.3 m | 508.0 cm | 406.4 cm | 304.8 cm |

Visual Systems Division Building A145-5N-01 6801 River Place Blvd. Austin, TX 78726-9000

3M Canada P.O. Box 5757 London, Ontario, Canada N6A 4T1 3M Mexico, S.A. de C.V. Apartado Postal 14-139 Mexico, D.F. 07070 Mexico

Specifications subject to change without notice. RCA is a trademark of Radio Corporation of America.

3M Presentation Solutions

Litho in U.S.A. © 3M IPC 2003 78-6970-8518-7 REV A (Feb.TG/10m)