

# Multimedia Projector

# 3M<sup>™</sup> Multimedia Projector MP8746

## The 3M Multimedia Projector MP8746

Light up the room with the new 3M Multimedia Projector MP8746. The bright 1,000 ANSI lumens completes your desire for portable quality brightness; finally, you won't feel like you left all those vivid images at the office. The XGA resolution of the 3M MP8746 brings presentations to life with sharp, clear images. The USB connection makes mouse emulation a snap. And at only 7 pounds, the 3M MP8746 is easily carried around the office or on the road.

## **KEY FEATURES**

- Weighs 7 pounds for easy movement
- 1,000 ANSI lumens for vivid presentations
- XGA (1024x768) resolution for detailed information
- Digital Keystone Correction for a square image every time
- Intelligent image scaling technology optimizes image quality for SXGA, SVGA and VGA resolution and video
- · Four times Magnification to highlight details
- · Adjustable Auto Off to save lamp hours
- Four input channels for simultaneous connection of two computers and two video signals. (one Composite and one S-Video)
- Virtual Mouse remote control with five presentation tools: blank, laser pointer, timer, magnification, mouse emulation
- 1.2:1 zoom ranges allows flexibility based upon the size of room
- Universal power supply for use anywhere in the world
- Kensington® Security Slot for protection from theft (Kensington Microsaver needed)
- · Ceiling mountable
- · One-year prorated warranty on original lamp

## **Computer Compatibility:**

- IBM® and compatible SXGA, XGA, SVGA, VGA
- Apple® Macintosh® (II, LC, Quadra, PowerPC, PowerBook®, iMac®DV, iMac®DV+, and iMac®DV Special Edition)

## **Video Compatibility:**

- Autosync: NTSC, NTSC 4.43, PAL, PAL-M, PAL-N, SECAM
- · Composite and S-VHS

## **Accessories Included:**

- Detachable power cords (US, UK, Europe)
- · VGA cable
- RCA video/audio cable
- S-VHS video cable
- PS/2 Mouse Emulation Cable
- IR Remote Control
- Multilanguage operator's guide
- Handle Strap

## TECHNICAL SPECIFICATIONS

- Display: 0.9" active matrix polysilicon TFT (x3)
- Resolution: 1024 (W) x 768 (H) pixels (XGA)
- Brightness: 1,000 ANSI lumens
- Weight: 7 lbs. (3.2 kg.)
- Dimensions: 11.7" x 3.0" x 8.98" (29.8cm x 7.6cm x 22.8cm)
  (WxHxD)
- Colors: 16.7 million (maximum)
- · Contrast: 100:1 ANSI
- Aspect ratio: 4:3 or 16:9
- Zoom lens: 1.2:1
- Screen size: 31" (minimum) to 300" (maximum) diagonal
- Horizontal scan: 31 kHz to 80 kHz
- Vertical scan: 56 Hz to 120 Hz
- Speakers: Two, 1 watt stereo
- Lamp type: 160 Watts UHB
- Lamp life: 1,500 hours (average)
- Operating temperature: 32°F (0°C) to 95°F (35°C)
- Storage temperature: -4°F (-20°C) to 140°F (60°C)
- Power consumption: 250 Watts
- Power supply: Universal 100-120V AC, 220-240V AC, 50/60 Hz
- Regulatory approvals: FCC Part 15 Class B, CE, UL, cUL, TUVGS
- Order Number: 78-9236-6574-5

## Warranties:

Prime Value: Two-year limited warranty on parts and labor Original lamp prorated for one year

Max Value: 78-6969-9264-9 Ultra Value: 78-6969-9265-6

"Wherever there's a great meeting

you'll find 3M."™

# 3M™ Personal Projector MP8746



Made from durable DuPont™ Ballistic Nylon, this carry case fits easily under airplane seats or in overhead compartments.

Dimensions: 12" (H) x 6.5" (W) x 14" (L) Order number: 78-6969-9203-7 (EP7640CC)



## Replacement Lamp Kit for 3M MP8746

User replaceable lamp assembly for 3M MP8746. Order number: 78-6969-9260-7 (EP8746LK)



## Hard Shipping Case (ATA) for 3M MP8746

This rugged shipping case is custom-designed to safeguard your 3M MP8746/8747 projector from the hazards of travel. It features a hard shell, locking extension handle, wheels, and a combination lock. Internal storage area holds cords, cables, remote, and more.

Dimensions: 8" (H) x 12.25" (W) x 21" (L)

Weight: 26 lbs.

Order number: 78-6969-9259-9 (EP8746SC)

### Projection Distance Charts - MP8746 Screen Size Distance to Screen Height Minimum Diagonal Width Maximum 5.0 ft. 7.0 ft. 40.0 in. 32.0 in. 24.0 in. 2.1 m 1.5 m 81.3 cm 61.0 cm 101.6 cm 8.0 ft. 10.0 ft. 48.0 in. 36.0 in. 60.0 in. 91.4 cm 2.4 m 3.0 m 152.4 cm 121.9 cm 11.0 ft. 64.0 in. 48.0 in. 13.0 ft. 80.0 in. 121.9 cm 3.4 m 4.0 m 203.2 cm 162.6 cm 14.0 ft. 16.0 ft. 100.0 in. 80.0 in. 60.0 in. 4.3 m 4.9 m 254.0 cm 203.2 cm 152.4 cm 20.0 ft. 120.0 in. 96.0 in. 72.0 in. 16.0 ft. 4.9 m 6.1 m 304.8 cm 243.8 cm 182.9 cm 21.0 ft. 25.0 ft. 150.0 in. 120.0 in. 90.0 in. 38<u>1.0 cm</u> 6.4 m 7.6 m 304.8 cm 228.6 cm 27.0 ft. 33.0 ft. 120.0 in. 200.0 in. 160.0 in. 8.2 m508.0 cm 406.4 cm 304.8 cm 10.1 m

Note: These sizes are  $\pm 10$  percent. This is due to variations in the manufacture of the lens. If you are close to one of the endpoints you should verify with your unit that the image is the proper size at the proper distance.

## 3M Enhanced Value Warranties for 3M MP8746

Receive a one-year Prorated Warranty on your original lamp and guaranteed repair and return of your projector with the Prime Value Warranty. Purchase the Max or Ultra Value Warranties and receive:

## Max Value:

- Parts and Labor 2 years (Total)
- Free loaner\* delivery next business day
- Paid shipping
- 1 Free lamp during term of warranty
- Repair turn-around time-3 business days
- Max Value: 78-6969-9264-9

## **Ultra Value:**

- Parts & Labor 3 years (Total)
- Free loaner\* delivery next business day
- Paid shipping
- 1 Free lamp during term of warranty
- Repair turn-around time-3 business days
- Ultra Value: 78-6969-9265-6


## **RGB Cable Extension Kit**

Order number: 78-6969-8582-5 (EP1880)

## Ceiling Mount for 3M MP8746

Order Number: 78-6969-9261-5 (EP8746CM)

## CONNECTORS



"Wherever there's a great meeting

you'll find 3M."<sup>TM</sup>

## www.3M.com/meetings



## **Visual Systems Division**

Building A145-5N-01 6801 River Place Blvd. Austin, TX 78726-9000

## 3M Canada

P.O. Box 5757 London, Ontario, Canada N6A 4T1

## 3M Mexico, S.A. de C.V.

Apartado Postal 14-139 Mexico, D.F. 07070 Mexico

Specifications subject to change without notice Apple, Macintosh, Mac, Power Macintosh and PowerBook are registered trademarks of Apple Computer, Inc. PS/2 are registered trademarks of IBM Corp. RCA is a trademark of Radio Corporation of America.

Litho in U.S.A. © 3M IPC 2001 78-6970-8448-7