

DX607 Data Projector

An Elegant and Bright Multimedia Solution

Redefining the multimedia data projector category, the Optoma DX607 makes a statement. With built-in audio, 3000 lumens, a 2300:1 contrast ratio and a sleek form factor, the DX607 takes bright and powerful to the next level. The Optoma DX607 is an elegant solution to multimedia presentations.



Features

- Bright 3000 ANSI lumens with 2300:1 contrast ratio
- Native XGA (1024 x 768) with support up to SXGA+ (1400 x 1050)
- Portable at 7.3lbs and attractive form factor
- Fully featured remote control with laser pointer and mouse
- Recessed focus and zoom controls eliminate accidental adjustments

Specifications

Brightness

3000 ANSI Lumens

Resolution

Native XGA (1024 x 768)

Contrast Ratio

2300:1

Lamp Life and Type

2000/3000/4000 Hours
(Bright/STD/ECO)
230W

Display Type

Single 0.7" DDR DLP® Technology
by Texas Instruments

Throw Ratio

1.94 to 2.27:1 (Distance/Width)

Projection Distance

3.2' to 32.8'

Image Size

27.5" to 306"

Aspect Ratio

Native 4:3, 16:9 Compatible

Vertical Refresh Rate

50 to 85 Hz

Keystone Correction

± 15° Vertical

Audio

One Internal 3-Watt Speaker

Displayable Colors

16.7 Million, 256 Shades of Gray

Uniformity

85%

Remote Control

Fully Featured IR Remote w/ Laser
Pointer and Mouse

Computer Compatibility

All Resolutions Supported up to SXGA+;
PC and Macintosh Compatible

Video Compatibility

NTSC, PAL, SECAM,
HDTV (480p, 576i/p, 720p, 1080i)

Monitor Loop Through

D-Sub 15pin VGA Output (Functional in
Both Normal and Standby Modes)

User Controls

Advanced Adjustability Options Through
the On-Screen-Display

I/O Connection Ports

VGA-In, DVI w/HDCP, Composite Video,
S-Video, Two Audio-In (RCA & Mini-Din),
USB, RS-232, VGA-Out, Audio-Out,
+12V Trigger

Projection Method

Front, Rear, Table Top and Ceiling
Mount

Weight

7.3lbs

Power Supply

100-240 Volts, 50-60Hz

Operating Temperature

5 to 35°C, 80% Max Humidity

Storage Temperature

-20 to 60°C, 80% Max Humidity

Dimensions (W x H x D)

11.81" x 3.46" x 9.61"
(300 x 100.5 x 244mm)

Noise Level

36dB/33dB/31dB (Bright/STD/ECO)

Power Consumption

290W, <5W Standby Power

Warranty

1 Year Limited Parts and Labor,
90 Days on Lamp

Standard Accessories

AC Power Cord, VGA to VGA
Cable, Composite Cable, Remote
Control, Batteries for Remote, Lens
Cap, Carrying Case, CD-ROM
User's Manual, Quick Start Guide
and Warranty Card

Optional Accessories

Bering Ceiling Mount, DVI to HDMI
Adapter, Gold Service Warranty
and GrayWolfII™ Series Screens

UPC

796435 11 127 4