



SIM2 *Grand Cinema* HT



WWW.SIM2.COM

Headquarters:

SIM2 MULTIMEDIA S.p.A.
Viale Lino Zanussi, 11
33170 Pordenone - Italy
Tel. +39.0434.383256
Telefax +39.0434.383260
E-mail: info@sim2.it
Web site: www.sim2.com

Germany:

SIM2 DEUTSCHLAND GmbH
ArndStr. 34-36
D-60325 Frankfurt Am Main
Tel. +49.0800-800 7462
Fax. +49.0800-900 7462
e-mail: info@sim2.de
web site: www.sim2de.com

UK:

SIM2 UK LTD
Steinway House, Worth Farm
Little Horsted, Nr. Uckfield
East Sussex TN22 5TT
Tel. +44.01825.750850
Telefax +44.01825.750851
e-mail: info@sim2.co.uk

USA:

SIM2 USA INC.
10108 USA Today Way
Miramar, FL 33025
Tel. +1.954.442.2999
Telefax +1.954.442.2998
E-mail: sales@sim2usa.com
Web site: www.sim2usa.com

SIM2 Multimedia is certified
UNI EN ISO 9001



Due to constant product development, specifications and design might be subject to change without notice. GRAND CINEMA HT3000 leaflet - World - June 2006

HT3000

1080p: full
HDTV resolution



SIM2 Grand Cinema™ HT3000

The new benchmark for future standards
in single-chip front projection

SIM2 Grand Cinema HT

SIM2 Multimedia presents the latest addition to: their award-winning Grand Cinema™ HT range: the all-new Grand Cinema HT3000. This premier single chip projector offers true, uncompressed 1920x1080 HDTV Resolution, thanks to a new 0,95" 1080p DLP® chipset from Texas Instruments.

Combining this new chipset with full 10 bit video processing, SIM2's ALPHA PATH™ light engine and Live Colors Management system, HT3000 is able to reach a new level of cinematic realism in single chip projection.

This is achieved in typical SIM2 style through a balanced design ethos: a finely tuned system will always deliver the best results.

HT3000 has a wide range of both analogue and digital video inputs, including two HDCP enabled HDMI™ sockets, ensuring compatibility with the vast array of today's video sources (including HD).

Taking styling cues from the C3X series, HT3000 sports an elegant Giorgio Revoldini designed cabinet in SIM2's signature Gunmetal finish.



Key points

- New 0,95" 1080p DLP® chipset by Texas Instruments
- 1920 x 1080 pixel HDTV resolution
- Proprietary SIM2 ALPHA PATH™ light engine
- New 7-segment color wheel (RGBRGB + NDF Neutral Density Filter)
- 2 HDMI™ HDCP inputs
- Contrast ratio >5000:1
- Lamp: 200W (dimmed)
- SIM2 Live Colors Management and Gamma Functions
- Intelligent memory functions
- New Dynamic Noise Reduction and Spatial Noise Reduction

Grand Cinema™ HT3000: Technical Specifications

LIGHT ENGINE

Technology: 1 chip DMD 0,95" 1080p DarkChip3™
Resolution: 1920 x 1080 pixels
Color Wheel: 7 segment (RGBRGB+NDF Neutral Density Filter)
Lamp power & life time*: 200W dimmed, 4000 hours*

INSTALLATION

Throw ratio: 1,5-2,0:1
Lens shift: V+/-6°
Digital keystone adjustment: V+/-18°
Picture size (inches diagonal): 50-300
Aspect ratio: 4:3, 16:9 Anamorphic, LetterBox, panoramic, pixel to pixel + 3 custom-user adjustments

ELECTRONICS

Horizontal & vertical scan freq.: 15-80kHz/48-100Hz
Video and Graphic standards: PAL (B,G,H,I,M,N,60); SECAM; NTSC 3,58; NTSC 4,43 automatically selected; HDTV: ATSC (480p, 720p, 1080i, 1080p); EU 576p + 1080i 50Hz; PC graphic: VGA, SVGA, XGA, SXGA, UXGA
Contrast ratio (Full ON/ Full OFF): >5000:1
Format Board: 10 Bit
Video processor: built in
Special video adjustments: Dynamic Noise Reduction, Spatial Noise Reduction, Fleshtone Regulation

Other special adjustments: Memories/Overscan, Live Colors Management (LCM) and Gamma Functions

INPUTS/OUTPUTS

1 x Composite Video (RCA)
1 x S-Video (mini Din 4 pin)
1 x RGBS/YCrCb (4x RCA)
1 x RGBHV/YCrCb (1x VGA)
2 x HDMI – HDCP compliant
1 x OUT Digital Audio via SPDIF connector
1 x RS232 (D-Sub 9 pin)
1 x Input External IR sensor
2 x OUT 12V 100mA (via Jack)

GENERAL SPECIFICATIONS

Software control: upgradable via RS232 serial interface
Mains voltage range: 100-240Vac ±10% (48/62Hz)
Weight: 11 Kg (24,2 lbs)
Dimensions (WxHxD): 435x195x431mm (17.1"x7.7"x17")

SUPPLIED ACCESSORIES

Installation and User Manual; AC power cords (EU, UK and USA) 2m (6.6 ft); Backlit remote control and batteries



The DLP® logo and DLP® medallion are trademarks of Texas Instruments.

(*) Lamp life: the hours quoted have been measured in a lab under strict test conditions. Lamp life varies depending on usage conditions and the surrounding environment. The measured lamp life cannot be guaranteed and is not protected by warranty