



# EPSON PowerLite® 505c

## Powerful presentations made easy

Eleven hundred lumens in a convenient 6 lb package when you size it all up, the EPSON® PowerLite® 505c is the perfect solution for highly effective mobile presentations. Bright enough to deliver brilliant performances, even in the most challenging lighting conditions, this remarkable SVGA projector consistently delivers sharp, vivid images. Take it across the hall or around the world. Its awardwinning 3-LCD design and exceptional video processing make it the ideal partner for business professionals. Its innovative EPSON EasyMP™ technology facilitates PC-free presentations so you can leave your laptop and cables behind without sacrificing advanced features. This technology also delivers lightning-fast image renderings plus fifteen transitional effects. And, with its "power-on-and-go" operation, even novice users can be up and running in no time. Having contributed over 50 years of engineering excellence to the business world, Epson continues to provide technologically-advanced, user-friendly solutions like the EPSON PowerLite 505c—the perfect combination of portability and performance.

#### Ultra bright 1100 lumens

 Projects brilliant images, even in the most challenging lighting conditions

#### Superior detail and razor-sharp contrast

- 3 LCD technology offers three 0.9" high aperture LCDs for evenly distributed color
- SVGA (800 x 600) resolution delivers sharp, vivid detail
- 400:1 contrast ratio for blacker blacks and whiter whites

#### Compact and lightweight

 Only 6 lb, allowing travel flexibility for presentations of any size, in any environment

#### PC-free presenting with EPSON EasyMP

- Auto-run capability—just power on the projector and begin
- · Unique editing capability:
  - Rearrange the order of projected images, individually or as a group
  - Select and hide individual images
  - Customize your presentation to your audience
- Easy to use—drag and drop your entire presentation using EPSON conversion software
- Smooth picture transitions—jpeg or bitmap images advance as fast as 40 milliseconds, either automatically or with a mouse click
- 15 PowerPoint\*-type transitions—includes wipes, dissolves, etc. for smooth, professional presentations

- Annotations—make notes and annotations directly on the image and capture them for future reference
- Memory card slot—multicard capability including PCMCIA Flash Memory, Compact Flash\*, SmartMedia\*, and Memory Stick\* cards

#### Component video input

 Great for movie viewing: the best video quality of any superportable available

#### Easy installation, setup and operation


- · Zoom lens adds versatility
- 15° digital keystone correction adjusts the angle, aspect ratio and shape of projected images
- EPSON SizeWise™ resizing technology supports virtually any computer (Mac or PC) up to SXGA (1280 x 1024)
- Cool and quiet operation translates into longer lamp life and lower total cost of ownership, and eliminates excessive sound during presentations

#### Renowned Epson service and support

- Comprehensive 2-year warranty
- · 90-day bulb warranty for added dependability
- EPSON PrivateLine<sup>SM</sup> dedicated toll-free support line available from 6 a.m. to 6 p.m. PST Monday – Friday. This program is free for the duration of the warranty
- EPSON Road Service Program provides a replacement projector, typically within 24 hours. This program is free for the duration of the warranty
- International warranty in over 45 countries, offered exclusively by Epson

zoom lens

<sup>\*</sup>PCMCIA adapter required, not included



### **EPSON PowerLite 505c Specifications**

Projection System		N original LCD prism technology	
Projection Method		Front/rear/ceiling mount	
LCD Size Driving method Pixel number Native resolution Aspect ratio Pixel arrangement		licon TFT Active Matrix (800 x 600) x 3 16:9, 5:4)	
Projection Lens Type F-number f-number Zoom ratio	Manual: zoom/ 2.0 to 2.2 35 to 42mm 1:1.2	focus (focus	
<b>Lamp</b> Type Life (typical)	150W UHE 1000 hours		
Screen Width Ratio: (Dis	tance/Width)	1.83 to 2.23:1	
Screen Size (Projected Di	stance)	26" to 300" (1.1m to 13.8m)	
Keystone Correction		±15 degrees	
Brightness (typical)		1100 ANSI lumens	
Contrast Ratio		400:1	
Brightness Uniformity (ty	ypical)	85%	
Color Reproduction		24 bit; 16.7 mi	
Sound Output		1W Monaura	
Operating Temperature		5°C to 35°C (41°F to 95°F)	
Power Supply Voltage	100-120\	/, 200-240V ±10%, 50/60Hz AC	
Power Consumption		230W (5W at standby mode)	
Dimension (including len	s and feet)	10.5"D x 8.4"W x 3.4"H	
Weight		6.0 lb/2.7kg	
Fan Noise		42db	
<b>Effective Scanning Frequ</b> Pixel clock Horizontal Vertical	ency Range	13.5MHz to 160MHz 15KHz to 92KHz 50Hz to 85Hz	
right/left mouse click, volur	e, special effects, s	ource selection, power, resize,	
RGB	Analog RGB I/0	)	
Display performance	, maiog Rob I/C	•	
Native	800 x 600		
Resize	1280 x 1024 1024 x 768 640 x 480		
Input terminal			
Video	Mini D-sub 15p	pin	
Audio	Stereo mini jac	k	
Output terminal Audio	Stereo mini jac	k	

600 TV Line  NTSC/NTSC4.43/NTSC50/ PAL/M-PAL/N-PAL/PAL60/SECAM  RCA x 1 S-Video x 1 Mini D-sub 15pin  RCA x 2 0 - 500m Vrms / 600ohm  Stereo mini jack (common analog RGB audio out; (plug-in, then speaker-off)  Din 9pin x 1 / USB type B x 1 PS/2, ADB, USB	out)
PAL/M-PAL/N-PAL/PAL60/SECAM  RCA x 1 S-Video x 1 Mini D-sub 15pin  RCA x 2 0 - 500m Vrms / 600ohm  Stereo mini jack (common analog RGB audio outs (plug-in, then speaker-off)  Din 9pin x 1 / USB type B x 1 PS/2, ADB, USB	out)
S-Video x 1 Mini D-sub 15pin RCA x 2 0 - 500m Vrms / 600ohm Stereo mini jack (common analog RGB audio out) (plug-in, then speaker-off)  Din 9pin x 1 / USB type B x 1 PS/2, ADB, USB	out)
0 - 500m Vrms / 600ohm Stereo mini jack (common analog RGB audio out) (plug-in, then speaker-off) Din 9pin x 1 / USB type B x 1 PS/2, ADB, USB	out)
Stereo mini jack (common analog RGB audio out) (plug-in, then speaker-off)  Din 9pin x 1 / USB type B x 1 PS/2, ADB, USB	out)
(common analog RGB audio outs (plug-in, then speaker-off)  Din 9pin x 1 / USB type B x 1 PS/2, ADB, USB	out)
PS/2, ADB, USB	
ion	
anada only) o cable, remote control, 2 batteries use cable, USB mouse cable, soft ca h memory card), application softwa rt Here Kit	s, computer ase, memory
umbers e  ulder bag  ng mount, 11/2" pipe	EMP-505 ELPLP14 ELPKC19 ELPKS35 ELPKS31 ELPKS32 ELPKS30 ELPSC06 ELPSC07 ELPSC08 ELPAP01 ELPSL01 ELPMB32 ELPMBAS
Culture e	o cable, remote control, 2 batteries is e cable, USB mouse cable, soft can memory card), application softwart Here Kit imbers ctor

800-463-7766

800-922-8911

www.epson.com

presentersonline.com



Epson America, Inc. 3840 Kilroy Airport Way, Long Beach, CA 90806

Epson Canada, Ltd.

550 McNicoll, Willowdale, Ontario M2H 2E1

**Epson Latin America** 

6303 Blue Lagoon Drive, Miami, FL 33126

Support-The Epson Connection<sup>SM</sup> Pre-Sales Support U.S. and Canada

Automated Technical Support

Presenters ONLINE™

Internet Web Site