

EPSON®

BRIGHT, SVGA PROJECTOR PACKED WITH PRESENTER-PLEASING FEATURES.

Best-in-class image quality. Exceptional 1500 ANSI lumens of brightness. Dazzling color saturation and Epson's worldclass reliability. Put them together and you've got an idea of why the EPSON PowerLite® 5350 is one of the most talked-about portable projectors to hit the market.

For starters, its 3-LCD technology produces 1.44 million pixels of eye-pleasing color. A unique metal sandwich placed between each pixel virtually eliminates light leakage and pixel "cross-talk". You'll notice the images projected from the PowerLite 5350 are sharper, crisper and better defined than those from its less sophisticated competition.

But there's more. Like a phenomenal 85% illumination ratio. So your projected images are just as rich and vivid and colorful at the image corners as in the center. A 250:1 contrast ratio makes the finest print easier to read—even from the back of the room.

The PowerLite 5350 is also one of the most versatile, easy-to-use projectors available. Its exclusive SizeWise™ imaging technology lets you use it with SXGA, XGA, SVGA and VGA computers and enjoy picture-perfect projection from them all, making it ideal for multiple presenters using different types of computers. Plus, its 20° keystone correction feature ensures sharp, easy-to-view imagery—even in small or odd shaped rooms. A remote control is a standard accessory with a host of features, including mouse control, electronic zoom and a pointer.

You can also use the PowerLite 5350 with a wide range of video signals. It supports NTSC, PAL, SECAM and is HDTV compatible! A new Picture-in-Picture feature allows simultaneous viewing of computer and video images.

The EPSON PowerLite 5350—the new high-performance, multimedia portable projector from the #1 projector manufacturer in the world. Use it to take your presentations from merely memorable to truly outstanding.



EPSON PowerLite 5350 Multimedia Projector

FEATURES

BENEFITS

- **SVGA (800 x 600) projection, 3 LCD design and unique metal sandwich structure** State-of-the-art image quality, superior color saturation, and reduced light leakage between pixels for more distant images.
- **Powerful 1500 ANSI lumens** Ultra-bright, easy-to-view images in a wide range of lighting conditions.
- **85% illumination ratio and a 250:1 contrast ratio** Even, vivid color saturation without "hot spots" and easier-to-read black text.
- **20° keystone correction** Automatic squaring of screen image lets you place the projector anywhere in the room.
- **EPSON SizeWise technology** Supports SXGA(1280 x 1024) technology, XGA (1024 x 768), SVGA (800 x 600), and VGA (640 x 480) Macintosh and PC computers.
- **Wide range of video and installation capabilities** Compatible with international video formats. Supports 16:9 aspect ratio. (HDTV)
- **EPSON PrivateLineSM toll-free technical support number** Staffed from 6 a.m. to 6 p.m. PST Monday to Friday. Calls are typically answered within 45 seconds.

EPSON POWERLITE 5350 SPECIFICATIONS

Projection System

EPSON Original Prism technology

LCD Panel

EPSON 1.32" Poly-Silicon TFT; Active-matrix

Number of Pixels

1,440,000 pixels
(800 x 600) x 3 panels

Pixel Arrangement

Stripe

Lens

Manual zoom /manual focus
1:1.3 zoom, F = 2.0 - 2.3, f = 55 - 72mm

Keystone Correction

Electronic +/- 20 degrees

Lamp

Ultra High Efficiency (UHE)
150W (user replaceable)

Image Size

Diagonal 23" - 300"

Projection Distance

3.9' - 52' (1.2m - 15.7m)

Color Reproduction

24 bit, 16.7 million colors

Brightness

1500 ANSI lumens (typical)

Contrast Ratio

250:1

Illumination Ratio

85% (typical)

Projection Methods

Front projection	Yes
Rear/ceiling mount	Yes

Audio

Built-in stereo speakers
3w + 3w stereo

Pixel Clock

13.5 - 160 MHz

H Sync

15 - 92 kHz

V Sync

43 - 85 Hz

Video Signal RGB (PC)

Video signal level

Analog RGB	0.71Vp-p 75 Ω
TTL RGB*	

Sync. signal level

Separate H, V	TTL RGB*
Composite	TTL RGB*
Sync. on green	0.286Vp-p 75 Ω

Operating Noise Level

<42 dB

*accepts 3.3V output level

Power Requirements/Consumption

AC 100 to 120V/200 to 240V
± 10%, 50/60 Hz

Multiple Aspect Ratio

5:4	SXGA, UXGA
4:3	VGA, SVGA, XGA
16:9	Wide screen video

Video

Signal level	
Composite video	1Vp-p 75 Ω
S-video	Luminance .714Vp-p, Chrominance 0.284Vp-p 75 Ω

Interface Standards

NTSC	NTSC, Chroma subcarrier frequency 3.58 MHz, 4.43 MHz Chroma subcarrier frequency CCIR, Chroma Subcarrier frequency 4.43 MHz CCIR, Carrier frequency 4.43 MHz
PAL, PAL-M, PAL-N PAI-N SECAM	
HDTV	480I, 480P, 720P, 1080I, 1080P

Audio Signal

Input	
Input voltage	500 mVrms
Input impedance	47K Ω
Output	
Output voltage	0 - 500 mVrms
Output impedance	600 Ω

Physical Characteristics

11.8" x 15.8" x 5.1" (W x D x H); 13.8 lb

Supplied Accessories

AC cable, main cable, audio/video cable, Macintosh® desktop adapter, Macintosh monitor adapter, remote control, 2 AA batteries, Link IV software CD, user's manual, quick reference guide, PS/2 mouse cable, serial mouse cable, Macintosh mouse cable, USB mouse cable, PC serial cable, Macintosh serial cable

Product/Accessory Part Numbers

EPSON PowerLite 5350 multimedia projector	ELP-5350
Optional Accessories	
Wheeled soft case for projector/laptop	ELPKS18
Soft shell shoulder case projector/laptop	ELPKS10
Molded hard shell carrying case	ELPKS17
ATA shipping case	ELPKS19
Replacement lamp unit	ELPLP09
Long throw lens	ELPLL01
Wide angle conversion lens	ELPCW01
Remote control IR receiver	ELPST02
ELP communication cable set	ELPKC17

Warranty

Standard one year limited warranty includes EPSON Road Service Program and EPSON PrivateLine dedicated toll-free support (U.S. and Canada only)

Support - The Epson Connection™

Pre-Sales Support U.S. & Canada	800-463-7766
Automated Technical Support	800-922-8911
Internet Website	http://www.epson.com
Presenters ONLINE	http://www.presentersonline.com



YOU'VE GOT TO SEE IT IN

EPSON

COLOR.™



project isle
.com.au

Where Projectors Roam Free