

EPSON PowerLite® 5600p

With 2200 Lumens, its the brightest in its class!

Just how much brightness do you expect from a high-performance, travel-friendly SVGA projector? Well, it's time to start expecting more. With the EPSON PowerLite 5600p you get a phenomenal 2200 lumens, brighter than any portable SVGA projector, in a convenient sub-15 lb package. You already know Epson for printers that deliver world class image quality. And you've probably used our innovative LCD technology in cell phones, PDAs, and camcorders. What you might not know is that we are also a world leader in LCD projector technology. So with the EPSON PowerLite 5600p, you can be confident that every image will be the best it can be. As an added benefit, the EPSON PowerLite 5600p operates at a remarkably quiet 38db, so your audience stays focused on your presentation, rather than your projector. And, with multiple input capabilities, you'll have the flexibility to present from a variety of sources. At Epson, we're committed to bringing you quality, reliability, and user-friendly

Choose the ultra bright EPSON PowerLite 5600p and go beyond your expectations.

Ultra bright 2200 lumens; weighs just 14.9 lb

 Astonishing brightness, wherever you go, from a lightweight, travel-friendly projector

Superior detail and razor-sharp contrast

- Three 1.3" high aperture LCDs for evenly distributed color across the screen
- SVGA (800 x 600) resolution for sharp, vivid detail
- 400:1 contrast ratio for blacker blacks and whiter whites
- · 200W UHE lamp

Quiet and unobtrusive

- · Whisper-quiet performance (38db)
- · Minimal light leakage

State-of-the-art video performance

- Digital comb filter for extraordinary video clarity, reduced noise and improved contrast
- Multiple video input capability
- HDTV-ready, supports 480i, 480p, 720p, 1080i and 1080p formats
- Digital Visual Interface (DVI) for convenient digital connectivity and plug and play operation

Easy installation, setup and operation


- Bayonet style twist-and-pull lens mount for quick, easy changes on site
- 30° digital keystone correction maintains distortion-free images
- EPSON SizeWise™ resizing technology supports virtually any computer (Mac or PC) up to SXGA (1280 x 1024)
- · Full-featured remote control
- · USB mouse with hot swap capability
- · Optional hard wired remote control adapter
- Lockable with Kensington[™] style locks
- RS-232 communication works with control systems and installation accessories from leading manufacturers like Crestron,™ Panja™ and Extron™
- Start Here Kit gets first-time users projecting in just minutes

Renowned EPSON service and support

- International warranty in over 45 countries, offered exclusively by Epson
- · 90-day bulb warranty for added dependability
- EPSON Road Service Program provides a replacement projector, typically within 24 hours
- EPSON PrivateLine[™] dedicated toll-free support line is available from 6 a.m. to 6 p.m. PST Monday - Friday



Front View



EPSON PowerLite 5600p Specifications

Projection System	EPSON o	original LCD prism technology	Video I/O		
Projection Method	Front/rear/ceiling mount		Display performance	NTSC: 550 line PAL: 550 line	
LCD				(Depend on observation	
Size	1.3"	TET A A		of multi-burst pattern)	
Driving method Pixel number	EPSON Poly-silicon TFT Active Matrix 480,000 dots (800 x 600) x 3		Input signal	NTSC/NTSC4.43/NTSC50/	
Native resolution	ution SVGA			PAL/M-PAL/N-PAL/PAL60/SECAM	
Aspect ratio 4:3 (supports 16:9; 5:4) Pixel arrangement Stripe		Input terminal	Composite video: RCA x 1 S-video; Mini D-sub 15pin x 1		
Projection Lens	эттре			Component video:	
Type	Manual: zoom	/focus		Mini D-sub 15pin x 1	
F-number	1.7 to 2.3		Accelia de ambieral	(common with component video)	
f-number Zoom ratio	49 to 63mm 1:1.3		Audio terminal	RCA x 2 (for composite video/ S-video/component video)	
Lamp				Stereo mini jack (for video-RGB)	
Туре	200W UHE		Output signal	Analog RGB (composite video,	
Life (typical)	1500H			S-video, Component video, Video-RGB are converted)	
Screen Width Ratio ((distance/width)	1.82 to 2.36:1		Separate HV (TTL)	
Screen Size (projecte	ed distance)	22" to 300" (1.0m to 14.5m)	Output terminal	Mini D-sub 15pin x 1	
Keystone Correction		±30°		(Common Analog RGB)	
Brightness (typical)		2200 ANSI lumens	Control I/O Mouse/serial I/O		
Contrast Ratio		300:1	I/O terminal	D-Sub 9pin x 1 (RS-232C)	
Brightness Uniformi	ty (typical)	85%	Mouse compatibility	PS/2, USB	
Color Reproduction		24 bit; 16 mil	Input terminal		
Sound Output		3W + 3W SRS	Remote control	Stereo mini jack	
Operating Temperature 5°C to 40°C (41°F to 104°F)		Warranty Standard two year limited war	ranty, international warranty, 90-day lamp		
Power Supply Voltage 100-120V, 200-240V ±10%, 50/60Hz AC			warranty, EPSÓN Road Service	warranty, EPSON Road Service Program and EPSON PrivateLine dedicated	
Power Consumption	<u>-</u> I	285W/9W @ stand by mode	toll-free support (U.S. and Car	ada only)	
Dimensions 15.8"D x 10.9"W x 6.0"H		Supplied Accessories Power cord, RCA audio cable, RCA video cable, remote control, 2 batteries, computer cable HD15/HD15, audio cable, video/audio cable,			
Weight Approx. 14.9 lbs/6.8Kg					
Fan Noise 38db			PS/2 mouse cable, USB mouse	cable, Start Here Kit	
Effective Scanning F	requency Range		Product/Accessory Part Nun		
Pixel Clock	.equency nange	14MHz to 230MHz	Epson PowerLite 5600p Projec Wide angle attachment lens	tor EMP-5600	
Horizontal Vertical		15KHz to 92KHz 43Hz to 120Hz	1.4 to 1.8	ELPAW01	
	huroc	43112 10 120112	Long throw attachment lens 2.3 to 3.0	ELPAL01	
Remote Control Features Keystone, picture in picture, special effects, source selection, power, resize,			Remote control receiver	ELPST02	
right/left mouse, click, volume, presets			Hard wired remote control rec	eiver kit ELPSTO4 ELPLP11	
RGB			Replacement lamp Component Video Cable (Dsul		
D' l	Analog RGB I/O	Digital RGB Input	ATA molded hard shell case	ELPKS38	
Display performance Native	800 x 600	800 x 600	Samsonite wheeled soft case	ELPKS35	
Resize	1280 x 1024	1024 x 768	ATA shipping case Digital video cables	ELPKS39	
Resize	1024 x 768	640 x 480	DVI to DVI, 3m	ELPKC20	
	640 x 480		DVI to DVP, 3m	ELPCK21	
Input terminal	MULD LAFT. A	D.// T D . 1	Ceiling mount Mac adapter set	ELPMB34 ELPAP01	
Video	Mini D-sub 15pin x 1 (Select with	DVI Type D x 1 (Select with	Kensington security lock	ELPSL01	
	manual switch	manual switch,	Portable screens	FLD000/	
	Exclusive to D-sub15)	Exclusive to D-sub15)	50" 60"	ELPSC06 ELPSC07	
	0		70"	ELPSC08	
Audio	Stereo mini jack (for Mini D-Sub 15)		Support-The Epson Connec	tionsm	
	RCA x2 (for 5-BNC)		Pre-Sales Support U.S. and Cal		
Output terminal			Automated Technical Support Internet Web Site	800-922-8911 www.epson.com	
Video			Presenters ONLINE	presentersonline.com	
Security	K	ensington-style lock provision	Presenters Ontint	presentersoriille.com	



Epson America, Inc.

3840 Kilroy Airport Way, Long Beach, CA 90806

Epson Canada, Ltd.

550 McNicoll, Willowdale, Ontario M2H 2E1

Epson Latin America

6303 Blue Lagoon Drive, Miami, FL 33126