IN1100 SERIES

InFocus
The Big Picture

- Compact (2400cc) and light (2.75 lb/1.25kg)
- Up to 2200 lumens with DLP® BrilliantColor™
- Instant setup with exclusive DisplayLink™ feature
- Optional WXGA widescreen works with the latest laptops

Flexible Mobility

The InFocus IN1100 mobile projector series is the perfect solution for business teams, teaching groups and presenters looking for a projector that's easy to use, easy to move, and provides a great image every time you turn it on. Connect to your laptop via USB to instantly project with InFocus' exclusive DisplayLink™ feature. This new technology transmits video along one tiny cable and also offers on-screen projector controls with zero setup time or screen configuration.

The InFocus IN1100 series projectors provide presenters with the true-to-life colors of InFocus tuned DLP® with BrilliantColor™ technology. Choose the IN1100 series if you're looking for unparalleled image quality, a widescreen resolution option and DisplayLink™ innovation bundled into a small, 2.75 pound (1.25kg) projector.

IN1100:
XGA Resolution (1024 x 768)
2100 Lumens

IN1102:
WXGA Resolution (1280 x 800)
2200 Lumens

DisplayLink™ over USB

DisplayLink™ technology transmits video content over mini-USB, offering the simplicity of zero display setup - just connect and present in seconds. Easy to carry and simple to use, DisplayLink™ eliminates the need to toggle screens and turns your computer into a fully functional remote control in the process.

8.3" / 21cm

7.1" / 18.2cm

2.5" / 6.3cm

Specifications

Native Resolution	**1100** - XGA 1024 x 768 **1102** - WXGA 1280 x 800
Display Technology	**1100** -Texas Instruments DLP 0.55"DMD with Brilliant Color™ **1102** -Texas Instruments DLP 0.65"DMD with Brilliant Color™
Brightness	**1100** - 2100 max ANSI Lumens (1550 eco mode) **1102** - 2200 max ANSI Lumens (1650 eco mode)
Contrast Ratio	1800:1
Input Sources	1 x D-Sub (HD15), 1 x S-Video, 1 x Composite (RCA), 1 x USB type B mini, 1 x 3.5mm audio in
Max Resolution	**1100** - UXGA (1600 x 1200) **1102** - WSXGA+ (1680 x 1050)
Supported Aspect Ratio	**1100** - 4:3 (native), 5:4,16:9, 16:10 **1102** - 16:10 (native), 5:4,16:9, 4:3
Computer Compatibility	PC, Macintosh
Video Compatibility	SDTV (NTSC, PAL, SECAM, 480i, 576i), ED/HDTV (480p, 576p, 720p,1080i,1080p)
Number of Colors	16.7 million
Min/Max Image Size (width)	**1100** - 22"- 242" (56 - 615cm) **1102** - 28"- 304" (71 - 772cm)
Keystone Correction	Vertical -30/+30 degrees
Zoom Ratio	1.1:1
Throw Ratio	**1100** - 1.95 - 2.15 **1102** - 1.55 – 1.7
Projection distance	3.9ft – 39ft (1.2m – 12m)
Image Offset	**1100** - 115% **1102** - 112%
Projection Methods	Front, rear
Audio	1 Watt speaker (mono)
Closed Caption	CC1, CC2
Control	Projector keypad, IR remote control, USB, RS232, RJ45, wired remote
Lamp	165W Normal / 132W Eco
Product Weight	2.75lbs (1.25Kg)
Product Dimensions	2.5"H x 8.3"W x 7.2"D (6.3cm-H x 21cm-W x 18.2cm-D)
Product Color	Black with Silver
Shipping Weight	7.5lbs (3.4Kg)
Shipping Dimensions	15.5"L x 7.28"W x 11.42"D (39 cm-H x 18cm-W x 29cm-D)
Power Consumption	185W normal operation, 164W Eco, 4.3W standby
Power Supply	100-240 Volts at 50-60 Hz
Operating Temperature	5-35°C / 41-95°F
Max Altitude	10,000ft
Ships with	Power Cord, Remote w/batteries, USB A⋯>B mini, VGA Cable, Carrying case
Menu Languages	English, Français, Deutsch, Italiano, Korean, Norsk, Português, Russian, Simplified Chinese, Spanish, Traditional Chinese, Swedish, Dutch, Polish, Turkish, Danish, Finnish
Lamp Life	4000 hrs Eco, 3000 hrs Normal
Warranty	2 years
Lamp Warranty	6 months
Accessories Warranty	90 days
Audible Noise	35 dBA Typical : Normal / 30 dBA Typical : Eco
Approvals	C-Tick (Australia), NOM (Mexico), CE (Europe), UL & CUL (USA & Canada), FCC (USA), IRAM (Argentina), GOST (Russia), MIC & eK (South Korea), CCC (China), PSB (Singapore), WEEE (EU), S. Africa, RoHS, China RoHS
Security	Kensington slot, Pin

* Product specifications, terms, and offerings are subject to change at any time without notice.

** Actual lamp life may vary based on the ambient environment and projector usage. Conditions that may affect lamp life include temperature, altitude, and rapidly switching the projector on and off.

Optional Accessories

Projection Screens (4:3, 16:10 & 16:9)
Cables & Adaptors
Security Lock (SEC-LOCK-01)
Replacement Lamp (SP-LAMP-043)
LiteShow II Wireless Adapter (IN-LITESHOW2)

LiteShow II

This wireless adaptor enables cable-free presentations through any of the InFocus IN1100 projector series. Switch presenters in seconds and transmit data, audio and stunning video over a 3oo' (95m) range.

Warranty

Providing the highest quality products and support is very important to InFocus. Just one reason why the IN1100 series of digital projectors come standard with a 2-year limited factory warranty (including parts and labor) and a 6 month limited lamp-replacement warranty. Extended product & lamp warranty programs are also available. For more information about warranty and service programs in your region, please visit:
www.infocus.com/service

InFocus
The Big Picture