



EPSON PowerLite® 703c Shine bright, travel light

Where do you find corner-to-corner brightness, superior image quality, and a host of user-friendly tools—all in one compact package? It's all at your fingertips with the EPSON® PowerLite® 703c. Take 1000 lumens and native XGA (1024 x 768) resolution with you wherever you go, on the road or in the conference room down the hall. Or, install this unobtrusive projector in your board room as a permanent fixture. A convenient 5.8 lb unit, it boasts bright, brilliant presentations, without sacrificing flexibility or high performance features. Epson's innovative three-LCD design delivers rich, vivid colors across the screen while a 320:1 contrast ratio makes even the finest print easy to read. Our versatile SizeWise™ technology enables you to use the projector with virtually any computer or workstation, up to UXGA (1600 x 1200) resolution. Use the 15° digital keystone correction to correct the angle, aspect ratio, and shape of projected images, based on where the projector is placed. And, for presentations that incorporate video, take advantage of its convenient S-video and composite video connections. A zoom lens, USB mouse port, and full-featured remote control are also included

Superior Image Quality; Weighs Under 6 lb

- 1000 lumens offers incredible brightness, even in the most challenging lighting conditions
- XGA (1024 x 768) resolution delivers sharp, vivid images and astounding detail
- 320:1 contrast ratio for blacker blacks and whiter whites
- Three 0.9" high aperture LCDs for evenly distributed color across the screen

Convenient Video Connectivity

- · Composite and S-video compatibility
- 150 Watt UHE lamp with optimized optical system
- Picture-in-picture capability for simultaneous display of video and computer presentations
- Digital comb filter for improved image quality

Easy Installation, Setup and Operation


- Compact size (10.5" x 3.4" x 8.4") designed to fit in your computer bag
- · 15° digital keystone correction
- Zoom lens
- EPSON SizeWise[™] resizing technology supports virtually any computer from VGA to UXGA (1600 x 1200)
- · Full-featured remote control
- USB mouse connection
- · Auto setup tunes and optimizes your computer input
- Start Here Kit gets first-time users projecting in just minutes
- · Cable lock feature for security conscious environments
- 4-button control panel with help button

Renowned Epson Service and Support

- · Comphrehensive 2-year warranty
- · 90-day bulb warranty for added dependability
- EPSON PrivateLineSM dedicated toll-free support line available from 6 a.m. to 6 p.m. PST Monday – Friday. This program is free for the duration of the warranty
- EPSON Road Service Program provides a replacement projector, typically within 24 hours. This program is free for the duration of the warranty
- International warranty in over 45 countries, offered exclusively by Epson



Front View



Back View

EPSON PowerLite 703c Specifications

Projection System	EPSON original LCD prism technology		
Projection Method		Front/rear/ceiling mount	
LCD Size Driving method	0.9"	n TET Active Matrix	
Pixel number Native resolution	EPSON Poly-Silicon TFT Active Matrix 786,432 dots (1024 x 768) x 3 XGA		
Aspect ratio Pixel arrangement	4:3 (supports 16:9, 5:4) Stripe		
Projection Lens Type	Manual: zoom/focus		
F-number	2.0 to 2.2		
f-number Zoom ratio	35 to 42mm 1:1.2		
Lamp			
Туре	150W UHE		
Life(typical)	1000H		
Screen Width Ratio: (Dista	<u> </u>	1.83 to 2.23:1	
Screen Size (Projected Dis	tance)	26" to 300" (1.1m to 13.8m)	
Keystone Correction		±15 degrees	
Brightness (typical)		1000 ANSI lumens	
Contrast Ratio		320:1	
Brightness Uniformity (ty	pical)	85%	
Color Reproduction		24 bit; 16.7 mil	
Sound Output		1W monaural	
Operating Temperature		5°C to 35°C (41°F to 95°F)	
Power Supply Voltage	100-120V, 2	200-240V ±10%, 50/60Hz AC	
Power Consumption		230W (5W at standby mode)	
Dimension (including lens	and feet)	10.5"D x 8.4"W x 3.4"H	
Weight		5.8 lb/2.6kg	
Fan Noise		42db	
Effective Scanning Freque Pixel clock Horizontal Vertical	ency Range	25.2MHz to 162MHz 15.6KHz to 91.1KHz 50Hz to 86.9Hz	
Remote Control Features Keystone, picture in picture, right/left mouse click, volum		rce selection, power, resize,	
RGB			
Display performance	Analog RGB I/O		
Native	1024 x 768		
Resize	1600 x 1200 1280 x 1024 800 x 600 640 x 480		
Input terminal			
Video	Mini D-sub 15pin		
Audio	Stereo mini jack		
Output terminal	Storoo mini incl		
Audio	Stereo mini jack (Common Video / (plug-in, then spe		

Video I/O Display performance	NTSC: 550 line PAL: 550 line (Depends on observation of multi-burst pattern)	
Input signal	NTSC/NTSC4.43/NTSC50/ PAL/M-PAL/N-PAL/PAL60/SECAM	
Input terminal Video	Composite video: RCA x 1 S-Video x 1 Video RGB: Mini D-sub 15p	oin
Audio	RCA x 2	
Output signal	0 - 500m Vrms / 600ohm	
Output terminal	Stereo mini jack (Common Analog RGB Audio output) (plug-in, then speaker-off)	
Control I/O Mouse/serial I/O I/O terminal Mouse compatibility	Din 9pin x 1 / USB type B x PS/2, ADB, USB	1
Security	Kensingtor	n-style lock provisio
	dio cable, remote control, 2 ba ouse cable, USB mouse cable, s	
Product/Accessory Part N EPSON PowerLite 703c Proj Replacement lamp Samsonite wheeled soft cas Slimline soft shoulder bag Notebook/projector soft sh ATA molded hardshell case 50" portable screen 60" insta-theatre screen 80" insta-theatre screen Mac adapter set Kensington security lock Ceiling mount Suspension adapter for ceil Suspension adapter for ceil Presentation audio system Wireless microphone syster	ector se pulder bag ing mount, 11/2" pipe ing mount, 1" pipe	EMP-703 ELPLP14 ELPKS35 ELPKS31 ELPKS30 ELPSC07 ELPSC08 ELPAP01 ELPSL01 ELPMB32 ELPMBA1 ELPMBA1 ELPPAS1
Support-The Epson Conr Pre-Sales Support U.S. and Automated Technical Support Internet Web Site	nection sm Canada	800-463-776 800-922-891 www.epson.co
		opssoo



presentersonline.com



Epson America, Inc. 3840 Kilroy Airport Way, Long Beach, CA 90806

Epson Canada, Ltd.

Presenters ONLINE™

550 McNicoll, Willowdale, Ontario M2H 2E1

Epson Latin America

6303 Blue Lagoon Drive, Miami, FL 33126