



EPSON PowerLite® 70c

A brilliant value in ultraportable projectors

If you're looking for an exceptional value, the 6.8 lb EPSON PowerLite 70c offers superior image quality and a comprehensive feature set–all at a price that's sure to please. With 700 lumens and native XGA resolution, it's designed to meet all your presentation needs, delivering both power and portability without sacrificing performance.

You already know Epson for our world class image quality printers. And, you've probably used our innovative LCD technology in cell phones, PDAs, and camcorders. What you might not know is that we are also the world leader in LCD projector technology. Our three-LCD design produces superior color saturation across the screen, while ensuring cool operation, even after many hours of use.

Built with a variety of user-friendly features, the EPSON PowerLite 70c gives you the flexibility to conduct any presentation with confidence and ease. Its simple 4-button control panel is ideal for both novice users and seasoned professionals, and includes a context-sensitive help feature. Use its 15° digital keystone correction to correct the angle, aspect ratio and shape of projected images. A digital zoom lens and full-featured remote control are also included in this powerful, yet economical, superportable projector.

700 lumens; weighs just 6.8 lb

 Incredible brightness from a travel-friendly, ultraportable projector

Superior detail and razor-sharp contrast

- Three EPSON 0.7" high aperture LCDs for rich color saturation across the screen
- 150W UHE lamp
- · 400:1 contrast ratio for blacker blacks and whiter whites
- XGA (1024 x 768) resolution for sharp, vivid detail

State-of-the-art video performance

- Digital comb filter for extraordinary video clarity, reduced noise and improved contrast
- Component video input capability (optional cable required)
- HDTV-ready, supports 480i, 480p, 720p, and 1080i formats (optional cable required)

Easy installation, setup and operation

- Start Here Kit gets first time users projecting in just minutes
- 15° digital keystone correction ensures distortion-free images
- Simplified 4-button control panel
- EPSON SizeWiseTM resizing technology supports virtually any computer (Mac or PC) up to SXGA (1280 x 1024)
- Easy-to-use remote control with right/left mouse emulation, a pointer, and three special effects (the stamp, horizontal bar, and marker)
- USB mouse with hot swap capability
- Digital zoom: scaling range of 100% to 83%
- · Standard carrying case included
- · Cable lock feature for security conscious environments

Renowned EPSON service and support

- · Comprehensive 2-year warranty
- · 90-day bulb warranty for added dependability
- EPSON PrivateLineSM dedicated toll-free support line available from 6 a.m. to 6 p.m. PST Monday - Friday. This program is free for the duration of the warranty
- EPSON Road Service Program provides a replacement projector, typically within 24 hours. This program is free for the duration of the warranty
- International warranty in over 45 countries, offered exclusively by EPSON



Front View



EPSON PowerLite 70c Specifications

Projection System Projection Method	EPSON original LCD prism technology Front/rear/ceiling mount		Video I/O Display performance	750 TV Line	
LCD		Ont/rear/celling mount	Input signal	NTSC/NTSC4.43/	
Size	0.7 inches		iripat signai	PAL/M-PAL/N-PAL/	
Driving Method	EPSON Poly-Silicon TFT Ac	ctive Matrix	Input terminal		
Pixel Number	786,432 dots (1024 x 768) x 3		Video	RCA x 1; S-video >	
Native Resolution Aspect Ratio	XGA 4:3 (supports 16:9, 5:4)				
Pixel Arrangement	4.3 (supports 10.4, 5.4) Stripe		Audio	RCA x 2	
Projection Lens			Output signal	0 - 500 Vrms/600	
Type	Manual focus		Output terminal	Stereo mini jack	
F-number	1.5		·	(Common analog	
f-number Zoom ratio	26.3mm Digital (1.0-1.2); lens at max size,			(Plug in, then spea	
20011114110	zoom reduces up to 83%		Control I/O		
Lamp	<u>'</u>		Mouse/Serial I/O	Din Onin v 1/UCD	
Туре	150W UHE		I/O terminal Mouse compatibility	Din 9pin x 1/USB t PS/2, ADB, USB	
Life (typical)	1500H				
	(Approx. 5 years, based on 6 hours/week x 50 weeks/year)		Security	K	
Company Milable Debies (died			Warranty Standard two year limited	warranty, internationa	
	en Width Ratio: (distance/width) 1.77 to 2.1		warranty, EPSON Road Se	warranty, EPSON Road Service Program and EPSO	
Screen Size (projected di	stance) 28 to	300" (1.0m to 11.0m)	toll-free support (U.S. and	Canada only)	
Keystone Correction		±15 degrees	Supplied Accessories	rol 2 AA battarias co	
Brightness (typical)		700 ANSI lumens	Power cable, remote cont video/audio cable, PS/2 m		
Contrast Ratio		400:1	standard carrying case		
Brightness Uniformity (t	ypical)	88%	Product/Accessory Part	Numbers	
Color Reproduction	on 24 bit; 16.7 mil		,	EPSON PowerLite 70c Projector Replacement lamp ATA shipping case ATA molded hard shell shipping case Samsonite wheeled soft case Laptop/projector carrying case Ceiling mount Component video cable	
Sound Output	1W monoaural		•		
Operating Temperature	41°F to 95°F (5°C to 35°C)				
Power Supply Voltage	100-120V, 200-240V ±10%, 50/60Hz AC				
Power Consumption	230W/8.6W @ stand by mode				
Dimension	9.1"D x 11.9"W x 3.9"H				
Weight	6.8 lbs/3.1 kg		Mac adapter set		
Fan Noise	42db		3	Presentation Audio System Wireless microphone system	
Effective Scanning Frequency Range			50" portable screen 60" insta-theatre screen		
Pixel Clock 13.5MHz to 162MHz					
Horizontal	15KHz to 92KHz			80" insta-theatre screen	
Vertical		50Hz to 85Hz	Kensington security lock		
Remote Control Features			Support-The Epson Cor Pre-Sales Support U.S. and		
	ource selection, power, e-zoo	om, right/left mouse,	Automated Technical Sup		
click, volume			Internet Web Site		
RGB	Analog RGB I/O		Presenters ONLINE		
Display performance	Allalog ROD I/O				
Native	1024 x 768				
Resize	1280 x 768				
	800 x 600				
	640 x 480				
Input terminal					
Video	Mini D-sub 15pin				
Audio	Stereo mini jack (RGB)				
	RCA x2 (YUV)				
Output terminal					
	Storoo mini lack				

PAL/M-PAL/N-PAL/PAL60/SECAM RCA x 1; S-video x 1 RCA x 2 0 - 500 Vrms/600 ohm Stereo mini jack (Common analog RGB audio output) (Plug in, then speaker off) Din 9pin x 1/USB type B x 1 PS/2, ADB, USB Kensington-style lock provision ranty, international warranty, 90-day lamp Program and EPSON PrivateLine dedicated nada only) 2 AA batteries, computer cable HD15/HD15 cable, USB mouse cable, Start Here kit, nbers EMP-70 ELPLP13 ELPKS37 g case ELPKS36 ELPKS35 ELPKS13 ELPMB35 ELPKC19 ELPAP01 ELPPAS1 ELPCVS1 ELPSC06 ELPSC07 ELPSC08 ELPSL01 tion℠ 800-463-7766 800-922-8911 www.epson.com presentersonline.com



Stereo mini jack

(common video audio output) (plug in, then speaker off)

Audio

Epson America, Inc.

3840 Kilroy Airport Way, Long Beach, CA 90806

Epson Canada, Ltd.

550 McNicoll, Willowdale, Ontario M2H 2E1

Epson Latin America

6303 Blue Lagoon Drive, Miami, FL 33126

Specifications and terms are subject to change without notice. EPSON is a registered trademark of Seiko Epson Corporation. PowerLite is a registered trademark, SizeWise is a trademark and Epson Connection, PrivateLine and Presenters Online are service marks of Epson America, Inc. All other product and brand names are trademarks and/or registered trademarks of their respective companies. Epson disclaims any and all rights in these marks. $^{\odot}$ Copyright 2001 Epson America, Inc. CPD-11614 50K 2/01 LG Printed on Recycled Paper