EB-L12000Q



DATASHEET / BROCHURE



























The EB-L12000Q is the industry's first 12,000-lumen native 4K 3LCD projector¹

The EB-L12000Q offers an incredible resolution and a host of features that hugely benefit the rental and installation sector, such as backwards lens compatibility and swappable interface boards. It's a great addition to the line-up as it's designed to be used at events, festivals, visitor attractions, large auditoriums, trade shows and shopping centres, as well as for corporate and educational purposes.

Enter the world of ultra-detailed projection with Epson's first native 4K projector, which works perfectly with existing Epson lenses. The EB-L12000Q includes a native 4K panel developed to offer 4K resolution, at 3840x2160 pixels, for projections of a higher quality than UHD.

Epson's highest resolution projector

The EB-L12000Q is the industry's first 12,000-lumen native 4K 3LCD projector¹. It's compatible with standard Epson 4K-compatible lenses, as used on the EB-L1000 series and EB-L20000U projectors.

Easy installation

It's light, compact and easy for a single person to transport and install. The EB-L12000Q offers 360-degree installation and can project from any angle, as well as in portrait mode. It can be used in conjunction with Epson's Professional Projector Tool software to set up multiple-unit installations, and take advantage of advanced techniques such as edge blending and projection mapping.

Minimal maintenance

A five-year, 20,000-hour warranty, coupled with inbuilt self-recalibration, means these projectors can be installed and forgotten about. A built-in camera enables remote adjustment and troubleshooting.

Reliability

A steel chassis and sealed optical system protect against dust and smoke, making it suitable for the harshest environments and the toughest rental jobs. The EB-L12000Q can also be fitted with confidence in hard-to-access areas.

KEY FEATURES

- Bright, detailed, vibrant images
 The industry's first 12,000-lumen native
 4K 3LCD projector¹
- Light and compact
 A small, light unit that is easy to fit into existing installations
- Trusted reliability
 A five-year, 20,000-hour warranty
- Easy installation
 Simple for a single person to transport and install.
- Dust-proof structure
 Housing a sealed optical engine ensures durability







PRODUCT SPECIFICATIONS

TECHNOLOGY

Projection System 3LCD Technology
LCD Panel 1.03 inch with C2 Fine

IMAGE

Colour Light Output 12,000 lumen- 8,400 lumen (economy) in accordance with IDMS15.4

White Light Output 12,000 lumen - 8,400 lumen (economy) in accordance with ISO 21118:2012

Portrait Colour Light Output 12,000 lm Portrait White Light Output 12,000 lm

Resolution Native 4K, 3840x2160, 16:9

Contrast Ratio 2,500,000 : 1

Native Contrast 1.200 : 1

Keystone Correction Manual vertical: ± 45 °, Manual horizontal ± 30 °

Colour Reproduction upto 1.07 billion colours

OPTICAL

Projection Ratio 1.52 - 2.47:1

Zoom Motorized, Factor: 1 - 1.61

Lens position memory 10 positions

Image Size 60 inches - 1,000 inches

 Projection Distance Wide
 2 m - 34.2 m

 Projection Distance Tele
 3.2 m - 55.3 m

 Projection Distance Wide/Tele 1.98 m - 55.28 m

 Projection Lens F Number
 1.8 - 2.3

 Focal Distance
 36 mm - 57.3 mm

 Focus
 Motorized

CONNECTIVITY

Interfaces HDBaseT, DVI in, VGA out, VGA in, Ethernet interface (100 Base-TX / 10 Base-T), RS-232C,

USB 2.0 Type B (Service Only), Wireless LAN b/g/n (2.4GHz) (optional), HDMI (HDCP 2.2), Display Port (optional), 12G SDI Input, 12G SDI Output, 3G-SDI Input (4x), DC Power Output

(900mA), 3G-SDI Output (4x), Ethercon LAN

Epson iProjection App Ad-Hoc / Infrastructure

ADVANCED FEATURES

Video Colour Modes

Security Kensington lock, Security bar, Wireless LAN security, Password protection

Features Absolute Black, Auto calibration, Customizable user logo, Frame interpolation, Integrated

camera for image calibration & image capture, Lens position memory Cinema, Dynamic, Presentation, DICOM SIM, Multi Projection, BT709

GENERAL

Energy Use 1,741 W, 1,030 W (economy), 0.5 W (standby), On mode power consumption as defined in

JBMS-84 1,546 W

Heat Dissipation 5,919 BTU/hour (max)

Product dimensions 620 x 790 x 358 mm (Width x Depth x Height)

Product weight 51.4 kg

Noise Level Normal: 45 dB (A) - Economy: 38 dB (A)

Included Software Epson Projector Management Software, EasyMP Multi PC Projection

Room Type / Application Boardroom, Large Meeting Room / Auditorium, Projection Mapping, Rental / Staging, Signage

/ Retail, Visitor Attraction

OTHER

Warranty 60 months Carry in or 20,000 h

EB-L12000Q

WHAT'S IN THE BOX

- Remote control incl. batteries
- Quick Start Guide
- Power and signal cable (3 m)
- Cable cover
- CD Manual



OPTIONAL ACCESSORIES

EB-L12000Q


- Stacking Frame ELPMB57 L12000Q/L20000U (EVO) V12H989B57
- Ceiling Mount ELPMB47 Low EB-G7000/L1000 V12H802010
- Ceiling Mount ELPMB48 High EB-G7000/L1000 V12H803010
- HDBaseT Transmitter ELPHD01 V12H547041

OPTIONAL LENSES

- Lens ELPLW08 Wide throw V12H004W08
- Lens ELPLL08 Long throw G7000/L1000 series V12H004L08
- Lens ELPLM10 Mid throw 3 G7000/L1000 series V12H004M0A
- Lens ELPLM11 Mid throw 4 G7000/L1000 series V12H004M0B
- Lens ELPLM15 Mid Throw L1500/L1700 Series V12H004M0F
- Lens ELPLU03 G7000 & L1000 Series ST off axis 1 V12H004U03
- Lens ELPLU04 G7000 & L1000 Series ST off axis 2 V12H004U04
- Lens ELPLW06 L1500U/1505U wide zoom 2 V12H004W06
- Lens ELPLX02 UST Lens L1500/1700 Series V12H004X02

LOGISTICS INFORMATION

SKU	V11H832840
EAN code	8715946663203
Country of Origin	China



Home users: 0343 90 37766
Business users*: 0871 42 37766
Republic of Ireland: 01 436 7742
Or visit us at https://www.epson.co.uk/contactus
* 10p per minute plus network extras.

Web: www.epson.co.uk www.epson.ie

1. As of October 2018.

