

Key Features

- 1.3X optical zoom
- SuperColor™ technology
- Energy-efficient SmartEco+ Mode
- Vertical Lens Shift
- vColorTuner



Product Description

The ViewSonic PX703HD is a practical Home Cinema Projector, featuring 3500 ANSI lumens, 1080p Full HD resolution, and ViewSonic's exclusive SuperColor™ technology, which together produce the finest of details and stunning colour in any medium sized space. The projector comes with an energy-saving SuperEco+ mode that reduces power consumption and extends lamp life to up to 20,000 hours, reducing the frequency of lamp replacement and lowering maintenance costs. Digital lens shift and 1.3x optical zoom make flexible installation a breeze. Users can also utilise the vColorTuner software and cloud-based colour profile exchange to create customised colour profiles, share them, or download other profiles to fine-tune them as their own. Dual HDMI inputs and USB power supply further increase the flexibility of the user's entertainment experience.



1. Keypad
2. LED Indicator
3. Lens
4. Power Key
5. Zoom/Focus
6. Front IR
7. USB Type A

8. HDMI Port
9. Audio In/Out
10. Computer In
11. Computer Out
12. RS-232
13. Kensington Lock

SPECIFICATION

Projection System:	0.47" 1080p
Native Resolution:	1920x1080
DMD Type:	DC3
Brightness:	3500 ANSI Lumens
Contrast Ratio with SuperEco Mode:	12000:1
Display Colour:	1.07 Billion Colours
Light Source Type:	Lamp
Light Source Life (Normal):	5000
Light Source Life (SuperEco):	20000
Lamp Watt:	203W
Lens:	F=1.9-2.47, f=12-15.6mm
Projection Offset:	110%+/-6%
Throw Ratio:	1.13-1.47
Optical Zoom:	1.3x
Digital Zoom:	0.8x-2.0x
Image Size:	30"-300"
Throw Distance:	0.75m-9.76m (100"@2.5m)
Keystone:	+/- 40° (V)
Lens Shift V. Range:	Yes (+/- 5%)
Audible Noise (Normal):	31dB
Audible Noise (Eco):	27dB
Input Lag:	16ms
Resolution Support:	VGA(640 x 480) to WUXGA_RB(1920 x 1200) *RB-Reduced Blanking
HDTV Compatibility:	480i, 480p, 576i, 576p, 720p, 1080i, 1080p
Video Compatibility:	NTSC, PAL, SECAM
Horizontal Frequency:	15K-102KHz
Vertical Scan Rate:	23-120Hz

INPUT

Computer in (share with component):	1
HDMI:	2 (HDMI 1.4/ HDCP 1.4)
Audio-in (3.5mm):	1

OUTPUT

Monitor out:	1
Audio out (3.5mm):	1
Speaker:	10W
USB Type A (Power):	1 (5V/ 1.5A)

CONTROL

RS232 (DB 9-pin male):	1
------------------------	---

OTHERS

Power Supply Voltage:	100-240V+/- 10%, 50/60Hz (AC in)
Power Consumption:	Normal: 300W Standby: <0.5W
Operating Temperature:	0-40°C
Net Weight:	2.62kg
Dimensions (WxDxH) with Adjustment Foot:	312x222x108mm
OSD Language:	English, French, Spanish, Thai, Korean, German, Italian, Russian, Swedish, Dutch, Polish, Czech, T-Chinese, S-Chinese, Japanese, Turkish, Portuguese, Finnish, Indonesian, India, Arabic, Vietnamese, Greek, Total 23 languages

STANDARD ACCESSORY

Power Cord:	1
VGA Cable:	1
Remote Control:	1
QSG:	1

OPTIONAL ACCESSORY

Lamp/Light Source:	RLC-123
--------------------	---------