EB-L1715S



DATASHEET / BROCHURE































Versatile 15,000-lumen 3LCD laser projector, offering outstanding fit and forget reliability as well as sharp, vivid imagery with SXGA+ resolution.

Exceptionally bright 15,000-lumen SXGA+ performance combines with rich, vivid colours to make the EB-L1715S installation laser projector an ideal option for large rooms and venues. As well as reliable fit and forget performance, it offers very flexible installation, creating a dedicated solution for scenarios where only maximum performance and durability will do.

Laser-sharp images

Ensure that your presentations, images and video pack a punch with the vivid, sharp projection offered by this 3LCD laser projector. Designed for larger venues, its high resolution SXGA+ images are vivid and bright, even in daylight, while inorganic phosphor wheel technology provides superior light and heat resistance to deliver excellent reliability that lasts for up to 83,000 hours¹.

Flexible positioning

Thanks to a wide range of motorised lenses, including optional ultra-short-throw (UST) lens, the projector benefits from true 360° installation flexibility, allowing it to be placed virtually anywhere - without loss of brightness or distortion of image. The projector also has a built-in camera to ensure accurate calibration and capture diagnostic images (this can be fully disabled to prevent remote access).

Versatile new software

All models in the EB-L1000 series can take advantage of free Epson Professional Projector Tool software from December 2017. It allows you to set up multiprojector installations straight out of the box, simply and quickly, as well as utilising advanced techniques such as projection-mapping and edge-blending.

Quick set-up

Get started quickly thanks to a lens memory function which stores projector settings such as image position, focus and zoom, for prompt access when projecting images in different aspect ratios, or using different lenses.

KEY FEATURES

- Laser light source technology
 Outstanding brightness and colour, with fit and forget reliability
- Sharp, clear imagery
 Outstanding clarity and detail for crisp images and readable text
- Versatile new software
 Set up multiple projector installations and utilise advanced projection techniques
- Flexible 360° installation
 True flexibility without distortion or loss of brightness
- Added peace of mind
 Product comes with five-year, 20,000-hour warranty





PRODUCT SPECIFICATIONS

TECHNOLOGY

Projection System 3LCD Technology
LCD Panel 1.06 inch with C2 Fine

IMAGE

Color Light Output 15,000 Lumen (economy) In accordance with ISO 21118:2013
White Light Output 15,000 Lumen - 10,500 Lumen (economy) In accordance with ISO 21118:2013

Portrait Colour Light Output 15,000 lm Portrait White Light Output 15,000 lm

Resolution SXGA+ (14000 x 1050), 4:3

 Aspect Ratio
 4:3

 Contrast Ratio
 2,500,000 : 1

 Native Contrast
 2,000 : 1

 Light source
 Laser

Laser Light source 20,000 hours Durability High, 30,000 hours Durability Eco

Keystone Correction Manual vertical: ± 45 °, Manual horizontal ± 30 °

Colour Reproduction Upto 1.07 billion colours

OPTICAL

Throw Ratio 1.62 - 2.65:1

Zoom Motorized, Factor: 1 - 1.6

Projection Lens Zoom Ratio 1.62 - 2.56 : 1 Lens Optical

Lens Shift Motorized - Vertical ± 55 %, horizontal ± 19 %

Lens position memory
Screen Size
60 inches - 500 inches
Projection Distance Wide
Projection Distance Tele
3.2 m - 27.1 m
Projection Distance Wide/Tele 1.93 m - 27.1 m
Projection Lens F Number
Projection Lens Focal Length
Projection Lens Focus
Motorized
Interchangeable Lens
10 positions
1.9 m - 16.7 m
1.9 m - 27.1 m
1.8 - 2.3
Projection Lens Focus
Motorized
Interchangeable Lens
10 positions
1.9 m - 16.7 m
1.9 m - 16.7 m
1.9 m - 16.7 m
1.9 m - 27.1 m
1.8 - 2.3
Projection Lens Focus
Motorized
Interchangeable Lens

CONNECTIVITY

Interfaces Stereo mini jack audio in (3x), Stereo mini jack audio out, HDBaseT, BNC in, HDMI in, DVI in,

VGA out, VGA in, Ethernet interface (100 Base-TX / 10 Base-T), RS-232C, USB 2.0 Type B

(Service Only), Wireless LAN b/g/n (2.4GHz) (optional)

Epson iProjection App Ad-Hoc / Infrastructure

ADVANCED FEATURES

Security Kensington lock, Security bar, Wireless LAN unit lock, Wireless LAN security, Password

protection

Other features Absolute Black, Auto Calibration, Customizable user logo, Frame interpolation, Integrated

camera for image calibration & image capture, Lens position memory

Video Color Modes Cinema, Dynamic, Presentation, DICOM SIM, Multi Projection, BT709

Projector control via: AMX, Crestron, Extron

GENERAL

Power consumption 1,024 Watt, 647 Watt (economy), 0.3 Watt (standby), On mode power consumption as defined

in JBMS-84 938 Watt

Supply Voltage AC 100 V - 240 V, 50 Hz - 60 Hz

Product dimensions 586 x 492 x 211 mm (Width x Depth x Height)

Product weight 24 kg

Noise Level Normal: 40 dB (A) - Economy: 32 dB (A) (4K enhancement OFF)

Supported Temperature Storage -10° C - 60° C

Supported Humidity Operation 20% - 80%, Storage 10% - 90% Included Software EasyMP Monitor, EasyMP Multi PC Projection

Options HDBaseT Transmitter, Quick wireless USB key, Wireless LAN unit

| Poem Type | Application | Medical room | Claserson | Projection | Medical room | Violette Attra

Room Type / Application Meeting room / Classroom, Projection Mapping, Rental / Staging, Visitor Attraction

Positioning Ceiling Mounted

Colour Black

OTHER

Warranty 60 months Carry in or 20,000 h
Optional warranty extension available

EB-L1715S

WHAT'S IN THE BOX

- Remote control incl. batteries
- Quick Start Guide
- Power and signal cable (3 m)
- Computer cable
- Cable cover
- CD Manual







OPTIONAL ACCESSORIES

Air Filter - ELPAF51

V13H134A51

V12H547040

• Ceiling Mount - ELPMB47 Low EB-G7000/L1000 V12H802010

• Ceiling Mount - ELPMB48 High EB-G7000/L1000

V12H803010 HDBaseT Transmitter - ELPHD01

• Quick Wireless Connect USB key - ELPAP09 V12H005M09

• Wireless LAN Adapter - ELPAP10 V12H731P01

• Stacking Frame - ELPMB59 - L1000 Series (EVO) V12H996B59

OPTIONAL LENSES

- Lens ELPLU03S L & G Series ST off axis 1 V12H004UA3
- Lens ELPLL08 Long throw G7000/L1000 series V12H004L08
- Lens ELPLM10 Mid throw 3 G7000/L1000 series V12H004M0A
- Lens FLPI M11 Mid throw 4 G7000/L1000 series V12H004M0B
- Lens ELPLM15 Mid Throw L1500/L1700 Series V12H004M0F
- Lens ELPLU03 G7000 & L1000 Series ST off axis 1 V12H004U03
- Lens ELPLU04 G7000 & L1000 Series ST off axis 2 V12H004U04
- Lens ELPLW05 G7000 & L1000 Series wide zoom 1 V12H004W05
- Lens ELPLW06 L1500U/1505U wide zoom 2 V12H004W06
- Lens ELPLX02 UST Lens L1500/1700 Series V12H004X02
- Lens ELPLW08 Wide throw V12H004W08

LOGISTICS INFORMATION

sku	V11H890140
EAN code	8715946645988
Country of Origin	China

For further information please contact your local Epson office or visit www.epson-europe.com

Austria 01 253 49 78 333 Belgium +32 (0)2 792 04 47 Czech 800/142 052 Denmark 44 50 85 85 Finland 0201 552 091 France 09 74 75 04 04

(Cost of local call, operator charges may apply) Germany +49 (0) 2159/92 79 500 Greece +30 211 198 62 12 Hungary 06800 147 83 Ireland 01 436 7742 Italy 02-660321 10 (0,12 /min) Luxembourg +352 27860692 Middle East +9714 8872172 Netherlands +31 (0)20 708 5099 Norway

+47 67 11 37 00 Poland 0-0-800 4911299 (0,16 zł/min) Portugal 707 222 111 Russia (095) 777-03-55 Slovakia 0850 111 429 South Africa (+2711)

Spain 93 582 15 00 Sweden 0771-400135 (Mobilsamtal - 0,99 kr/min, Lokala samtal - 0,30 kr/min, Utlandssamtal - 0,89 kr/min)

Turkey (0212) 3360303 United Kingdom 0871 222 6702

Switzerland 022 592 7923

EPSON

1. - Laser life of up to 83,000 hours in custom mode.

EB-L1715S

^{*} Warranty offers are not available for all countries. Please contact your local Epson representative.