EB-L1555U



Extremely bright 12,000-lumen WUXGA 3LCD laser projector , offering outstanding fit and forget reliability with 4K enhancement technology.

Thanks to outstandingly bright 12,000-lumen WUXGA performance and rich, vivid colours as well as reliable fit and forget performance, the EB-L1555U installation laser projector is ideally suited to large rooms and venues. With flexible installation and low maintenance, this 4K-enhanced projector offers a perfect solution for scenarios where only maximum performance and durability will do.

Laser-sharp images

Ensure that your presentations, images and video pack a punch with the vivid, sharp projection offered by this 3LCD laser projector. Designed for larger venues, its high resolution WUXGA images are vivid and bright, even in daylight, while inorganic phosphor wheel technology provides superior light and heat resistance to deliver excellent reliability that lasts for up to 83,000 hours¹.

4K enhancement

For a next-level viewing experience, the projector features ingenious 4K enhancement technology, giving images exceptional sharpness and clarity, and ensuring that text in presentations is clearly legible.

Flexible positioning

Thanks to a wide range of motorised lenses, including optional ultra-short-throw (UST) lens, the projector benefits from true 360° installation flexibility, allowing it to be placed virtually anywhere - without loss of brightness or distortion of image. The projector also has a built-in camera to ensure accurate calibration and capture diagnostic images (this can be fully disabled to prevent remote access).

Versatile new software

All models in the EB-L1000 series can take advantage of free Epson Professional Projector Tool software from December 2017. It allows you to set up multiprojector installations straight out of the box, simply and quickly, as well as utilising advanced techniques such as projection-mapping and edge-blending.

DATASHEET / BROCHURE



KEY FEATURES

- Laser light source technology Outstanding brightness and colour, with fit and forget reliability
- HD images with 4K enhancement Exceptional sharpness, clarity and detail for crisp images and legible text
- Versatile new software Set up multiple projector installations and utilise advanced projection techniques
- Flexible 360° installation True flexibility without distortion or loss of brightness
- Added peace of mind Product comes with five-year, 20,000hour warranty







PRODUCT SPECIFICATIONS

TECHNOLOGY	
Projection System	3LCD Technology
LCD Panel	1.03 inch with C2 Fine
IMAGE	
Color Light Output	12,000 Lumen- 10,500 Lumen (economy) In accordance with ISO 21118:2013
White Light Output	12,000 Lumen - 10,500 Lumen (economy) In accordance with ISO 21118:2013
Resolution	WUXGA, 1920 x 1200, 16:10
High Definition	4K enhancement
Aspect Ratio	16:10
Contrast Ratio	2,500,000 : 1
Native Contrast	2,000 : 1
Light source	Laser
Laser Light source	20,000 hours Durability High, 30,000 hours Durability Eco
Keystone Correction	Manual vertical: ± 45 °, Manual horizontal ± 30 °
Colour Reproduction	Upto 1.07 billion colours
OPTICAL	
Throw Ratio	1.57 - 2.56:1
Zoom	Motorized, Factor: 1 - 1.6
Projection Lens Zoom Ratio	1.57 - 2.56 : 1
_ens	Optical
Lens Shift	Motorized - Vertical ± 60 %, horizontal ± 18 %
ens position memory	10 positions
Screen Size	60 inches - 500 inches
Projection Distance Wide	2 m - 17.2 m
Projection Distance Tele	3.3 m - 27.8 m
Projection Distance Wide/Tele	e 1.99 m - 27.77 m
Projection Lens F Number	1.8 - 2.5
Projection Lens Focal Length	
Projection Lens Focus	Motorized
nterchangeable Lens	Yes
CONNECTIVITY	
nterfaces	Stereo mini jack audio in (3x), Stereo mini jack audio out, HDBaseT, BNC in, HDMI in, DVI in,
nterfaces	Stereo mini jack audio in (3x), Stereo mini jack audio out, HDBaseT, BNC in, HDMI in, DVI in, VGA out, VGA in, Ethernet interface (100 Base-TX / 10 Base-T), RS-232C, USB 2.0 Type B
nterfaces	
	VGA out, VGA in, Ethernet interface (100 Base-TX / 10 Base-T), RS-232C, USB 2.0 Type B
Interfaces Epson iProjection App ADVANCED FEATURES	VGA out, VGA in, Ethernet interface (100 Base-TX / 10 Base-T), RS-232C, USB 2.0 Type B (Service Only), HD-SDI, Wireless LAN b/g/n (2.4GHz) (optional)
Epson iProjection App	VGA out, VGA in, Ethernet interface (100 Base-TX / 10 Base-T), RS-232C, USB 2.0 Type B (Service Only), HD-SDI, Wireless LAN b/g/n (2.4GHz) (optional)
Epson iProjection App	VGA out, VGA in, Ethernet interface (100 Base-TX / 10 Base-T), RS-232C, USB 2.0 Type B (Service Only), HD-SDI, Wireless LAN b/g/n (2.4GHz) (optional) Ad-Hoc / Infrastructure
Epson iProjection App ADVANCED FEATURES Security	VGA out, VGA in, Ethernet interface (100 Base-TX / 10 Base-T), RS-232C, USB 2.0 Type B (Service Only), HD-SDI, Wireless LAN b/g/n (2.4GHz) (optional) Ad-Hoc / Infrastructure Kensington lock, Security bar, Wireless LAN unit lock, Wireless LAN security, Password protection
Epson iProjection App	VGA out, VGA in, Ethernet interface (100 Base-TX / 10 Base-T), RS-232C, USB 2.0 Type B (Service Only), HD-SDI, Wireless LAN b/g/n (2.4GHz) (optional) Ad-Hoc / Infrastructure Kensington lock, Security bar, Wireless LAN unit lock, Wireless LAN security, Password protection 4K enhancement, Absolute Black, Auto Calibration, Customizable user logo, Frame
Epson iProjection App ADVANCED FEATURES Security Other features	VGA out, VGA in, Ethernet interface (100 Base-TX / 10 Base-T), RS-232C, USB 2.0 Type B (Service Only), HD-SDI, Wireless LAN b/g/n (2.4GHz) (optional) Ad-Hoc / Infrastructure Kensington lock, Security bar, Wireless LAN unit lock, Wireless LAN security, Password protection 4K enhancement, Absolute Black, Auto Calibration, Customizable user logo, Frame interpolation, Integrated camera for image calibration & image capture, Lens position memory
Epson iProjection App ADVANCED FEATURES Security Other features //ideo Color Modes	VGA out, VGA in, Ethernet interface (100 Base-TX / 10 Base-T), RS-232C, USB 2.0 Type B (Service Only), HD-SDI, Wireless LAN b/g/n (2.4GHz) (optional) Ad-Hoc / Infrastructure Kensington lock, Security bar, Wireless LAN unit lock, Wireless LAN security, Password protection 4K enhancement, Absolute Black, Auto Calibration, Customizable user logo, Frame interpolation, Integrated camera for image calibration & image capture, Lens position memory Cinema, Dynamic, Presentation, DICOM SIM, Multi Projection, BT709
Epson iProjection App ADVANCED FEATURES Security Other features Video Color Modes Projector control	VGA out, VGA in, Ethernet interface (100 Base-TX / 10 Base-T), RS-232C, USB 2.0 Type B (Service Only), HD-SDI, Wireless LAN b/g/n (2.4GHz) (optional) Ad-Hoc / Infrastructure Kensington lock, Security bar, Wireless LAN unit lock, Wireless LAN security, Password protection 4K enhancement, Absolute Black, Auto Calibration, Customizable user logo, Frame interpolation, Integrated camera for image calibration & image capture, Lens position memory
Epson iProjection App ADVANCED FEATURES Security Other features /ideo Color Modes /rojector control SENERAL	VGA out, VGA in, Ethernet interface (100 Base-TX / 10 Base-T), RS-232C, USB 2.0 Type B (Service Only), HD-SDI, Wireless LAN b/g/n (2.4GHz) (optional) Ad-Hoc / Infrastructure Kensington lock, Security bar, Wireless LAN unit lock, Wireless LAN security, Password protection 4K enhancement, Absolute Black, Auto Calibration, Customizable user logo, Frame interpolation, Integrated camera for image calibration & image capture, Lens position memory Cinema, Dynamic, Presentation, DICOM SIM, Multi Projection, BT709 via: AMX, Crestron, Extron
Epson iProjection App ADVANCED FEATURES Security Other features /ideo Color Modes /rojector control SENERAL	VGA out, VGA in, Ethernet interface (100 Base-TX / 10 Base-T), RS-232C, USB 2.0 Type B (Service Only), HD-SDI, Wireless LAN b/g/n (2.4GHz) (optional) Ad-Hoc / Infrastructure Kensington lock, Security bar, Wireless LAN unit lock, Wireless LAN security, Password protection 4K enhancement, Absolute Black, Auto Calibration, Customizable user logo, Frame interpolation, Integrated camera for image calibration & image capture, Lens position memory Cinema, Dynamic, Presentation, DICOM SIM, Multi Projection, BT709 via: AMX, Crestron, Extron
Epson iProjection App ADVANCED FEATURES Security Other features /ideo Color Modes Projector control SENERAL	VGA out, VGA in, Ethernet interface (100 Base-TX / 10 Base-T), RS-232C, USB 2.0 Type B (Service Only), HD-SDI, Wireless LAN b/g/n (2.4GHz) (optional) Ad-Hoc / Infrastructure Kensington lock, Security bar, Wireless LAN unit lock, Wireless LAN security, Password protection 4K enhancement, Absolute Black, Auto Calibration, Customizable user logo, Frame interpolation, Integrated camera for image calibration & image capture, Lens position memory Cinema, Dynamic, Presentation, DICOM SIM, Multi Projection, BT709 via: AMX, Crestron, Extron
Epson iProjection App ADVANCED FEATURES Security Other features Video Color Modes Projector control SENERAL Power consumption	VGA out, VGA in, Ethernet interface (100 Base-TX / 10 Base-T), RS-232C, USB 2.0 Type B (Service Only), HD-SDI, Wireless LAN b/g/n (2.4GHz) (optional) Ad-Hoc / Infrastructure Kensington lock, Security bar, Wireless LAN unit lock, Wireless LAN security, Password protection 4K enhancement, Absolute Black, Auto Calibration, Customizable user logo, Frame interpolation, Integrated camera for image calibration & image capture, Lens position memory Cinema, Dynamic, Presentation, DICOM SIM, Multi Projection, BT709 via: AMX, Crestron, Extron
Epson iProjection App ADVANCED FEATURES Security Other features Video Color Modes Projector control SENERAL Power consumption Supply Voltage	VGA out, VGA in, Ethernet interface (100 Base-TX / 10 Base-T), RS-232C, USB 2.0 Type B (Service Only), HD-SDI, Wireless LAN b/g/n (2.4GHz) (optional) Ad-Hoc / Infrastructure Kensington lock, Security bar, Wireless LAN unit lock, Wireless LAN security, Password protection 4K enhancement, Absolute Black, Auto Calibration, Customizable user logo, Frame interpolation, Integrated camera for image calibration & image capture, Lens position memory Cinema, Dynamic, Presentation, DICOM SIM, Multi Projection, BT709 via: AMX, Crestron, Extron 1,024 Watt, 647 Watt (economy), 0.3 Watt (standby), On mode power consumption as defined in JBMS-84 938 Watt
Epson iProjection App ADVANCED FEATURES Security Other features Projector control SENERAL Power consumption Supply Voltage Product dimensions	VGA out, VGA in, Ethernet interface (100 Base-TX / 10 Base-T), RS-232C, USB 2.0 Type B (Service Only), HD-SDI, Wireless LAN b/g/n (2.4GHz) (optional) Ad-Hoc / Infrastructure Kensington lock, Security bar, Wireless LAN unit lock, Wireless LAN security, Password protection 4K enhancement, Absolute Black, Auto Calibration, Customizable user logo, Frame interpolation, Integrated camera for image calibration & image capture, Lens position memory Cinema, Dynamic, Presentation, DICOM SIM, Multi Projection, BT709 via: AMX, Crestron, Extron 1,024 Watt, 647 Watt (economy), 0.3 Watt (standby), On mode power consumption as defined in JBMS-84 938 Watt AC 100 V - 240 V, 50 Hz - 60 Hz
Epson iProjection App ADVANCED FEATURES Security Other features Projector control SENERAL Power consumption Supply Voltage Product dimensions Product weight	VGA out, VGA in, Ethernet interface (100 Base-TX / 10 Base-T), RS-232C, USB 2.0 Type B (Service Only), HD-SDI, Wireless LAN b/g/n (2.4GHz) (optional) Ad-Hoc / Infrastructure Kensington lock, Security bar, Wireless LAN unit lock, Wireless LAN security, Password protection 4K enhancement, Absolute Black, Auto Calibration, Customizable user logo, Frame interpolation, Integrated camera for image calibration & image capture, Lens position memory Cinema, Dynamic, Presentation, DICOM SIM, Multi Projection, BT709 via: AMX, Crestron, Extron 1,024 Watt, 647 Watt (economy), 0.3 Watt (standby), On mode power consumption as defined in JBMS-84 938 Watt AC 100 V - 240 V, 50 Hz - 60 Hz 586 x 492 x 211 mm (Width x Depth x Height)
Epson iProjection App DVANCED FEATURES iecurity Other features iideo Color Modes Projector control ENERAL Power consumption Supply Voltage Product dimensions Product dimensions Product weight loise Level	VGA out, VGA in, Ethernet interface (100 Base-TX / 10 Base-T), RS-232C, USB 2.0 Type B (Service Only), HD-SDI, Wireless LAN b/g/n (2.4GHz) (optional) Ad-Hoc / Infrastructure Kensington lock, Security bar, Wireless LAN unit lock, Wireless LAN security, Password protection 4K enhancement, Absolute Black, Auto Calibration, Customizable user logo, Frame interpolation, Integrated camera for image calibration & image capture, Lens position memory Cinema, Dynamic, Presentation, DICOM SIM, Multi Projection, BT709 via: AMX, Crestron, Extron 1,024 Watt, 647 Watt (economy), 0.3 Watt (standby), On mode power consumption as defined in JBMS-84 938 Watt AC 100 V - 240 V, 50 Hz - 60 Hz 586 x 492 x 211 mm (Width x Depth x Height) 24.1 kg
Epson iProjection App ADVANCED FEATURES Security Other features Projector control SENERAL Prower consumption Supply Voltage Product dimensions Product weight Noise Level Supported Temperature	VGA out, VGA in, Ethernet interface (100 Base-TX / 10 Base-T), RS-232C, USB 2.0 Type B (Service Only), HD-SDI, Wireless LAN b/g/n (2.4GHz) (optional) Ad-Hoc / Infrastructure Kensington lock, Security bar, Wireless LAN unit lock, Wireless LAN security, Password protection 4K enhancement, Absolute Black, Auto Calibration, Customizable user logo, Frame interpolation, Integrated camera for image calibration & image capture, Lens position memory Cinema, Dynamic, Presentation, DICOM SIM, Multi Projection, BT709 via: AMX, Crestron, Extron 1,024 Watt, 647 Watt (economy), 0.3 Watt (standby), On mode power consumption as defined in JBMS-84 938 Watt AC 100 V - 240 V, 50 Hz - 60 Hz 586 x 492 x 211 mm (Width x Depth x Height) 24.1 kg Normal: 40 dB (A) - Economy: 32 dB (A) (4K enhancement OFF)
Epson iProjection App ADVANCED FEATURES Security Other features Projector control SENERAL Power consumption Supply Voltage Product dimensions Product weight Noise Level Supported Temperature Supported Humidity	VGA out, VGA in, Ethernet interface (100 Base-TX / 10 Base-T), RS-232C, USB 2.0 Type B (Service Only), HD-SDI, Wireless LAN b/g/n (2.4GHz) (optional) Ad-Hoc / Infrastructure Kensington lock, Security bar, Wireless LAN unit lock, Wireless LAN security, Password protection 4K enhancement, Absolute Black, Auto Calibration, Customizable user logo, Frame interpolation, Integrated camera for image calibration & image capture, Lens position memory Cinema, Dynamic, Presentation, DICOM SIM, Multi Projection, BT709 via: AMX, Crestron, Extron 1,024 Watt, 647 Watt (economy), 0.3 Watt (standby), On mode power consumption as defined in JBMS-84 938 Watt AC 100 V - 240 V, 50 Hz - 60 Hz 586 x 492 x 211 mm (Width x Depth x Height) 24.1 kg Normal: 40 dB (A) - Economy: 32 dB (A) (4K enhancement OFF) Storage -10° C - 60° C
Epson iProjection App ADVANCED FEATURES Security Other features Projector control SENERAL Power consumption Supply Voltage Product dimensions Product weight Noise Level Supported Temperature Supported Humidity Included Software	VGA out, VGA in, Ethernet interface (100 Base-TX / 10 Base-T), RS-232C, USB 2.0 Type B (Service Only), HD-SDI, Wireless LAN b/g/n (2.4GHz) (optional) Ad-Hoc / Infrastructure Kensington lock, Security bar, Wireless LAN unit lock, Wireless LAN security, Password protection 4K enhancement, Absolute Black, Auto Calibration, Customizable user logo, Frame interpolation, Integrated camera for image calibration & image capture, Lens position memory Cinema, Dynamic, Presentation, DICOM SIM, Multi Projection, BT709 via: AMX, Crestron, Extron 1,024 Watt, 647 Watt (economy), 0.3 Watt (standby), On mode power consumption as defined in JBMS-84 938 Watt AC 100 V - 240 V, 50 Hz - 60 Hz 586 x 492 x 211 mm (Width x Depth x Height) 24.1 kg Normal: 40 dB (A) - Economy: 32 dB (A) (4K enhancement OFF) Storage -10° C - 60° C Operation 20% - 80%, Storage 10% - 90%
Epson iProjection App ADVANCED FEATURES Security Other features //ideo Color Modes Projector control SENERAL Power consumption Supply Voltage Product dimensions Product dimensions Product weight doise Level Supported Temperature Supported Humidity included Software Options	VGA out, VGA in, Ethernet interface (100 Base-TX / 10 Base-T), RS-232C, USB 2.0 Type B (Service Only), HD-SDI, Wireless LAN b/g/n (2.4GHz) (optional) Ad-Hoc / Infrastructure Kensington lock, Security bar, Wireless LAN unit lock, Wireless LAN security, Password protection 4K enhancement, Absolute Black, Auto Calibration, Customizable user logo, Frame interpolation, Integrated camera for image calibration & image capture, Lens position memory Cinema, Dynamic, Presentation, DICOM SIM, Multi Projection, BT709 via: AMX, Crestron, Extron 1,024 Watt, 647 Watt (economy), 0.3 Watt (standby), On mode power consumption as defined in JBMS-84 938 Watt AC 100 V - 240 V, 50 Hz - 60 Hz 586 x 492 x 211 mm (Width x Depth x Height) 24.1 kg Normal: 40 dB (A) - Economy: 32 dB (A) (4K enhancement OFF) Storage -10° C - 60° C Operation 20% - 80%, Storage 10% - 90% EasyMP Monitor, EasyMP Multi PC Projection HDBaseT Transmitter, Quick wireless USB key, Wireless LAN unit
Epson iProjection App ADVANCED FEATURES Security Other features //ideo Color Modes Projector control SENERAL Power consumption Supply Voltage Product dimensions Product dimensions Product weight doise Level Supported Temperature Supported Humidity included Software Options	VGA out, VGA in, Ethernet interface (100 Base-TX / 10 Base-T), RS-232C, USB 2.0 Type B (Service Only), HD-SDI, Wireless LAN b/g/n (2.4GHz) (optional) Ad-Hoc / Infrastructure Kensington lock, Security bar, Wireless LAN unit lock, Wireless LAN security, Password protection 4K enhancement, Absolute Black, Auto Calibration, Customizable user logo, Frame interpolation, Integrated camera for image calibration & image capture, Lens position memory Cinema, Dynamic, Presentation, DICOM SIM, Multi Projection, BT709 via: AMX, Crestron, Extron 1,024 Watt, 647 Watt (economy), 0.3 Watt (standby), On mode power consumption as defined in JBMS-84 938 Watt AC 100 V - 240 V, 50 Hz - 60 Hz 586 x 492 x 211 mm (Width x Depth x Height) 24.1 kg Normal: 40 dB (A) - Economy: 32 dB (A) (4K enhancement OFF) Storage -10° C - 60° C Operation 20% - 80%, Storage 10% - 90% EasyMP Monitor, EasyMP Multi PC Projection HDBaseT Transmitter, Quick wireless USB key, Wireless LAN unit Boardroom, Large Meeting Room / Auditorium, Projection Mapping, Rental / Staging, Signage
Epson iProjection App ADVANCED FEATURES Security Other features //ideo Color Modes Projector control SENERAL Power consumption Supply Voltage Product dimensions Product dimensions Product weight Noise Level Supported Temperature Supported Humidity Included Software Options Room Type / Application	VGA out, VGA in, Ethernet interface (100 Base-TX / 10 Base-T), RS-232C, USB 2.0 Type B (Service Only), HD-SDI, Wireless LAN b/g/n (2.4GHz) (optional) Ad-Hoc / Infrastructure Kensington lock, Security bar, Wireless LAN unit lock, Wireless LAN security, Password protection 4K enhancement, Absolute Black, Auto Calibration, Customizable user logo, Frame interpolation, Integrated camera for image calibration & image capture, Lens position memory Cinema, Dynamic, Presentation, DICOM SIM, Multi Projection, BT709 via: AMX, Crestron, Extron 1,024 Watt, 647 Watt (economy), 0.3 Watt (standby), On mode power consumption as defined in JBMS-84 938 Watt AC 100 V - 240 V, 50 Hz - 60 Hz 586 x 492 x 211 mm (Width x Depth x Height) 24.1 kg Normal: 40 dB (A) - Economy: 32 dB (A) (4K enhancement OFF) Storage -10° C - 60° C Operation 20% - 80%, Storage 10% - 90% EasyMP Monitor, EasyMP Multi PC Projection HDBaseT Transmitter, Quick wireless USB key, Wireless LAN unit Boardroom, Large Meeting Room / Auditorium, Projection Mapping, Rental / Staging, Signage / Retail, Visitor Attraction
Epson iProjection App ADVANCED FEATURES Security Dther features Video Color Modes Projector control GENERAL Power consumption Supply Voltage Product dimensions Product dimensions Product weight Noise Level Supported Temperature Supported Humidity Included Software Options Room Type / Application Positioning	VGA out, VGA in, Ethernet interface (100 Base-TX / 10 Base-T), RS-232C, USB 2.0 Type B (Service Only), HD-SDI, Wireless LAN b/g/n (2.4GHz) (optional) Ad-Hoc / Infrastructure Kensington lock, Security bar, Wireless LAN unit lock, Wireless LAN security, Password protection 4K enhancement, Absolute Black, Auto Calibration, Customizable user logo, Frame interpolation, Integrated camera for image calibration & image capture, Lens position memory Cinema, Dynamic, Presentation, DICOM SIM, Multi Projection, BT709 via: AMX, Crestron, Extron 1,024 Watt, 647 Watt (economy), 0.3 Watt (standby), On mode power consumption as defined in JBMS-84 938 Watt AC 100 V - 240 V, 50 Hz - 60 Hz 586 x 492 x 211 mm (Width x Depth x Height) 24.1 kg Normal: 40 dB (A) - Economy: 32 dB (A) (4K enhancement OFF) Storage -10° C - 60° C Operation 20% - 80%, Storage 10% - 90% EasyMP Monitor, EasyMP Multi PC Projection HDBaseT Transmitter, Quick wireless USB key, Wireless LAN unit Boardroom, Large Meeting Room / Auditorium, Projection Mapping, Rental / Staging, Signage / Retail, Visitor Attraction Ceiling Mounted, Flying Frame
Epson iProjection App ADVANCED FEATURES Security Other features /ideo Color Modes Projector control SENERAL Power consumption Supply Voltage Product dimensions Product dimensi	VGA out, VGA in, Ethernet interface (100 Base-TX / 10 Base-T), RS-232C, USB 2.0 Type B (Service Only), HD-SDI, Wireless LAN b/g/n (2.4GHz) (optional) Ad-Hoc / Infrastructure Kensington lock, Security bar, Wireless LAN unit lock, Wireless LAN security, Password protection 4K enhancement, Absolute Black, Auto Calibration, Customizable user logo, Frame interpolation, Integrated camera for image calibration & image capture, Lens position memory Cinema, Dynamic, Presentation, DICOM SIM, Multi Projection, BT709 via: AMX, Crestron, Extron 1,024 Watt, 647 Watt (economy), 0.3 Watt (standby), On mode power consumption as defined in JBMS-84 938 Watt AC 100 V - 240 V, 50 Hz - 60 Hz 586 x 492 x 211 mm (Width x Depth x Height) 24.1 kg Normal: 40 dB (A) - Economy: 32 dB (A) (4K enhancement OFF) Storage -10° C - 60° C Operation 20% - 80%, Storage 10% - 90% EasyMP Monitor, EasyMP Multi PC Projection HDBaseT Transmitter, Quick wireless USB key, Wireless LAN unit Boardroom, Large Meeting Room / Auditorium, Projection Mapping, Rental / Staging, Signage / Retail, Visitor Attraction
Epson iProjection App ADVANCED FEATURES Security	VGA out, VGA in, Ethernet interface (100 Base-TX / 10 Base-T), RS-232C, USB 2.0 Type B (Service Only), HD-SDI, Wireless LAN b/g/n (2.4GHz) (optional) Ad-Hoc / Infrastructure Kensington lock, Security bar, Wireless LAN unit lock, Wireless LAN security, Password protection 4K enhancement, Absolute Black, Auto Calibration, Customizable user logo, Frame interpolation, Integrated camera for image calibration & image capture, Lens position memory Cinema, Dynamic, Presentation, DICOM SIM, Multi Projection, BT709 via: AMX, Crestron, Extron 1,024 Watt, 647 Watt (economy), 0.3 Watt (standby), On mode power consumption as defined in JBMS-84 938 Watt AC 100 V - 240 V, 50 Hz - 60 Hz 586 x 492 x 211 mm (Width x Depth x Height) 24.1 kg Normal: 40 dB (A) - Economy: 32 dB (A) (4K enhancement OFF) Storage -10° C - 60° C Operation 20% - 80%, Storage 10% - 90% EasyMP Monitor, EasyMP Multi PC Projection HDBaseT Transmitter, Quick wireless USB key, Wireless LAN unit Boardroom, Large Meeting Room / Auditorium, Projection Mapping, Rental / Staging, Signage / Retail, Visitor Attraction Ceiling Mounted, Flying Frame

EB-L1555U

WHAT'S IN THE BOX

- Remote control incl. batteries
- Quick Start Guide
- Power and signal cable (3 m)

EPSON[®]

- Computer cable
- Cable cover
- CD Manual

OPTIONAL ACCESSORIES

- Wireless LAN Adapter ELPAP10 V12H731P01
- HDBaseT Transmitter ELPHD01 V12H547041
- Ceiling Mount ELPMB48 High EB-G7000/L1000 V12H803010
- Ceiling Mount ELPMB47 Low EB-G7000/L1000 V12H802010
- Air Filter ELPAF51
 V13H134A51
- Stacking Frame ELPMB59 L1000 Series (EVO) V12H996B59

OPTIONAL LENSES

- Lens ELPLU03S L & G Series ST off axis 1 V12H004UA3
- Lens ELPLM15 Mid Throw L1500/L1700 Series V12H004M0F
- Lens ELPLW06 L1500U/1505U wide zoom 2 V12H004W06
- Lens ELPLW05 G7000 & L1000 Series wide zoom 1 V12H004W05
- Lens ELPLU04 G7000 & L1000 Series ST off axis 2 V12H004U04
- Lens ELPLU03 G7000 & L1000 Series ST off axis 1 V12H004U03
- Lens ELPLM11 Mid throw 4 G7000/L1000 series V12H004M0B
- Lens ELPLM10 Mid throw 3 G7000/L1000 series V12H004M0A
- Lens ELPLL08 Long throw G7000/L1000 series V12H004L08
- Lens ELPLX02 UST Lens L1500/1700 Series V12H004X02
- Lens ELPLW08 Wide throw V12H004W08
- 1. Laser life of up to 83,000 hours in custom mode.

